

## Cat6a RJ45 Plug - MPTL, Shielded, 100W High-Power PoE & PoE++, Zinc Die-Cast, Black, TAA

MODEL NUMBER: N238-P01-MPTL-A



Cat6a RJ45 shielded plug connects devices where installing a wall plate isn't practical or where outlets, jacks and patch cords must be plenum rated.

### Features

**RJ45 Cat6a Plug Designed for Field Installation in Above-Ceiling Applications** This Cat6a RJ45 shielded plug simplifies the installation of devices in an above-ceiling application where installing a face plate isn't practical or where outlets, jacks and patch cords must be plenum rated. Modular Plug Terminated Link (MPTL) topology allows a Cat6a cable to be terminated to the N238-P01-MPTL-A plug, which then connects to a Type 3 or Type 4 PoE device, such as a WAP (Wireless Access Point) or surveillance camera.

**Delivers Type 3 and Type 4 Power over Ethernet to Security Cameras and Other PoE Devices** Because this Cat6a shielded plug supports PoE++/4PPoE and High-Power PoE applications, it helps deliver power to PoE devices requiring up to 100 watts, such as security cameras, access control devices and large-screen displays for digital signage. This saves you the expense and effort of purchasing, connecting and installing individual power supplies for each device. It also helps you install PoE devices in areas far away from AC outlets, including ceilings.

**Assembles Easily with No Special Tools Required** The die-cast zinc plug is made for fast, reliable terminations in the field with just a wire stripper/cutter. It accommodates 22–26 AWG solid or stranded cabling and 6.5–8.5 mm cable jacket diameters. Ideal for assembling high-performance patch cords in a hurry, the N238-P01-MPTL-A can be re-terminated as many as 20 times. An IDC cap and a dust cap are included.

**TAA-Compliant for GSA Schedule Purchases** The N238-P01-MPTL-A is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

## Specifications

### OVERVIEW

UPC Code

037332247926

### Highlights

- Designed for fast, reliable field terminations with no special tools in PoE applications
- Supports PoE++ and high-power PoE to save you expense of powering PoE devices individually
- Accommodates 22–26 AWG solid or stranded cabling in 6.5–8.5 mm diameters
- Versatile and durable die-cast zinc plug can be re-terminated as many as 20 times
- Complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Applications

- Connect network components, such as WAPs and security cameras, in above-ceiling and plenum-rated PoE applications up to 100W

### Package Includes

- N238-P01-MPTL-A Cat6a RJ45 Plug
- IDC cap
- Dust cap
- Quick Start Guide



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                      |                                                               |
|--------------------------------------|---------------------------------------------------------------|
| Technology                           | Cat6a; PoE                                                    |
| <b>INPUT</b>                         |                                                               |
| Plug Type                            | RJ45                                                          |
| <b>PHYSICAL</b>                      |                                                               |
| Color                                | Black                                                         |
| Cable Outer Diameter (OD)            | 6.5mm to 8.5mm                                                |
| Unit Dimensions (hwd / in.)          | 0.77 x 0.59" x 2.3"                                           |
| Unit Dimensions (hwd / cm)           | 1.95 x 1.5 x 5.83                                             |
| Unit Dimensions (hwd / mm)           | 19.5 x 15 x 58.3                                              |
| <b>ENVIRONMENTAL</b>                 |                                                               |
| Operating Temperature Range          | 14 ~ 140F (-10 ~ 60C)                                         |
| Storage Temperature Range            | -40 ~ 154F (-40 ~ 68C)                                        |
| Relative Humidity                    | 10% ~ 90% RH (Non-Condensing)                                 |
| <b>CONNECTIONS</b>                   |                                                               |
| PoE Capability                       | 100W (802.3bt); 15.4W (802.3af); 30W (802.3at); 60W (802.3bt) |
| PoE Power Budget (Watts)             | 100                                                           |
| Side A - Connector 1                 | RJ45 (MALE)                                                   |
| Side B - Connector 1                 | 110 IDC                                                       |
| PoE Type                             | Type 3 PoE++/UPoE (60W, IEEE 802.3bt)                         |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                                               |
| Recommended Category Cable           | CAT6A                                                         |
| DC Current Rating                    | 1.5A                                                          |
| Cable Compatibility                  | Accommodates 22 to 26 AWG Solid or Stranded Cabling           |
| <b>WARRANTY</b>                      |                                                               |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty                                     |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>