

Heavy-Duty Power Extension Cord, 20A, 12AWG (Left Angle IEC-320-C19 to IEC-320-C20), 2-ft.

MODEL NUMBER: P036-002-19LA



Highlights

- C19 Left Angle to C20 Power Cord, 2 ft.
- 12AWG (3.31mm²) x 3C, 20 Amp
 Rated, 100-250V
- RoHS Approved

Package Includes C19 Left Angle to C20 Power Cable, 2 ft.

Description

Use Tripp Lite's P036-002-19LA in server applications that require a higher rated, heavier gauge cable. C19 Left Angle to C20 connectors, 3 x 12ga (3.31mm²) conductors, 20AMP rated, 100-250V - ideal for use with Blade Server Chassis.

Features

- Molded, Heavy-Duty Power Cord, 2 ft.
- IEC-60320-C19 Left Angle to IEC-60320-C20
- 12AWG (3.31mm²) x 3C, SJTW, 20A, 100-250Volt
- RoHS Approved

Specifications

OVERVIEW		
UPC Code	037332156501	
INPUT		
Cable Length (ft.)	2	
Cable Length (m)	0.6	
PHYSICAL		
Color	Black	
Power Cord Jacket Type	SJTW	





	+	
Shipping Dimensions (hwd / cm)	15.24 x 19.81 x 23.88	
Shipping Dimensions (hwd / in.)	6.00 x 7.80 x 9.40	
Shipping Weight (kg)	2.36	
Shipping Weight (lbs.)	5.20	
Wire Gauge (AWG)	12	
Wire Gauge (OD - mm²)	3.31mm²	
CONNECTIONS		
Side A - Connector 1	IEC-320-C20	
Side B - Connector 1	IEC-320-C19 - LEFT ANGLE	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies