

TAA-Compliant 45U SmartRack 2-Post Open Frame Rack - Organize and Secure Network Rack Equipment

MODEL NUMBER: **SR2POSTAA**



Highlights

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 45U 2-post open frame rack
- Black aluminum with 12-24 threaded and numbered mounting holes
- Toolless button holes to accept PDUs or cable managers

Description

Tripp Lite's TAA Compliant 45U 2-Post SmartRack Open Frame Rack is an economical way to accommodate 45U of rack space for 19-inch rackmount applications in limited spaces that do not require a lockable enclosure. Its heavy-duty, aluminum construction can safely support 800 lbs. of rackmount equipment, and its open design provides easy access to equipment and cabling. The black, textured powder coat finish makes it resistant to scratching while giving it a "classic," attractive appearance. The SR2POSTAA is easy to install due to a self-squaring design combined with 12-24 threaded and numbered mounting positions along with bolt down provisions. It provides toolless button-hole mounting for vertical PDUs and cable managers. In high-density environments, multiple units can be bolted together side by side for easy expansion or customization. The SR2POSTAA is in full TAA (Trade Agreements Act) compliance for easy addition to GSA Schedule contracts and other government contracts, as well as EIA-compliant for vendor-neutral compatibility with 19-inch rackmount equipment. It is backed by a 5-year warranty.

Features

- Supports 800lbs of rackmount equipment
- Textured powder coat finish
- Heavy Duty Aluminum construction
- 12-24 threaded and numbered mounting positions
- Bolt down provisions
- Toolless button holes to accept PDUs or cable managers
- Self squaring design
- Black finish
- Easy assembly



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Specifications

OVERVIEW	
UPC Code	037332154040
PHYSICAL	
Rack Height	45U
Maximum Device Depth (in.)	48
Maximum Device Depth (cm)	121.92
Shipping Dimensions (hwd / in.)	4.53 x 6.50 x 87.99
Shipping Dimensions (hwd / cm)	11.51 x 16.51 x 223.49
Shipping Weight (lbs.)	33.10
Shipping Weight (kg)	15.01
Unit Dimensions (hwd / in.)	84 x 20.3 x 4.75
Unit Dimensions (hwd / cm)	213.36 x 51.56 x 12.07
Integrated Keyhole Mounting Slots	Toolless button holes to accept PDUs or cable managers
Color	Black
Weight Capacity - Stationary (lbs.)	800
EIA Mounting Rails	12-24 threaded and numbered mounting holes
Weight Capacity - Stationary (kg)	363
Maximum Device Depth (mm)	1,219
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>