

Specification Sheet

Part Number: 170-03120



Braided Sleeving, Expandable, Fray Resistant, Flame Retardant, 1" Dia, PET, Black, 250 ft/bulk reel

Article Number	170-03120
Type	BSSCFR100B
Color	Black (BK)
Features & Benefits	•Provides fuller coverage and a medium-to-high abrasion resistance. •Expands for ease of installation in either the shop or the field. •Increased braid density coverage provides higher level of abrasion resistance without losing flexibility. •Contains white tracer thread for simple identification of flame retardancy. •Treated yarns extinguish quickly and reduces potential flame spread to surrounding components. •Cuts with ordinary scissors without fraying ends.
Quantity Per	reel

Product Description	This protective sleeving is self-extinguishing and can be cut with sharp scissors instead of a hot knife for fray-resistant ends. Readily used in the automotive, audiovisual, industrial, wire, cable and computer industries where flame retardancy is required to reduce the likelihood of ignition and/or reduce the rate of flame spread. It is suited for situations where access to a hot knife is either impractical or impossible.
Short Description	Braided Sleeving, Expandable, Fray Resistant, Flame Retardant, 1" Dia, PET, Black, 250 ft/bulk reel
Global Part Name	BSSCFR100B-PET-BK
Length L (Imperial)	250.0
Length L (Metric)	76.2
Bundle Diameter Min (Imperial)	0.75
Bundle Diameter Min (Metric)	19.1
Bundle Diameter Max (Imperial)	1.2
Bundle Diameter Max (Metric)	30.5
Diameter D (imperial)	1.2
Diameter D (metric)	30.5
Nominal Diameter (Imperial)	1
Nominal Diameter (Metric)	25.4

Material	Polyester (PET)
Material Shortcut	PET
Flammability	UL VW-1 Mil-202
Halogen free	Yes
Operating Temperature (Metric)	-94°F to +257°F (-70°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	250
Package Quantity (Metric)	76.20
Customs Number	5808100000
Weight (Metric)	1.4
Weight (Imperial)	3.1