


Specification Sheet

Part Number: 184-15155



High Density Slotted Wall Wiring Duct, 1.5" x 1.5", Non-Adhesive, PVC, White, 120ft/Carton

Article Number	184-15155
----------------	-----------

Type	SLHD1.5X1.5
------	-------------

Color	White (WH)
-------	------------

Features & Benefits	•Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance. •Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation. •Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation. •Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.
---------------------	---

Quantity Per	carton
--------------	--------

Product Description	HellermannTyton Pro-Duct High-Density, Slotted-Wall Wiring Duct features narrow fingers equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.
---------------------	--

Short Description	High Density Slotted Wall Wiring Duct, 1.5" x 1.5", Non-Adhesive, PVC, White, 120ft/Carton
Global Part Name	SLHD1.5X1.5-PVC-WH
Technical Description	Non-Adhesive
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	1.5
Width W (Metric)	38.1
Height H (Imperial)	1.57
Height H (Metric)	39.9
Mounting Hole Centers (Imperial)	2.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	Self-Extinguishing
Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)

Reach Complaint(Article 33)

No

ROHS Complaint

Yes

Certification/Specification WEB

UL EN 50085-2-3_1A CSA EN 50085-1:2005 + A1:2013

UL Recognized (US)

Yes

Package Quantity(Imperial)

120

Package Quantity (Metric)

36.58

Customs Number

3925900000