

Specification Sheet

Part Number: 184-23004



High Density Slotted Wall Wiring Duct, 2" x 3", Non-Adhesive, PVC, Gray, 120ft/Carton

Article Number	184-23004
----------------	-----------

Type	SLHD2X3
------	---------

Color	Gray (GY)
-------	-----------

Features & Benefits	•Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance. •Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation. •Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation. •Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.
---------------------	---

Quantity Per	carton
--------------	--------

Product Description	HellermannTyton Pro-Duct High-Density, Slotted-Wall Wiring Duct features narrow fingers equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.
---------------------	--

Short Description	High Density Slotted Wall Wiring Duct, 2" x 3", Non-Adhesive, PVC, Gray, 120ft/Carton
Global Part Name	SLHD2X3-PVC-GY
Technical Description	Non-Adhesive
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	2.0
Width W (Metric)	50.8
Height H (Imperial)	3.07
Height H (Metric)	77.9
Mounting Hole Centers (Imperial)	2.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	Self-Extinguishing
Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)

Reach Complaint(Article 33)

No

ROHS Complaint

Yes

Certification/Specification WEB

UL CSA EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A

UL Recognized (US)

Yes

Package Quantity(Imperial)

120

Package Quantity (Metric)

36.58

Customs Number

3925900000