

Specification Sheet

Part Number: 156-00067



Heavy Duty Cable Tie/Fir Tree Mount, 15" x .3" , .04"—.25" Panel Thick, PA66HIRHSUV, Black, 100/pkg

Article Number	156-00067
Type	T120RFT9A
Color	Black (BK)
Features & Benefits	•Friction tab inside the fir tree allows the tie to sit in mount without falling out prior to installation. •Fir tree provides low insertion effort yet demonstrates high extraction resistance. •Disc feature prevents rattling in high-vibration applications and protects against debris ingress.
Quantity Per	bag
Product Description	HellermannTyton's fir tree mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

Short Description	Heavy Duty Cable Tie/Fir Tree Mount, 15" x .3", .04"—.25" Panel Thick, PA66HIRHSUV, Black, 100/pkg
Global Part Name	T120RFT9A-PA66HS/PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	120.0
Minimum Tensile Strength (Metric)	535
Length L (Imperial)	15.0
Length L (Metric)	380.0
Fixation Method	Fir Tree
Identification Plate Position	none
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.3
Width W (Metric)	7.6
Bundle Diameter Max (Imperial)	4.0
Bundle Diameter Max (Metric)	100.0
Height H (Imperial)	.07
Height H (Metric)	1.80

Panel Thickness Min(Imperial)	0.039
Panel Thickness Max(Imperial)	0.256
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	6.5
Mounting Hole Diameter D (Imperial)	0.34 - 0.36
Mounting Hole Diameter D (Metric)	8.7 - 9.2 mm
Mounting Hole Diameter D Min (Imperial)	0.34
Mounting Hole Diameter D Max (Imperial)	0.36
Mounting Hole Diameter D Max (Metric)	9.2
Disc Diameter(Metric)	21.6
Disc Diameter (Imperial)	0.85
Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV PA66HS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 HB

Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988
Content Unit(BMEcat)	pcs.