

Specification Sheet

Part Number: T18R9VOC2



Flame-Retardant Cable Tie, 4" Long, UL Rated, 18lb Tensile Strength, PA66V0, Natural, 100/pkg

|                     |                                                                                                                                                                                                                                                                                                                                          |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 111-00928                                                                                                                                                                                                                                                                                                                                |
| Type                | T18R                                                                                                                                                                                                                                                                                                                                     |
| Color               | Natural (NA)                                                                                                                                                                                                                                                                                                                             |
| Features & Benefits | <ul style="list-style-type: none"><li>•Feature a UL 94 V-0 rating to comply with low flame and smoke requirements.</li><li>•Inside serrations provide strong grip on cables and wire bundles.</li><li>•Easy application either manually or with a tensioning tool.</li><li>•Bent tail ensures a quick and simple installation.</li></ul> |
| Quantity Per        | bag                                                                                                                                                                                                                                                                                                                                      |

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | HellermannTyton's flame retardant cable ties meet the UL 94 V-0 flammability requirements. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                     |                                                                                               |
|-------------------------------------|-----------------------------------------------------------------------------------------------|
| Short Description                   | Flame-Retardant Cable Tie, 4" Long, UL Rated, 18lb Tensile Strength, PA66V0, Natural, 100/pkg |
| Global Part Name                    | T18R-PA66V0-NA                                                                                |
| Minimum Tensile Strength (Imperial) | 18.0                                                                                          |
| Minimum Tensile Strength (Metric)   | 80.0                                                                                          |
| Length L (Imperial)                 | 4.0                                                                                           |
| Length L (Metric)                   | 101.6                                                                                         |
| Identification Plate Position       | none                                                                                          |
| Releasable Closure                  | No                                                                                            |
| Tie Closure                         | plastic pawl                                                                                  |
| Variant                             | Inside Serrated                                                                               |
| Width W (Imperial)                  | 0.10                                                                                          |
| Width W (Metric)                    | 2.5                                                                                           |
| Bundle Diameter Min (Imperial)      | 0.12                                                                                          |
| Bundle Diameter Min (Metric)        | 3.0                                                                                           |
| Bundle Diameter Max (Imperial)      | 0.87                                                                                          |
| Bundle Diameter Max (Metric)        | 22.0                                                                                          |

|                                 |                                  |
|---------------------------------|----------------------------------|
| Thickness T (Metric)            | 1.0                              |
| Height H (Metric)               | 3.7                              |
| Material                        | Polyamide 6.6 V0 (PA66V0)        |
| Material Shortcut               | PA66V0                           |
| Flammability                    | UL 94 V0                         |
| Operating Temperature (Metric)  | -40°F to +185°F (-40°C to +85°C) |
| ROHS Complaint                  | Yes                              |
| Certification/Specification WEB | UL-ZODZ2.E64139                  |
| UL Recognized (US)              | Yes                              |
| UL Recognized (US and Canada)   | Yes                              |
| Package Quantity(Imperial)      | 100                              |
| Package Quantity (Metric)       | 100                              |
| Customs Number                  | 3926909988                       |

