

Specification Sheet

Part Number: T30R10C2



Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66, White, 100/pkg

Article Number	116-03019
Type	T30R
Color	White (WH)
Features & Benefits	• Inside serrations allow for strong grip on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Quantity Per	bag
Product Description	T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66, White, 100/pkg

Global Part Name	T30R-PA66-WH
Minimum Tensile Strength (Imperial)	30.0
Minimum Tensile Strength (Metric)	135.0
Length L (Imperial)	5.8
Length L (Metric)	147.32
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.14
Width W (Metric)	3.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.38
Bundle Diameter Max (Metric)	35.0
Thickness T (Metric)	1.1

Material	Polyamide 6.6 (PA66)	
Material Shortcut	PA66	
US MIL SPEC	MS3367-5-10	
SAE-AS33671		
Flammability		
UL 94 V2		Halogen free
Yes		Operating Temperature (Metric)
-40°F to +185°F (-40°C to +85°C)		ROHS Complaint
Yes		Certification/Specification WEB
UL-ZODZ2.E64139		UL Recognized (US)
Yes		UL Listed (US and Canada)
Yes		UL Recognized (US and Canada)
Yes		UL Listed (US
Yes		
Package Quantity(Imperial)	100	
Package Quantity (Metric)	100	
Customs Number	3926909988	

Content Unit(BMEcat)

pcs.

Weight (Metric)

0.7