

Specification Sheet

Part Number: T50L2M4



Cable Tie, 15.35" Long, UL Rated, 50lb Tensile Strength, PA66, Red, 1000/pkg

Article Number	111-05458
Type	T50L
Color	Red (RD)
Features & Benefits	•Engineered and manufactured for maximum performance and quality. •Made from 100% high-quality plastic to ensure efficient recycling. •Inside serration for a strong grip onto bundles. •Easy application either manually or with a tensioning tool. •Bent tail allows for simpler insertion.
Quantity Per	bag
Product Description	T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Cable Tie, 15.35" Long, UL Rated, 50lb Tensile Strength, PA66, Red, 1000/pkg
Global Part Name	T50L-PA66-RD
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	15.35
Length L (Metric)	389.89
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19
Width W (Metric)	4.8
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	4.3
Bundle Diameter Max (Metric)	109.2
Thickness T (Metric)	1.4

Material	Polyamide 6.6 (PA66)	
Material Shortcut	PA66	
US MIL SPEC	SAE-AS33671	
MS3367-2-2		
Flammability		
UL 94 V2	Halogen free	
Yes	Operating Temperature (Metric)	
-40°F to +185°F (-40°C to +85°C)	ROHS Complaint	
Yes	Certification/Specification WEB	
CAGE Code 53421 UL-ZODZ.E64139	UL Recognized (US)	
Yes	UL Listed (US and Canada)	
Yes	UL Recognized (US and Canada)	
Yes	UL Listed (US	
Yes		
Package Quantity(Imperial)	1000	
Package Quantity (Metric)	1000	

Customs Number

3926909988