

Specification Sheet

Part Number: T50R2M4



Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Red, 1000/pkg

Article Number	111-04868
Type	T50R
Color	Red (RD)
Features & Benefits	•Engineered and manufactured for maximum performance and quality. •Made from 100% high-quality plastic to ensure efficient recycling. •Inside serration for a strong grip onto bundles. •Easy application either manually or with a tensioning tool. •Bent tail allows for simpler insertion.
Quantity Per	bag

Product Description	T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
---------------------	--

Short Description	Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Red, 1000/pkg
Global Part Name	T50R-PA66-RD
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	8.0
Length L (Metric)	203.2
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Thickness T (Metric)	1.2

Material	Polyamide 6.6 (PA66)		
Material Shortcut	PA66		
US MIL SPEC	MS3367-1-2		
SAE-AS33671			
Flammability			
UL 94 V2	Halogen free		
Yes	Operating Temperature (Metric)		
-40°F to +185°F (-40°C to +85°C)	ROHS Complaint		
Yes	Certification/Specification WEB		
CAGE Code 53421 UL-ZODZ.E64139	UL Recognized (US)		
Yes	UL Listed (US and Canada)		
Yes	UL Recognized (US and Canada)		
Yes	UL Listed (US		
Yes			
Package Quantity(Imperial)	1000		
Package Quantity (Metric)	1000		

Customs Number

3926909988