

Specification Sheet

Part Number: T50R3M4



Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Orange, 1000/pkg

|                     |                                                                                                                                                                                                                                                                                               |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 111-04865                                                                                                                                                                                                                                                                                     |
| Type                | T50R                                                                                                                                                                                                                                                                                          |
| Color               | Orange (OG)                                                                                                                                                                                                                                                                                   |
| Features & Benefits | •Engineered and manufactured for maximum performance and quality. •Made from 100% high-quality plastic to ensure efficient recycling. •Inside serration for a strong grip onto bundles. •Easy application either manually or with a tensioning tool. •Bent tail allows for simpler insertion. |
| Quantity Per        | bag                                                                                                                                                                                                                                                                                           |

|                     |                                                                                                                                                                                                                                                                                                                                                              |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                     |                                                                             |
|-------------------------------------|-----------------------------------------------------------------------------|
| Short Description                   | Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Orange, 1000/pkg |
| Global Part Name                    | T50R-PA66-OG                                                                |
| Minimum Tensile Strength (Imperial) | 50.0                                                                        |
| Minimum Tensile Strength (Metric)   | 225.0                                                                       |
| Length L (Imperial)                 | 8.0                                                                         |
| Length L (Metric)                   | 203.2                                                                       |
| Identification Plate Position       | none                                                                        |
| Releasable Closure                  | No                                                                          |
| Tie Closure                         | plastic pawl                                                                |
| Variant                             | Inside Serrated                                                             |
| Width W (Imperial)                  | 0.18                                                                        |
| Width W (Metric)                    | 4.6                                                                         |
| Bundle Diameter Min (Imperial)      | 0.06                                                                        |
| Bundle Diameter Min (Metric)        | 1.5                                                                         |
| Bundle Diameter Max (Imperial)      | 1.97                                                                        |
| Bundle Diameter Max (Metric)        | 50.0                                                                        |
| Thickness T (Metric)                | 1.2                                                                         |

|                                  |                                 |  |
|----------------------------------|---------------------------------|--|
| Material                         | Polyamide 6.6 (PA66)            |  |
| Material Shortcut                | PA66                            |  |
| US MIL SPEC                      | MS3367-1-3                      |  |
| SAE-AS33671                      |                                 |  |
| Flammability                     |                                 |  |
| UL 94 V2                         | Halogen free                    |  |
| Yes                              | Operating Temperature (Metric)  |  |
| -40°F to +185°F (-40°C to +85°C) | ROHS Complaint                  |  |
| Yes                              | Certification/Specification WEB |  |
| UL-ZODZ.E64139 CAGE Code 53421   | UL Recognized (US)              |  |
| Yes                              | UL Listed (US and Canada)       |  |
| Yes                              | UL Recognized (US and Canada)   |  |
| Yes                              | UL Listed (US                   |  |
| Yes                              |                                 |  |
| Package Quantity(Imperial)       | 1000                            |  |
| Package Quantity (Metric)        | 1000                            |  |

**Customs Number**

3926909988