

Specification Sheet

Part Number: TM1SF0C2



Push-Button Cable Tie Mount, .25" Hole Dia, .13" Max Panel, .2" Max Tie Width, PA66, Black, 100/pkg

|                     |                                                                                                                                                                                                                                                                        |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 151-40100                                                                                                                                                                                                                                                              |
| Type                | TM1SF                                                                                                                                                                                                                                                                  |
| Color               | Black (BK)                                                                                                                                                                                                                                                             |
| Features & Benefits | <ul style="list-style-type: none"><li>• Push Mounts, when used with standard cable ties, provide a permanent bundling solution.</li><li>• The low profile style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.</li></ul> |
| Quantity Per        | bag                                                                                                                                                                                                                                                                    |
| Product Description | HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for quick installation by pushing the mount through a pre-drilled hole. The low profile head is suitable in space constrained areas.                         |
| Short Description   | Push-Button Cable Tie Mount, .25" Hole Dia, .13" Max Panel, .2" Max Tie Width, PA66, Black, 100/pkg                                                                                                                                                                    |

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| Global Part Name                    | TM1SF-PA66-BK                        |
|                                     |                                      |
| Length L (Imperial)                 | 0.62                                 |
| Length L (Metric)                   | 15.75                                |
| Fixation Method                     | with Arrowhead / Push Mount (Mounts) |
| Width W (Imperial)                  | 0.4                                  |
| Width W (Metric)                    | 10.2                                 |
| Cable Ties                          | T18 - T50                            |
| Height H (Imperial)                 | .18                                  |
| Height H (Metric)                   | 4.60                                 |
| Cable Tie Width Max (Imperial)      | 0.2                                  |
| Cable Tie Width Max (Metric)        | 5.0                                  |
| Panel Thickness Min(Imperial)       | 0.13                                 |
| Panel Thickness Max(Imperial)       | 0.13                                 |
| Panel Thickness Min (Metric)        | 3.40                                 |
| Panel Thickness Max (Metric)        | 3.3                                  |
| Mounting Hole Diameter D (Imperial) | 0.25                                 |
| Mounting Hole Diameter D (Metric)   | 6.35 mm                              |

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Mounting Hole Diameter D Max (Metric) | 6.35                             |
| Material                              | Polyamide 6.6 (PA66)             |
| Material Shortcut                     | PA66                             |
| Flammability                          | UL 94 V2                         |
| Operating Temperature (Metric)        | -40°F to +185°F (-40°C to +85°C) |
| ROHS Complaint                        | Yes                              |
| UL Recognized (US)                    | Yes                              |
| UL Recognized (US and Canada)         | Yes                              |
| Package Quantity(Imperial)            | 100                              |
| Package Quantity (Metric)             | 100                              |
| Customs Number                        | 3926909988                       |