

Specification Sheet

Part Number: TSRP2W-6A



One Piece Power Rated Raceway, 1-1/4", 6.0 ft Long, PVC, White, 120ft/Carton

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 250-62602                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Type                | TSRP2-6A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Color               | White (WH)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Features & Benefits | <ul style="list-style-type: none"><li>•Completely tamper resistant, the cover’s self-locking, hidden positive latch permits quick re-entry as well as providing a secure installation of power cables.</li><li>•U.L. Listed for power up to 600 Volts, meeting UL5A and CSA 22.2 Number 62-93 Standards.</li><li>•Manufactured from UL 94V-0 rated PVC material.</li><li>•Fittings incorporate a minimum 1" bend radius per TIA/EIA 568-B and 569-A standards.</li><li>•Large base for greater adhesive surface.</li><li>•Rubber-based foam tape adhesive with high ultimate bond strength, which conforms to any surface.</li><li>•Flexible hinge allows the raceway to endure numerous openings without creating discoloration or stress cracking.</li><li>•Junction boxes can be used for electrical or data outlets.</li><li>•Designed to complement HellermannTyton’s industry standard TSR low voltage raceway system.</li></ul> |
| Quantity Per        | carton                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

|                     |                                                                                                                                                                                                                                                                                                                                                                |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | HellermannTyton's TSRP power surface raceway is a one piece, non-metallic, adhesive backed latching raceway designed to aesthetically organize and route either power or communications cables. Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick reentry as well as providing a secure installation of power cables. |
| Short Description   | One Piece Power Rated Raceway, 1-1/4", 6.0 ft Long, PVC, White, 120ft/Carton                                                                                                                                                                                                                                                                                   |
| Global Part Name    | TSRP2-6A-PVC-WH                                                                                                                                                                                                                                                                                                                                                |
| Length L (Imperial) | 6.0                                                                                                                                                                                                                                                                                                                                                            |
| Length L (Metric)   | 1.83                                                                                                                                                                                                                                                                                                                                                           |
| Width W (Imperial)  | 1.25                                                                                                                                                                                                                                                                                                                                                           |
| Width W (Metric)    | 31.75                                                                                                                                                                                                                                                                                                                                                          |
| Height H (Imperial) | .75                                                                                                                                                                                                                                                                                                                                                            |
| Height H (Metric)   | 19.05                                                                                                                                                                                                                                                                                                                                                          |
| Material            | Polyvinylchloride (PVC)                                                                                                                                                                                                                                                                                                                                        |
| Material Shortcut   | PVC                                                                                                                                                                                                                                                                                                                                                            |
| Flammability        | UL 94 V0                                                                                                                                                                                                                                                                                                                                                       |
| Halogen free        | No                                                                                                                                                                                                                                                                                                                                                             |

|                                |                |
|--------------------------------|----------------|
| Operating Temperature (Metric) | +122°F (+50°C) |
| Reach Complaint(Article 33)    | No             |
| ROHS Complaint                 | Yes            |
| UL Listed (US and Canada)      | Yes            |
| UL Listed (US                  | Yes            |
| Package Quantity(Imperial)     | 120            |
| Package Quantity (Metric)      | 36.58          |
| Customs Number                 | 3925900000     |