

Specification Sheet

Part Number: 157-00402



Wide Strap Cable Tie with .25" Stud Mount, 15.7" Long, .5" Wide, PA66HIRHSUV, Black, 300/Bag

Article Number	157-00402
Type	WSR250
Color	Black (BK)
Features & Benefits	•Mount provides low insertion and high extraction forces which makes for a strong and easy installation. •Tie utilizes a strong hinge between the stud mount and strap head to provide superior holding ability. •Clamping rails increase grip on round bundles. •Thinner strap provides increased flexibility for improved ergonomics.
Quantity Per	bag
Product Description	The Wide Strap Stud Mount Cable Tie minimizes pinching on soft bundles and features a low profile head to provide compact bundling. A thinner strap provides increased flexibility for improved ergonomics. Available in various stud mount sizes, the wide strap tie utilizes a strong hinge between the stud mount and head to provide superior holding ability on a threaded stud.

Short Description	Wide Strap Cable Tie with .25" Stud Mount, 15.7" Long, .5" Wide, PA66HIRHSUV, Black, 300/Bag
Global Part Name	WSR250-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	120
Minimum Tensile Strength (Metric)	534
Length L (Imperial)	15.7
Length L (Metric)	398.8
Fixation Method	Weld Stud Fixing
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.5
Width W (Metric)	12.7
Bundle Diameter Min (Imperial)	0.38
Bundle Diameter Min (Metric)	9.5
Bundle Diameter Max (Imperial)	4.1

Bundle Diameter Max (Metric)	104.1
Stud Diameter (Metric)	M6
Stud Diamater (Imperial)	1/4
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	300
Package Quantity (Metric)	300
Customs Number	3926909988
Content Unit(BMEcat)	pcs.

