

## **Specification Sheet**

Part Number: 596-00499



Solar Label, Warning Turn off PV Prior to..., 4.125" x 2.0", V, Orange/White, 50/roll

Article Number	596-00499
Туре	WTOPVLBL
Color	Orange (OG)
Features & Benefits	<ul> <li>Made with UV-stable inks and materials for durability and weather resistance.</li> <li>Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.</li> <li>Abrasion resistant for high-performance identification.</li> <li>Meets NEC and IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li> </ul>
Quantity Per	roll

Product Description	HellermannTyton Pre-Printed Vinyl Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives designed to adhere to both baked enamel and powder coated surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Short Description	Solar Label, Warning Turn off PV Prior to, 4.125" x 2.0", V, Orange/White, 50/roll
Global Part Name	WTOPVLBL-443/281-OG
Technical Description	Pre-Printed Solar Label, "WARNING - TURN OFF PV BEFORE WORKING", 4.125" X 2", Orange/White
Local Order Number 2	Cross Reference = 10 per pack: 596-00664; Metal Solar Placard 5 pack: 596-00832
Length L (Imperial)	4.125
Length L (Metric)	104.6
Width W (Imperial)	4.1
Width W (Metric)	104.14
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	2.0

50.8

107.69

Height H (Metric)

Width of Liner (Metric)

Material	Type 443/281, UV Stable Flexible White Vinyl with Clear Polyester Laminate
Material Shortcut	443/281
Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	NEC2017 UL 969 NEC2020 NEC2014
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055

Labels per Row	1
Weight (Metric)	0.521
Weight (Imperial)	1.12

© 2019 HellermannTyton. All Rights Reserved.

Labels per Column

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions