


ML-010-07-0015/xxK



BENEFITS:

- Slim, simple and cost effective design
- Connect directly to AC, no external driver needed
- High system efficacy
- Low total life cycle cost
- Flicker free AC operation

CERTIFICATIONS:

- All modules are UL recognized components under file: E342490



PERFORMANCE:

- 50,000 Hours
- Lumen output
- Color temp ranging from 2700k to 5000k
- CRI 80+ (90+ Available)
- Three step Mcadam design

ELECTRICAL CHARACTERISTICS:

- Input voltage: 120VAC
- High power factor (>0.9) with no electrolytic capacitor or inductors
- Lower THD level is compatible with strict regulatory standards worldwide
- Over voltage, input surge protection
- Compatible with current (ELV) reverse phase dimmers

Product Code	Dimensions [in]	Lumen Output [lm]	CCT [K]	System efficacy [lm/w]	CRI [Ra]	Wattage	LED type
ML-010-07-0015/27k	1.55"x11"	840	2700k	105	80+	8 watts	5630 MJT
ML-010-07-0015/30k	1.55"x11"	840	3000k	105	80+	8 watts	5630 MJT
ML-010-07-0015/40k	1.55"x11"	840	4000k	105	80+	8 watts	5630 MJT
ML-010-07-0015/50k	1.55"x11"	840	5000k	105	80+	8 watts	5630 MJT

*** Special CCTs are available with special order

NOTES:

- All LED Light Modules are available in 2700K, 3000K, 4000K and 5000K
- Current models are 120VAC
- All lumen output and light efficacy are measured are derived from published documentation.
- Optimal case temperature $T_c = 65^{\circ}\text{C}$
- Storage temperature : - $40^{\circ}\text{C} \sim 80^{\circ}\text{C}$
- Operating temperature : - $35^{\circ}\text{C} \sim 65^{\circ}\text{C}$

DIMENSIONS:

