

## Angled brackets - BG/SA - 1201604

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Angled brackets with M6 screw, DIN rail limit stop, for fixing DIN rails at an angle of 30°, with M6 screw, height: 35.4 mm

### Your advantages

- ✓ The BG/S brackets can be used to fix DIN rails at a distance from the mounting surface
- ✓ 30° tilt angle

RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 10 pc                                                                                                   |
| GTIN         | <br>4 017918 017415 |
| GTIN         | 4017918017415                                                                                           |

### Technical data

#### Dimensions

|        |         |
|--------|---------|
| Height | 35.4 mm |
| Length | 87 mm   |
| Width  | 19.7 mm |

#### General

|          |                                           |
|----------|-------------------------------------------|
| Material | Steel                                     |
| Coating  | galvanized, passivated with a thick layer |
| Color    | silver                                    |

### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>