

Fiber optic coupling - PSM-SET-FSMA-LINK/2 - 2799416

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Coupling; set consisting of 2 couplings for connecting F-SMA plugs



Your advantages

✓ Suitable for fiber types:

- POF (980/1000 µm)
- PCF (200/230 µm)
- GOF MM (50/125µm)
- GOF SM (9/125µm)

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 118396
GTIN	4017918118396

Technical data

Mechanical characteristics

Connection profile	FSMA
Connection method	Coupling
Color	Bare metallic
Degree of protection	IP20

Ambient conditions

Ambient temperature (operation)	-25 °C ... 85 °C
Degree of protection	IP20

Material data

Flammability rating according to UL 94	V0
Material	Zinc die-cast
Depth	23.5 mm

Fiber optic coupling - PSM-SET-FSMA-LINK/2 - 2799416

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>