

Test adapter - PAI-4-FIX-5/6 GY - 3035982

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




4 mm test adapter, for terminal blocks with 5.2 mm and 6.2 mm pitch

Your advantages

- ✓ Make contact and latch securely to any point in the function shaft
- ✓ Test adapter for accommodating safety test plugs with a 4 mm diameter



Key Commercial Data

| | |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| GTIN |  4 046356 520744 |
| GTIN | 4046356520744 |

Technical data

Dimensions

| | |
|--------------|---------|
| Height | 45.3 mm |
| Length | 5.8 mm |
| Width | 5.8 mm |
| Diameter | 5.8 mm |
| Pin diameter | 2.4 mm |

General

| | |
|----------|--------------------------------------------------------------------------------------------|
| Note | Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in |
| | Do not plug in while the power is connected |
| | Latching testing accessories, therefore only suitable for being plugged in once |
| Color | gray |
| Material | Copper |

Test adapter - PAI-4-FIX-5/6 GY - 3035982

Technical data

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
| Max. voltage | 250 V |
| Maximum load current | 10 A |
| Insertion/withdrawal cycles | 1 |

Standards and Regulations

| | |
|--------------------------------------------------------|-------------|
| Flammability rating according to UL 94 | V0 |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26 | HL 1 - HL 3 |

Environmental Product Compliance

| | |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|-------------------------------------------------------------------------------------|---------------|
| EAC |  | EAC-Zulassung |
|-----|-------------------------------------------------------------------------------------|---------------|

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>