

17220.8

SQI 4/30 YE



Insulated cross-connector, No. of poles: 30, Mounting type: Plug in, Width: 181.1 mm, Rated cross-section: 4 mm², Colour: Yellow

RAL: 1026

Business data

Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	21 g
Weight per piece (including packaging)	22 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	17220.8
Product description	Insulated cross-connector

17220.8

SQI 4/30 YE

Technical data

Dimensions

Length	4.2 mm
Width	181.1 mm
Height	23 mm
Pitch size	6 mm

Ratings

Voltage with partition, max.	1000 V
Voltage without partition, max.	1000 V
Rated current	32 A
Current load, max.	41 A
Rated cross-section	4 mm ²
Contamination degree	2

Connection data

No. of poles	30
--------------	----

Materials

Material	Bronze
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	30

Print

Colour	Yellow
--------	--------

Data sheet

17220.8

SQI 4/30 YE



Technical data

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2021-07-08
REACH Candidate Substance Note	No
RoHS Conform	yes

17220.8
SQI 4/30 YE

Accessories

Insulation cap for cross-connector



Insulating cap, Colour: Yellow

General order data

Product number:	Article name	GTIN (EAN)	Packaging unit
17200.8	SQIK 2,5-10 YE	4044211148539	20