### 17235.8 SQI 10/6 YE





Insulated cross-connector, No. of poles: 6, Mounting type: Plug in, Width: 57.9 mm, Rated cross-section: 10 mm², Colour: Yellow

**RAL:** 1026

#### **Business data**

Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	8 g
Weight per piece (including packaging)	8.1 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	17235.8
Product description	Insulated cross-connector



17235.8 SQI 10/6 YE

Technical data	
Dimensions	
Length	4 mm
Width	57.9 mm
Height	23 mm
Pitch size	10 mm
Ratings	
Voltage with partition, max.	1000 V
Voltage without partition, max.	1000 V
Rated current	57 A
Current load, max.	57 A
Rated cross-section	10 mm²
Contamination degree	2
Connection data	
No. of poles	6
Materials	
Material	Copper alloy
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C
Further technical data	
Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	6
Print	
Colour	Yellow



17235.8 SQI 10/6 YE

#### **Technical data**

Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2021-07-08
REACH Candidate Substance Note	No
RoHS Conform	yes

17235.8 SQI 10/6 YE



#### **Accessories**

#### Insulation cap for cross-connector



Insulating cap, Colour: Yellow

General order data

Product number: Article name GTIN (EAN) Packaging unit

17200.8 SQIK 2,5-10 YE 4044211148539 20