

17238.8
SQI 10/9 YE



Insulated cross-connector, No. of poles: 9, Mounting type: Plug in, Width: 88.2 mm, Rated cross-section: 10 mm², Colour: Yellow

RAL: 1026

Business data

Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	12 g
Weight per piece (including packaging)	12.1 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	17238.8
Product description	Insulated cross-connector

17238.8

SQI 10/9 YE

Technical data

Dimensions

Length	4 mm
Width	88.2 mm
Height	23 mm
Pitch size	10 mm

Ratings

Voltage with partition, max.	1000 V
Voltage without partition, max.	1000 V
Rated current	57 A
Current load, max.	57 A
Rated cross-section	10 mm ²
Contamination degree	2

Connection data

No. of poles	9
--------------	---

Materials

Material	Copper alloy
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	9

Print

Colour	Yellow
--------	--------

Data sheet



17238.8

SQI 10/9 YE

Technical data

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2021-07-08
REACH Candidate Substance Note	No
RoHS Conform	yes

17238.8
SQI 10/9 YE

Accessories

Insulation cap for cross-connector



Insulating cap, Colour: Yellow

General order data

Product number:	Article name	GTIN (EAN)	Packaging unit
17200.8	SQIK 2,5-10 YE	4044211148539	20