

17252.8  
SQI 35/2 YE



Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 26.5 mm, Rated cross-section: 35 mm², Colour: Yellow

RAL: 1026

Business data

|  |                           |
|--|---------------------------|
| Packaging unit                             | 20                        |
| Quantity unit                              | PC                        |
| Weight per piece (not including packaging) | 14 g                      |
| Weight per piece (including packaging)     | 14.2 g                    |
| Unit of weight                             | G                         |
| Customs number                             | 85389099                  |
| Country of origin                          | DE                        |
| Product description                        | Insulated cross-connector |

17252.8

SQI 35/2 YE

## Technical data

### Dimensions

|            |         |
|------------|---------|
| Length     | 6.2 mm  |
| Width      | 26.5 mm |
| Height     | 34.1 mm |
| Pitch size | 16 mm   |

### Ratings

|                      |                    |
|----------------------|--------------------|
| Max. voltage         | 1000 V             |
| Rated current        | 101 A              |
| Current load, max.   | 101 A              |
| Rated cross-section  | 35 mm <sup>2</sup> |
| Contamination degree | 2                  |

### Connection data

|              |   |
|--------------|---|
| No. of poles | 2 |
|--------------|---|

### Materials

|                           |               |
|---------------------------|---------------|
| Material                  | Bronze        |
| Surface                   | Tin-plated    |
| Insulation housing        | Polyamide 6.6 |
| Flammability class UL 94  | V-2           |
| Working temperature, min. | -40 °C        |
| Working temperature, max. | 105 °C        |

### Further technical data

|                               |         |
|-------------------------------|---------|
| Mounting type                 | Plug in |
| Insulation available          | ✓       |
| Touch protection is available | ✓       |
| Number of bridged terminals   | 2       |

### Print

|        |        |
|--------|--------|
| Colour | Yellow |
|--------|--------|

17252.8

SQI 35/2 YE

---

## Technical data

---

### Environmental Product Compliance

|                                |            |
|--------------------------------|------------|
| REACH Conform                  | yes        |
| REACH Reference date           | 2021-07-08 |
| REACH Candidate Substance Note | No         |
| RoHS Conform                   | yes        |

---

**Accessories**

---