




Insulated cross-connector, No. of poles: 4, Mounting type: Can be screwed on, Width: 28.8 mm, Colour: Yellow

RAL: 1026

Business data

Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	9.4 g
Weight per piece (including packaging)	9.5 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Product description	Insulated cross-connector

Technical data

Dimensions

Length	2.4 mm
Width	28.8 mm
Pitch size	8 mm

Ratings

Voltage with partition, max.	800 V
Voltage without partition, max.	400 V
Rated current	57 A
Contamination degree	3

Connection data

No. of poles	4
Screw head	Slotted
Screw threading	M 3
Tightening torque, min.	0.5 Nm
Tightening torque, max.	1 Nm

Materials

Material	Copper
Surface	Tin-plated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Screwable
Insulation available	✓
Number of bridged terminals	4

Print

Colour	Yellow
--------	--------

Technical data


Environmental Product Compliance

REACH Conform	No
REACH Reference date	2021-07-08
REACH Candidate Substance Note	No
REACH CAS 1 Substance	LEAD
REACH CAS 1 Percent minimal	0.1 %
REACH CAS 1 Percent maximum	4 %
REACH CAS 1 Number	7439-92-1
RoHS Conform	yes
RoHS Exception rule	6c

2752.2
QI 4 YE

Media

M3



2752.2
QI 4 YE

Accessories

Screwdriver



Screwdriver with bare blade, Colour: Black-grey

General order data

Product number:	Article name	GTIN (EAN)	Packaging unit
1086.0	SDB 0,6x3,5	4044211014797	1 ST