


3450.9

FQI 1,5/10 RD



Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 40.9 mm, Colour: Red

Business data

| | |
|--|---------------------------|
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 5.2 g |
| Weight per piece (including packaging) | 5.3 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | CZ |
| Prio-Article | 3450.8 |
| Product description | Insulated cross-connector |

3450.9

FQI 1,5/10 RD

Technical data

Dimensions

| | |
|------------|---------|
| Length | 4 mm |
| Width | 40.9 mm |
| Pitch size | 4.1 mm |

Ratings

| | |
|---------------------|---------------------|
| Max. voltage | 800 V |
| Rated current | 17.5 A |
| Current load, max. | 17,5 A |
| Rated cross-section | 1.5 mm ² |

Connection data

| | |
|--------------|----|
| No. of poles | 10 |
|--------------|----|

Materials

| | |
|---------------------------|---------------|
| Material | Copper |
| Surface | Tin-nickel |
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-2 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|-------------------------------|---------|
| Mounting type | Plug in |
| Insulation available | ✓ |
| Touch protection is available | ✓ |
| Number of bridged terminals | 10 |

Print

| | |
|--------|-----|
| Colour | Red |
|--------|-----|

Environmental Product Compliance

| | |
|--------------------------------|------------|
| REACH Conform | yes |
| REACH Reference date | 2021-07-08 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

3450.9

FQI 1,5/10 RD

Accessories
