

3456.4  
FQI 1,5/6 BK

---

Insulated cross-connector, No. of poles: 6, Mounting type: Plug in, Width: 24.5 mm, Colour: Black

RAL: 9005

Business data

---

Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	2.8 g
Weight per piece (including packaging)	2.9 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Prio-Article	3456.8
Product description	Insulated cross-connector

---

3456.4

FQI 1,5/6 BK

## Technical data

### Dimensions

Length	4 mm
Width	24.5 mm
Pitch size	4.1 mm

### Ratings

Max. voltage	800 V
Rated current	17.5 A
Current load, max.	17,5 A
Rated cross-section	1.5 mm <sup>2</sup>

### Connection data

No. of poles	6
--------------	---

### Materials

Material	Copper
Surface	Tin-nickel
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

### Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	6

### Print

Colour	Black
--------	-------

### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2021-07-08
REACH Candidate Substance Note	No
RoHS Conform	yes

3456.4

FQI 1,5/6 BK

---

## Accessories

---