

3459.5

FQI 1,5/9 BU

Insulated cross-connector, No. of poles: 9, Mounting type: Plug in, Width: 36.8 mm, Colour: Blue

Business data

Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	4.4 g
Weight per piece (including packaging)	4.5 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Prio-Article	3459.8
Product description	Insulated cross-connector

3459.5

FQI 1,5/9 BU

Technical data

Dimensions

Length	4 mm
Width	36.8 mm
Pitch size	4.1 mm

Ratings

Max. voltage	800 V
Rated current	17.5 A
Current load, max.	17,5 A
Rated cross-section	1.5 mm ²

Connection data

No. of poles	9
--------------	---

Materials

Material	Copper
Surface	Tin-nickel
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	9

Print

Colour	Blue
--------	------

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2021-07-08
REACH Candidate Substance Note	No
RoHS Conform	yes

3459.5

FQI 1,5/9 BU

Accessories
