Data sheet







Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 50.9 mm, Colour: Yellow

RAL: 1026

Business data

Packaging unit	10			
Quantity unit	PC			
Weight per piece (not including packaging)	6.8 g			
Weight per piece (including packaging)	6.9 g			
Unit of weight	G			
Customs number	85389099			
Country of origin	CZ			
Prio-Article	3460.8			
Product description	Insulated cross-connector			

Data sheet



3460.8 FQI 2,5/10 YE

Technical data			
Dimensions			
Length	4 mm		
Width	50.9 mm		
Pitch size	5.1 mm		
Ratings			
Max. voltage	800 V		
Rated current	24 A		
Current load, max.	24 A		
Rated cross-section	2.5 mm²		
Connection data			
No. of poles	10		
Materials			
Material	Copper		
Surface	Tin-nickel		
Insulation housing	Polyamide 6.6		
Flammability class UL 94	V-2		
Working temperature, min.	-40 °C		
Working temperature, max.	105 °C		
Further technical data			
Mounting type	Plug in		
Insulation available	✓		
Touch protection is available	✓		
Number of bridged terminals	10		
Print			
Colour	Yellow		
Environmental Product Compliance			
REACH Conform	yes		
REACH Reference date	2021-07-08		
REACH Candidate Substance Note	No		
RoHS Conform	yes		

Data sheet



3460.8 FQI 2,5/10 YE

Λ	~	20	SS	^	ri2	20