

3467.9

FQI 2,5/7 RD



Insulated cross-connector, No. of poles: 7, Mounting type: Plug in, Width: 35.6 mm, Colour: Red

Business data

Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	4.6 g
Weight per piece (including packaging)	4.7 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Prio-Article	3467.8
Product description	Insulated cross-connector

3467.9

FQI 2,5/7 RD

Technical data

Dimensions

Length	4 mm
Width	35.6 mm
Pitch size	5.1 mm

Ratings

Max. voltage	800 V
Rated current	24 A
Current load, max.	24 A
Rated cross-section	2.5 mm ²

Connection data

No. of poles	7
--------------	---

Materials

Material	Copper
Surface	Tin-nickel
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	7

Print

Colour	Red
--------	-----

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2021-07-08
REACH Candidate Substance Note	No
RoHS Conform	yes

Accessories
