Data sheet

3468.5 FQI 2,5/8 BU



Insulated cross-connector, No. of poles: 8, Mounting type: Plug in, Width: 40.7 mm, Colour: Blue

Business data

Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	5.2 g
Weight per piece (including packaging)	5.3 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Prio-Article	3468.8
Product description	Insulated cross-connector

Data sheet



3468.5 FQI 2,5/8 BU

Technical data		
Dimensions		
Length	4 mm	
Width	40.7 mm	
Pitch size	5.1 mm	
Ratings		
Max. voltage	800 V	
Rated current	24 A	
Current load, max.	24 A	
Rated cross-section	2.5 mm²	
Connection data		
No. of poles	8	
Materials		
Material	Copper	
Surface	Tin-nickel	
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-2	
Working temperature, min.	-40 °C	
Working temperature, max.	105 °C	
Further technical data		
Mounting type	Plug in	
Insulation available	✓	
Touch protection is available	✓	
Number of bridged terminals	8	
Print		
Colour	Blue	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2021-07-08	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

Data sheet



3468.5 FQI 2,5/8 BU

Accessories