

Wire-end ferrules, Max. wire cross-section: 10 mm², Length: 24 mm, Length of copper pipe: 12 mm, Colour: Red

### Business data

|                                            |                 |
|--------------------------------------------|-----------------|
| Article number                             | 3088.0          |
| Article name                               | H 10,0/24 KS RD |
| GTIN (EAN)                                 | 4044211057930   |
| Colour                                     | Red             |
| Packaging unit                             | 100             |
| Quantity unit                              | PC              |
| Weight per piece (not including packaging) | 0.6 g           |
| Weight per piece (including packaging)     | 0.69 g          |
| Unit of weight                             | G               |
| Customs number                             | 85369010        |
| Country of origin                          | DE              |
| Product description                        | Ferrules        |

### Technical data

#### Dimensions

|                                  |        |
|----------------------------------|--------|
| Length                           | 24 mm  |
| Length of copper pipe            | 12 mm  |
| Diameter of copper pipe          | 4.6 mm |
| Diameter plastic collar          | 9.6 mm |
| Wall thickness of copper pipe    | 0.2 mm |
| Wall thickness of plastic collar | 0.3 mm |

#### Connection data

|                              |                    |
|------------------------------|--------------------|
| Wire cross-section, max.     | 10 mm <sup>2</sup> |
| Wire cross-section AWG, max. | 8                  |
| Stripping length             | 12 mm              |

#### Materials

|                           |                                |
|---------------------------|--------------------------------|
| Copper pipe               | Copper alloy                   |
| Surface                   | Galvanically tin-plated, shiny |
| Plastic collar            | Polypropylene homopolymer      |
| Working temperature, min. | -5 °C                          |
| Working temperature, max. | 105 °C                         |

#### Further technical data

|                      |   |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

#### Environmental Product Compliance

|                                |            |
|--------------------------------|------------|
| REACH Conform                  | yes        |
| REACH Reference date           | 2022-01-17 |
| REACH Candidate Substance Note | No         |
| RoHS Conform                   | yes        |

---

### Approvals

---

#### Standards and regulations

---

|                  |     |
|------------------|-----|
| DIN 46228-4:1990 | yes |
|------------------|-----|

---

---

### Media

---

---

### Accessories

---