



HDI-6150

The HDI-6150 Converter is a VGA video converter. It converts VGA input into HDMI to allow PC users to show their image not only on the PC's monitor, but could also on a HDTV monitor. This unit also adds the audio signal to the single HDMI cable for a single cable transmission to the TV.

The HDI-6150 offers solutions for digital entertainment center, HDTV retail and show site, HDTV, STB, DVD, information distribution, conference room presentation, school and corporate training environments.

FEATURES

Easy to Use: Installs in seconds, no user settings required.

Conversion: Converts PC or Laptop VGA video and R/L audio into one complete HDMI signal.

HDCP pass-through

SPECIFICATIONS

Signal Inputs/Output	
Input Video Signal	0.5-1.0 volts p-p
Input DDC Signal	5 volts p-p (TTL)
Output Video	HDMI 1.2a
VGA	640x480 60Hz 75Hz 800x600 60Hz 75Hz 1024x768 60Hz 75Hz 1280x720 60Hz 75Hz 1280x768 60Hz 75Hz 1280x960 60Hz 75Hz 1280x1024 60Hz 75Hz
DTV/HDTV	480i/576i/480p/576p/720p/1080i/1080P
Frequency	Up to 165MHz
Video Amplifier Bandwidth	1.65Gpbs/165MHz
Interlaced(50&60Hz)	480i,576i,1080i
Progressive(50&60Hz)	480p,576p,720p,1080p
Size(W-H-D)	89mmW x 29mmH x 68mmD
Weight(Net)	0.68kgs
Limited Warranty	1 Year Parts and Labor
Operating Temperature	0 °C to +70 °C
Operating Humidity	10% to 85 % RH (no condensation)
Storage Temperature	-10 °C to +80 °C
Storage Humidity	5% to 95 % RH (no condensation)
External Power Supply	5V DC@1A
Converter Unit	FCC,CE,
Power Supply	CE,FCC
AC Power Adapter	US standard,