

Title of Change:	Transfer FRD Rectifiers, and other discrete products to onsemi Roznov, Czech Republic.	
Proposed Changed Material First Ship Date:	21 Dec 2023 or earlier if approved by customer	
Current Material Last Order Date:	30 Sep 2023 <i>Orders received after the Current Material Last Order Date expiration are to be considered as orders for new changed material as described in this PCN. Orders for current (unchanged) material after this date will be per mutual agreement and current material inventory availability.</i>	
Current Material Last Delivery Date:	20 Dec 2023 <i>The Current Material Last Delivery Date may be subject to change based on build and depletion of the current (unchanged) material inventory</i>	
Product Category:	Active components – Discrete components	
Contact information:	Contact your local onsemi Sales Office or Phuong.Hoang@onsemi.com	
PCN Samples Contact:	Contact your local onsemi Sales Office to place sample order. Sample requests are to be submitted no later than 45 days after publication of this change notification. Samples delivery timing will be subject to request date, sample quantity and special customer packing/label requirements.	
Sample Availability Date:	30 Jun 2023	
PPAP Availability Date:	30 Jun 2023	
Additional Reliability Data:	Contact your local onsemi Sales Office or Marco.kang@onsemi.com	
Type of Notification:	This is a Final Product/Process Change Notification (FPCN) sent to customers. The change will be implemented at 'Proposed Change Material First Ship Date' in compliance to J-STD-46 or ZVEI, or earlier upon customer approval, or per our signed agreements. onsemi will consider this proposed change and it's conditions acceptable, unless an inquiry is made in writing within 45 days of delivery of this notice. To do so, contact PCN.Support@onsemi.com .	
Change Category		
Category	Type of Change	
Process - Wafer Production	Move of all or part of wafer fab to a different location/site/subcontractor, New wafer diameter	
Equipment	Production from a new equipment/tool which uses the same basic technology (replacement equipment or extension of existing equipment pool) without change of process.	
Description and Purpose:		
This notification is to inform the customers that onsemi plan to transfer their FRD Rectifiers, and other discrete products to onsemi Roznov, Czech Republic.		
	Before Change Description	After Change Description
Wafer fab	onsemi Bucheon, Korea	onsemi Roznov, Czech Republic
Wafer size	6 inch (150 mm)	8 inch (200 mm)
There are no product material changes and no product marking changes as a result of this change.		

Reason / Motivation for Change:	Supply disruption		
Anticipated impact on fit, form, function, reliability, product safety or manufacturability:	The device has been qualified and validated based on the same Product Specification. The device has successfully passed the qualification tests. Potential impacts can be identified, but due to testing performed by onsemi in relation to the PCN, associated risks are verified and excluded. No anticipated impacts.		
Sites Affected:			
onsemi Sites		External Foundry/Subcon Sites	
onsemi Roznov, Czech Republic		None	
Marking of Parts/ Traceability of Change:	Clean Date Code can be advised upon of request.		

Reliability Data Summary:

QV DEVICE NAME: NFVA35065L32 (QV8-1)

RMS: 83762, 84035

PACKAGE: ASPM27

Test	Specification	Condition	Interval	Results
HTRB	JESD22-A108, AQG324	Tj=175°C, 100% max rated V	1008 hrs	0/78
TC	JESD22-A104, AQG324	Ta= -40°C to +125°C	1000 cyc	0/39
TS1	AQG324	Ta= -40°C to +125°C, transition <30sec	1000 cyc	0/18
TS2	AQG324	Ta= -40°C to +125°C, transition <30sec, with heat sink	1000 cyc	0/6
H3TRB	JESD22-A110	85°C, 85% RH, 18.8psig, bias 100V	1008 hrs	0/78
uHAST	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs	0/36

QV DEVICE NAME: FGHL75T65MQD (QV8-2)

RMS: S85126

PACKAGE: TO-247

Test	Specification	Condition	Interval	Results
HTRB	JESD22-A108	Tj=175°C, 80% rated V	1008hrs	0/231
HTGB	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs	0/231
HTSL	JESD22-A103	Ta=175°C	1008hrs	0/231
IOL	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 5min	6000cyc	0/231
TC	JESD22-A104	Ta= -65°C to +150°C	1000cyc	0/231
HAST	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96hrs	0/231
uHAST	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96hrs	0/231
RSH	JESD22- B106	Ta = 265°C, 10 sec Required for through hole devices only		0/30

NOTE: AEC-1pager is attached.

To view attachments:

1. Download pdf copy of the PCN to your computer
2. Open the downloaded pdf copy of the PCN
3. Click on the paper clip icon available on the menu provided in the left/bottom portion of the screen to reveal the Attachment field
4. Then click on the attached file

Electrical Characteristics Summary:

Electrical characteristics are not impacted.

List of Affected Parts:

Note: Only the standard (off the shelf) part numbers are listed in the parts list. Any custom parts affected by this PCN are shown in the customer specific PCN addendum in the PCN email notification, or on the **PCN Customized Portal**.

Current Part Number	New Part Number	Qualification Vehicle
AFGHL40T65SPD	N/A	NFVA35065L32, FGHL75T65MQD
ISL9R3060G2-F085	N/A	NFVA35065L32, FGHL75T65MQD
FGH75T65UPD-F085	N/A	NFVA35065L32, FGHL75T65MQD

Appendix A: Changed Products

PCN#: FPCN24561ZC
Issue Date: Jun 21, 2023

DIKG: DIGI-KEY

Product	Customer Part Number	Qualification Vehicle	New Part Number	Replacement Supplier
AFGHL40T65SPD		NFVA35065L32, FGHL75T65MQD		
ISL9R3060G2-F085		NFVA35065L32, FGHL75T65MQD		
FGH75T65UPD-F085		NFVA35065L32, FGHL75T65MQD		