

PCN Number:	20230702011.0	PCN Date:	July 12, 2023
Title:	Datasheet for TMS320F2838x		
Customer Contact:	Change Management team	Dept:	Quality Services
Change Type:	Electrical Specification		

PCN Details

Description of Change:

Texas Instruments Incorporated is announcing an information only notification.
The product datasheet(s) is being updated as summarized below.
The following change history provides further details.



TMS320F28388D, TMS320F28386D, TMS320F28386D-Q1
TMS320F28384D, TMS320F28384D-Q1, TMS320F28388S
TMS320F28386S, TMS320F28386S-Q1, TMS320F28384S, TMS320F28384S-Q1
 SPRSP14E – MAY 2019 – REVISED JUNE 2023

Changes from February 2, 2021 to June 28, 2023

Page

• This Revision History lists the changes from SPRSP14D to SPRSP14E.	1
• Global: Changed "CAN-FD" to "CAN FD".....	1
• Global: Changed the Pin Type of ESC_TX0_ENA and ESC_TX1_ENA from "I/O" to "O".....	1
• Features section: Added "Functional Safety-Compliant" feature and "Safety-related certification" feature. Added "Hardware Built-in Self Test (HWBIST)" feature. Deleted "MCAN (CAN FD)" feature from "Connectivity Manager (CM)" group. Added "MCAN (CAN FD)" to "CM-C28x shared communications peripherals" group...	1
• Description section: Added reference paragraph to <i>Getting Started With C2000™ Real-Time Control Microcontrollers (MCUs) Getting Started Guide</i>	2
• Package Information table: Changed table title from <i>Device Information</i> to <i>Package Information</i> . Updated table.....	2
• Functional Block Diagram figure: Changed blue MUX arrow of "1x CAN FD".....	4
• Device Comparison table: Updated CAN with Flexible Data-Rate (CAN FD) by changing value to "1 (can be assigned to CPU1 or CM)".	8
• Pin Attributes table: Updated table. Changed Ball H4 on 337-ball ZWT package from "NC" to "NC1" and removed pin assignment 119 from 176-pin PTP package. Added "NC2" (Ball J18 on 337-ball ZWT package; pin 119 on 176-pin PTP package). Changed the description of TRSTn. Deleted duplicate sentence from the description of XRSn. Changed the VSS Description and pin number for the 176-pin package.	18
• Analog Signals table: Updated table.....	51
• Digital Signals table: Updated table.....	51
• Power and Ground table: Updated table. Changed the VSS Description and pin number for the 176-pin package.....	51
• Test, JTAG, and Reset table: Updated table. Changed "NC" to "NC1". Changed "337 BGA" ball number from "H4, J18" to "H4". Deleted "176 Pin" pin number 119. Added "NC2" (337 BGA ball number J18, 176 Pin number 119). Changed the description of TRSTn. Deleted duplicate sentence from the description of XRSn.....	51
• Specifications section: Moved "Stresses beyond those listed under <i>Absolute Maximum Ratings</i> ..." paragraph text to <i>Absolute Maximum Ratings</i> table as footnotes.....	90

• <i>Absolute Maximum Ratings</i> table: Added "Stresses beyond those listed under <i>Absolute Maximum Ratings</i> ..." footnote and "All voltage values are with respect to VSS, unless otherwise noted" footnote.....	90
• <i>Recommended Operating Conditions</i> table: Deleted $t_{VDDIO-RAMP}$	90
• <i>ESD Ratings – Commercial</i> table: Removed JEDEC specification JESD22-C101 from Charged-device model (CDM) description. Added CDM values for corner pins.....	90
• <i>Power Management Module (PMM)</i> section: Added section.....	100
• <i>Power Sequencing</i> section: Changed section.....	100
• <i>Reset Circuit</i> figure: Replaced 4-way tie dot.....	106
• <i>Reset Sources</i> section: Updated lead-in paragraph. Added Reset Signals table.....	106
• <i>Clocking System</i> figure: Added CLB.....	110
• <i>Internal Clock Frequencies</i> table: Changed MIN $f_{(INTCLK)}$ and MIN $f_{(AUXINTCLK)}$ from 10 MHz to 2 MHz. Added $f_{(CLBTILECLK)}$ and $f_{(CLBREGCLK)}$	114
• <i>XTAL Oscillator</i> section: Changed section title from <i>Crystal Oscillator</i> to <i>XTAL Oscillator</i> . Updated section.....	115
• <i>Flash Parameters</i> table: Changed " N_{wec} Write/Erase Cycles" to " N_{wec} Write/Erase Cycles per sector". Added " N_{wec} Write/Erase Cycles for entire Flash (combined all sectors)" and its associated footnote. Added " $t_{retention}$ Data retention duration at $T_J = 125^{\circ}C$ " and its associated footnote.....	123
• <i>RAM Specifications</i> section: Added section.....	124
• <i>ROM Specifications</i> section: Added section.....	125
• <i>Connecting to the 14-Pin JTAG Header</i> figure: Added 2.2-k Ω pullup resistor on TMS.....	126
• <i>Connecting to the 20-Pin JTAG Header</i> figure: Added 2.2-k Ω pullup resistor on TMS.....	126
• <i>EMIF Asynchronous Memory Switching Characteristics</i> table: Updated MIN and MAX values of parameters 3, 10, 15, and 24 for EW = 1. Added "Maximum wait timeout condition" footnote.....	139
• <i>Single-Ended Input Model</i> section: Added "The user should analyze the ADC input setting assuming worst-case initial conditions on C_h ..." paragraph.....	160
• <i>Differential Input Model</i> section: Added references to the <i>Charge-Sharing Driving Circuits for C2000 ADCs (using TINA-TI simulation tool)</i> Application Note and the <i>ADC Input Circuit Evaluation for C2000 MCUs (using TINA-TI simulation tool)</i> Application Note.....	161
• <i>Differential Input Model</i> section: Deleted "The user should analyze the ADC input setting assuming worst-case initial conditions on C_h ..." paragraph.....	161
• <i>ADC Timings in 12-Bit Mode (SYSCLK Cycles)</i> table: Added footnote about t_{INT}	163
• <i>ADC Timings in 16-Bit Mode</i> table: Added footnote about t_{INT}	165
• <i>Comparator Electrical Characteristics</i> table: Added MIN and MAX Hysteresis values.....	170
• <i>CMPSS DAC Dynamic Error</i> section: Added section.....	173
• <i>PMBus Electrical Data and Timing</i> section: Deleted lead-in paragraph.....	223
• <i>PMBus Fast Mode Switching Characteristics</i> table: Added F_{mod} , PMBus Module Clock Frequency.....	223
• <i>PMBus Standard Mode Switching Characteristics</i> table: Added F_{mod} , PMBus Module Clock Frequency.....	223
• <i>Universal Serial Bus (USB) Controller</i> section: Changed Note about the accuracy of the on-chip zero-pin oscillator.....	239
• <i>Modular Controller Area Network (MCAN) [CAN FD]</i> section: Changed first two paragraphs.....	241
• <i>MCAN Module Overview</i> figure: Changed figure.....	241
• <i>Functional Block Diagram</i> figure: Changed blue MUX arrow of "1x CAN FD".....	263
• <i>C28x Memory Map</i> table: Added MCAN Message RAM.....	264
• <i>Peripheral Registers Memory Map</i> section: Added section.....	267
• <i>CM Memory Map</i> table: Changed the START ADDRESS and END ADDRESS of "EtherCAT RAM (direct access)".....	274
• <i>Peripheral Registers Memory Map (CM)</i> section: Added section.....	276
• <i>CM Bus Master Peripheral Access</i> table: Added "Y" to "CPU1 SUBSYSTEM" column of "MCAN (CAN FD)" row.....	280
• <i>All Available Boot Modes</i> table: Added footnote about USB Bootloader.....	285
• <i>Configurable Logic Block (CLB)</i> section: Added "For normal operation, the clock frequency of the CLB peripheral is derived from device SYSCLK ..." paragraph.....	304
• <i>CM Clocking System</i> figure: Changed figure title from "Clocking System" to " CM Clocking System". Removed MCAN.....	313
• <i>Functional Safety</i> section: Added section.....	316
• <i>Applications, Implementation, and Layout</i> section: Updated section.....	317
• <i>Getting Started and Next Steps</i> section: Added section.....	332
• <i>Tools and Software</i> section: Added C2000 Third-party search tool.....	334

The datasheet number will be changing.

Device Family	Change From:	Change To:
TMS320F2838x	SPRSP14D	SPRSP14E

These changes may be reviewed at the datasheet links provided.

<http://www.ti.com/product/TMS320F28388D>

Reason for Change:

To accurately reflect device characteristics.

Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative):

No anticipated impact. This is a specification change announcement only. There are no changes to the actual device

Changes to product identification resulting from this PCN:

None.

Product Affected:

F28384DPTPQR	F28384SZWTS	F28386DZWTS	F28388DZWTS	
F28384DPTPS	F28386DPTPQ	F28386SPTPQR	F28388DZWTSR	
F28384DZWTQR	F28386DPTPQR	F28386SPTPS	F28388SPTPS	
F28384DZWTS	F28386DPTPS	F28386SZWTS	F28388SPTPSR	
F28384SPTPQR	F28386DZWTS	F28388DPTPS	F28388SZWTS	
F28384SPTPS	F28386DZWTQR	F28388DPTPSR	F28388SZWTSR	

For questions regarding this notice, e-mails can be sent to the Change Management team or your local Field Sales Representative.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disdaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.