





PIN #	COLOR
1, 11	BLACK
2, 12	BROWN
3	RED
4	ORANGE
5	YELLOW
6	GREEN
7	BLUE
8	VIOLET
9	GRAY
10	WHITE


INTERNAL USE ONLY
USE MFG LOADING
PROCEDURE MC-12P-2



ACTUAL SIZE
EXCLUDING WIRE LENGTH



SECTION A-A
LESS NUT



SUGGESTED
PANEL OPENING

PART NO.	A22468-001	REV	ECO	DATE	APP
		B	103966	11-09-17	TLM

NOTE:

DIMENSIONS IN [] ARE IN
MILLIMETERS UNLESS
OTHERWISE NOTED AND ARE
FOR REFERENCE ONLY

THIRD ANGLE
-TOLERANCES-
UNLESS OTHERWISE NOTED
DIMENSIONS IN INCHES
2 PL DEC ± .01
3 PL DEC ± .005
4 PL DEC ± .0005
ANGLES ± 1°

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION WHICH IS THE PROPERTY OF OMNETICS CONNECTOR CORP. THIS DOCUMENT MAY NOT, IN WHOLE OR IN PART, BE DUPLICATED, OR DISCLOSED FOR ANY PURPOSE, WITHOUT WRITTEN PERMISSION FROM OMNETICS CONNECTOR CORP.

DFTM. JPF	DATE	04-23-15	TITLE:
CHK'D.	DATE		(12) PIN MALE BREAK AWAY CONNECTOR
APP'D.	DATE		

OMNETICS
CONNECTOR CORPORATION
7260 COMMERCE CIRCLE EAST
MINNEAPOLIS, MN 55432
WWW.OMNETICS.COM

CAGE CODE 61873	DWG NO.
A22468-001	SHEET 1 OF 2
SCALE: 2:1	REV B

IP68