PCN Number: 2023071				3.1	July 12, 2023					
Title: Qualification	n of RF	AB as	an additional Fab site option for select HPA07 devices							
Customer Contact:	Chan	ge Management team Dept:			(Quality Services				
Proposed 1 st Ship Dat	e:	Oct 1					quests d until:			
*Sample requests red	eived	l after	· Au	gust 11, 2023	will no	ot be	suppo	rted.		
Change Type:										
☐ Assembly Site				Design			Wafer Bump Material			
Assembly Process				Data Sheet	ta Sheet		Waf	er Bump Process		
Assembly Materials				Part number change			☑ Waf	Wafer Fab Site		
Mechanical Specific			Test Site			☑ Waf	Wafer Fab Material			
Packing/Shipping/Labeling				Test Process			er Fab Process			
•										
·	PCN Details									

Description of Change:

Texas Instruments is pleased to announce the addition of RFAB as an additional Wafer Fab site option for the products listed in the "Product Affected" section of this document.

С	urrent Fab Site	9	New Fab Site				
Current Fab Site	Process	Wafer Diameter	New Fab Site	Process	Wafer Diameter		
DP1DM5	HPA 07	200mm	RFAB	HPA07	300mm		

Qual details are provided in the Qual Data Section.

Reason for Change:

Continuity of supply

Anticipated impact on Form, Fit, Function, Quality or Reliability (positive / negative):

None

Changes to product identification resulting from this PCN:

Fab Site Information:

Chip Site Origin Code (20L)	Chip Site Country Code (21L)	Chip Site City
DM5	USA	Dallas
RFB	USA	Richardson
	(20L) DM5	(20L) Code (21L) DM5 USA

Sample product shipping label (not actual product label)

TEXAS INSTRUMENTS

MADE IN: Malaysia 2DC: 2Q:

MSL '2 /260C/1 YEAR SEAL DT MSL 1 /235C/UNLIM 03/29/04

OPT: LBL: 5A (L)T0:1750



(1P) \$N74L\$07N\$R (Q) 2000 (D) 0336 (31T)LOT: 3959047MLA (4W) TKY(1T) 7523483812 (P) (2P) REV: (V) 0033317 (20L) CSO: SHE (21L) CCO:USA (22L) ASO: MLA (23L) ACO: MYS

Product Affected:

ADS1191IPBS	ADS1192IPBS	ADS1291IPBS	ADS1292IPBS
ADS1191IPBSR	ADS1192IPBSR	ADS1291IPBSR	ADS1292IPBSR
ADS1191IRSMR	ADS1192IRSMR	ADS1291IRSMR	ADS1292IRSMR
ADS1191IRSMT	ADS1192IRSMT	ADS1291IRSMT	ADS1292IRSMT

Oualification Results

Data Displayed as: Number of lots / Total sample size / Total failed

Туре	#	Test Name	Condition	Duration	Qual Device: ADS1292IRSMR	QBS Process Reference: CD3232A1YFFR	QBS Process Reference: CD3232A1YFFR	QBS Process Reference: AMC7836IPAP	QBS Process Reference: INA231AIYFDR	QBS Process Reference: INA231BIYFDR
HAST	A2	Biased HAST	130C/85%RH	96 Hours	-	3/231/0	3/231/0	-	-	-
UHAST	A3	Unbiased HAST	130C/85%RH	96 Hours	-	3/231/0	3/231/0	-	-	-
TC	A4	Temperature Cycle	-55C/125C	700 Cycles	-	3/231/0	3/231/0	-	-	-
HTSL	A6	High Temperature Storage Life	170C	420 Hours	-	3/231/0	3/231/0	-	1/77/0	2/154/0
HTOL	B1	Life Test	140C	480 Hours	-	1/77/0	2/154/0	-	-	-
HTOL	B1	Life Test	150C	300 Hours	-	-	-	1/77/0	1/77/0	2/154/0
ELFR	B2	Early Life Failure Rate	125C	48 Hours	-	1/1000/0	2/2000/0	-	1/1000/0	2/2000/0
ESD	E2	ESD CDM	-	200 Volts	-	3/9/0	3/9/0	-	-	-
ESD	E2	ESD CDM	-	250 Volts	-	-	-	1/3/0	-	2/6/0

Туре	#	Test Name	Condition	Duration	Qual Device: ADS1292IRSMR	QBS Process Reference: CD3232A1YFFR	QBS Process Reference: CD3232A1YFFR	QBS Process Reference: AMC7836IPAP	QBS Process Reference: INA231AIYFDR	QBS Process Reference: INA231BIYFDR
ESD	E2	ESD CDM	-	350 Volts	-	-	-	-	1/3/0	-
ESD	E2	ESD CDM	-	500 Volts	1/3/0	-	-	-		-
ESD	E2	ESD HBM	-	1000 Volts	1/3/0	3/9/0	3/9/0	1/3/0	1/3/0	2/6/0
LU	E4	Latch-Up	Per JESD78	-	1/3/0	3/9/0	3/9/0	1/3/0	1/6/0	2/12/0
CHAR	E5	Electrical Characterization	Per Datasheet Parameters	-	1/30/0	1/30/0	1/30/0	1/30/0	1/30/0	2/60/0
FTY	E6	Final Test Yield	-	-	1/Pass	-	-	-	-	-

- QBS: Qual By Similarity
- Qual Device ADS1292IRSMR is qualified at MSL2 260C
- Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable
- The following are equivalent HTOL options based on an activation energy of 0.7eV : 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours
- The following are equivalent HTSL options based on an activation energy of 0.7eV: 150C/1k Hours, and 170C/420 Hours
- The following are equivalent Temp Cycle options per JESD47: -55C/125C/700 Cycles and -65C/150C/500 Cycles

Quality and Environmental data is available at TI's external Web site: http://www.ti.com/

TI Qualification ID: R-CHG-2208-068

For questions regarding this notice, e-mails can be sent to Change Management team or your local Field Sales Representative.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your

application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.