

SURFACE MOUNT ULTRAFAST RECOVERY RECTIFIER

Reverse Voltage - 50 to 1000 V

Forward Current - 1 A

FEATURES


- For surface mounted applications
- Low profile package
- Glass Passivated Chip Junction
- Easy to pick and place
- High efficiency
- Lead free in comply with EU RoHS 2011/65/EU directives

MECHANICAL DATA

- Case: SMA
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.055g / 0.002oz

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Top View

Marking Code: US1A~US1M

Simplified outline SMA and symbol

Maximum Ratings and Electrical characteristics





Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	US1A	US1B	US1D	US1G	US1J	US1K	US1M	Units					
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	V					
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	560	700	V					
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	V					
Maximum Average Forward Rectified Current at T _c = 125 °C	I _{F(AV)}	1							A					
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I _{FSM}	30							A					
Maximum Instantaneous Forward Voltage at 1 A	V _F	1.0		1.3		1.65		V						
Maximum DC Reverse Current T _a = 25 °C at Rated DC Blocking Voltage T _a = 125 °C	I _R	5 100							µA					
Maximum Reverse Recovery Time ⁽¹⁾	t _{rr}	50			75			ns						
Typical Thermal Resistance ⁽²⁾	R _{θJA}	75							°C/W					
Operating and Storage Temperature Range	T _j , T _{stg}	-55 ~ +150							°C					

(1) Measured with I_F = 0.5 A, I_R = 1 A, I_{rr} = 0.25 A.





(2) P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.



PACKAGE OUTLINE


Plastic surface mounted package; 2 leads

SMA



UNIT		A	D	E	H _E	c	e	g	a
mm	max	2.2	4.5	2.7	5.2	0.31	1.6	1.5	0.3
	min	1.9	4.0	2.3	4.7	0.15	1.3	0.9	
mil	max	87	181	106	205	12	63	59	12
	min	75	157	91	185	6	51	35	

The recommended mounting pad size



Unit : mm
(mil)

Marking

Type number	Marking code
US1A	US1A
US1B	US1B
US1D	US1D
US1G	US1G
US1J	US1J
US1K	US1K
US1M	US1M