

**Cabtite (cable entry system)  
CABTITE LNS M25 BK**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



For metric M20 to M63 through-holes, the Cabtite cable entry system offers separable cable glands for cables with and without plugs. In case of maintenance or changes in the system, pre-assembled cables with diameters of 2 to 35 mm can be inserted quickly and safely in panels or enclosures. Reliable sealing of IP66 in accordance with DIN EN 60529 and an absolutely secure fitting (strain relief based on DIN EN 62444) is ensured by placing slotted sealing elements with a wave cut around the cable before being inserted into one of the two halves of the cable gland. The separable system ensures easy and fast installation. After inserting the sealing element, the two halves of the cable gland are simply snapped together. A locknut, which is also separable, on the inside of the panel ensures a reliable and secure hold.

**General ordering data**

Type	CABTITE LNS M25 BK
Order No.	<a href="#">2584090000</a>
Version	Locknut, Cabtite (cable entry system), Polyamide, glass fibre-reinforced, Deep black, Height: 7 mm, Width: 7 mm, Depth: 7 mm, -40 °C...120 °C
GTIN (EAN)	4050118616316
Qty.	10 pc(s).

**Cabtite (cable entry system)  
CABTITE LNS M25 BK**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Technical data****Dimensions and weights**

Length	33 mm	Length (inches)	1.299 inch
Width	7 mm	Width (inches)	0.276 inch
Height	7 mm	Height (inches)	0.276 inch
Depth	7 mm	Depth (inches)	0.276 inch
Net weight	99,999 g	Diameter	36 mm

**General information**

UL 94 flammability rating	V-0	External thread	M 25
Pitch of thread	1.5 mm	AF size 1	33 mm
AF size 2	36 mm	Halogen	No
Silicone	No	Material	Polyamide, glass fibre-reinforced

**Classifications**

ETIM 6.0	EC000940	eClass 6.2	27-14-92-01
eClass 9.1	27-14-44-24		

**Approvals**

ROHS	Conform
------	---------