



For the latest products,
information, innovations and
solutions, go to
bannerengineering.com

P/N 178074

Banner Engineering Corp.

9714 Tenth Avenue North
Minneapolis, Minnesota 55441
763-544-3164 • 1-888-373-6767
www.bannerengineering.com



Cordsets

Euro QD for DC and <i>Expert</i> models					
See page 908					
Length	Straight		Right-Angle		
	4-Pin	5-Pin	4-Pin	5-Pin	
1.83 m		MQDC-406	MQDC1-506		MQDC-406RA MQDC1-506RA
4.57 m		MQDC-415	MQDC1-515		MQDC-415RA MQDC1-515RA
9.14 m		MQDC-430	MQDC1-530		MQDC-430RA MQDC1-530RA

Micro QD for AC models			
See page 925			
Length	Threaded 3-Pin		
	Straight	Right-Angle	
1.83 m		MQDC-306	MQDC-306RA
4.57 m		MQDC-315	MQDC-315RA
9.14 m		MQDC-330	MQDC-330RA

NAMUR Euro QD (for Q models)			
See page 909			
Length	Threaded 4-Pin		
	Straight	Right-Angle	
1.83 m		MQD9-406	MQD9-406RA
4.57 m		MQD9-415	MQD9-415RA


 Additional cordset information available.
See page 904.

Brackets

MINI-BEAM				
See page 859	See page 860	See page 861	See page 862	See page 861
SMB18A	SMB18FA..	SMB18SF	SMB312B	SMB3018SC
				

 Additional brackets and information available.
See page 846.

Other Accessories

Reflectors	Apertures
See page 940	See page 966
	





4-Pin Threaded M12/Euro-Style Cordsets with Shield

Cable: PVC jacket, PUR (polyurethane) connector body, nickel-plated brass coupling nut

Conductors: 22 AWG (shielded), gold-plated contacts

Voltage/Current Rating: 250 V ac/dc, 4.0 A

Temperature: -40° to +105° C **Environmental Rating:** IP67

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
Straight	1.83 m	MQDEC2-406	5.20 mm		Female  1 = Brown 2 = White 3 = Blue 4 = Black	• QS18U • T30UX
	4.57 m	MQDEC2-415				
	9.14 m	MQDEC2-430				
Right-Angle	1.83 m	MQDEC2-406RA	5.20 mm		Female  1 = Brown 2 = White 3 = Blue 4 = Black	
	4.57 m	MQDEC2-415RA				
	9.14 m	MQDEC2-430RA				





4-Pin Threaded M12/Euro-Style Cordsets (for use with NAMUR sensors)

Cable: PVC jacket, PUR (polyurethane) connector body, nickel-plated brass coupling nut

Conductors: 20 AWG, gold-plated contacts

Voltage/Current Rating: 250 V ac/dc, 4.0 A

Temperature: -40° to +105° C **Environmental Rating:** IP67

Style	Length	Model	Cable Diameter	Dimensions (mm)	Pinout	Used With
Straight	1.83 m	MQD9-406	5.20 mm		Female  1 = Brown 2 = Blue	• MINI-BEAM & Q45 NAMUR sensors
	4.57 m	MQD9-415				
	9.14 m	MQD9-430				
Right-Angle	1.83 m	MQD9-406RA	5.20 mm		Female  1 = Brown 2 = Blue	
	4.57 m	MQD9-415RA				
	9.14 m	MQD9-430RA				