

<b>Product Name:</b>	HPL – 514 Minitek PWR	
	Minitek Power 4.2	
<b>Product Manager:</b>	Jithin George	
<b>Subject:</b>	Notification of Change with Immediate Effectivity	
<b>Distribution:</b>	Affected customers	
<b>Type of Change:</b>	Design Change	
<b>Change Description:</b>	1. Modification of conductor crimp height and width of 16AWG Terminal 2. Introducing chamfer to the Outside Edge of the Terminal	
<b>Reason for Change:</b>	1. Product improvement to be aligned with the requirement specified in IEC60352-2 Edition 3.0 standard 2. To prevent the plastic material shaving during terminals insertion into housing	
<b>Affected Parts:</b>		
<b>Effective Date of Change:</b>	April,15 2024	
<b>Last Time Buy Date:</b>	NA	
<b>Earliest Disty Return Date:</b>	NA	
<b>Last Time Shipment Date</b>	NA	
<b>Datasheet Attached?</b>	Yes	
<b>Qual/Test Data Attached?</b>	Yes	
<b>Samples Availability Date:</b>	30 January ,2024	
<b>Available Alternatives?</b>		
<b>Questions?</b>	<i>Contact your local ACS Representative, or Product Manager</i>	
	<i>Jithin George / Product Manager</i>	
	<i>Jithin.George@amphenol-fci.com</i>	

Note:  
Customers should contact Product Line Manager (or their local Amphenol Representative) directly regarding any concern on the PCN.  
Lack of any such customer feedback within three weeks of PCN release date will be interpreted as non-objection .