

## Cable Ties

### Catalogue Number Construction

|                                               |                 |                                                                       |                                                                                                                                                                                                                                                |                 |                                   |                                                                              |
|-----------------------------------------------|-----------------|-----------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------------------------|------------------------------------------------------------------------------|
| <b><u>L</u></b>                               | <b><u>4</u></b> | <b><u>18</u></b>                                                      | <b><u>HS</u></b>                                                                                                                                                                                                                               | <b><u>-</u></b> | <b><u>9</u></b>                   | <b><u>M</u></b>                                                              |
| <b>Product Prefix</b>                         | <b>Length</b>   | <b>Tensile Strength</b>                                               | <b>Type of Product</b>                                                                                                                                                                                                                         |                 | <b>Colour</b><br>See Colour Table | <b>Quantity</b>                                                              |
| P - Plain Bagged Cable Ties<br>L - Cable Ties |                 | 18 lb.<br>30 lb.<br>40 lb.<br>50 lb.<br>120 lb.<br>175 lb.<br>250 lb. | Nylon 66 - Leave Blank<br>Heat Stabilized - HS<br>(Black and Natural Colour Only)<br>Fluorescent - FL<br>Mounting Head - MH<br>Pushmount - PM<br>Pushmount Releasable - PMR<br>Releasable - R<br>Restricted Bundle - TB<br>Identification - ID |                 |                                   | Q - 25 pack<br>L - 50 pack<br>C - 100 pack<br>D - 500 pack<br>M - 1,000 pack |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                     |                 |                   |                 |                                   |                                                                              |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-----------------|-------------------|-----------------|-----------------------------------|------------------------------------------------------------------------------|
| <b><u>MP</u></b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <b><u>NY</u></b>                                                                                    | <b><u>-</u></b> | <b><u>750</u></b> | <b><u>-</u></b> | <b><u>9</u></b>                   | <b><u>C</u></b>                                                              |
| <b>Product Prefix</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | <b>Material</b>                                                                                     |                 | <b>Size / #</b>   |                 | <b>Colour</b><br>See Colour Table | <b>Quantity</b>                                                              |
| MP - Mounting Pad<br>ID - Identification<br>S# - Strapping Thickness<br>MC - Mounting Cradle<br>PM - Push Mounts<br>SM - Screw Mounts<br>N# - Plain-Edged Cable Clamps / Width<br>W# - Self-Aligning Cable Clamps / Dia.<br>UL - Adjustable Cable Clamps<br>GG - Gator Grip<br>FA - Flat Adhesive Clip<br>FS - Flat Screw Clip<br>FR - Flat Rubber Adhesive Clip<br>MS - Snap Mount<br>RA - Round Adhesive Clip<br>SR - Spiral Wrap<br>GS - Grommeting<br>GR - Extruded Grommeting<br>GRU - Extruded Grommeting Uncut | Nylon<br>TZ - Fluoropolymer<br>PV - PVC<br>PE - Polyethylene<br>FR - Flame Retardant<br>TL - Teflon |                 | .75"              |                 |                                   | Q - 25 pack<br>L - 50 pack<br>C - 100 pack<br>D - 500 pack<br>M - 1,000 pack |

#### Colour Table


|                                  |                         |
|----------------------------------|-------------------------|
| 0 - Black<br>(Weather-Resistant) | 7 - Purple              |
| 1 - Brown                        | 8 - Grey                |
| 2 - Red                          | 9 - Natural             |
| 3 - Orange                       | 11 - Fluorescent Pink   |
| 4 - Yellow                       | 16 - Fluorescent Orange |
| 5 - Green                        | 17 - Fluorescent Yellow |
| 6 - Blue                         | 18 - Fluorescent Green  |
|                                  | 20 - Fluorescent Blue   |

## Cable Ties



| Cat. No.                   | Length (in.) | Max. Bundle Dia. (in.) | Colour  | Std. Pkg. |
|----------------------------|--------------|------------------------|---------|-----------|
| <b>Identification Ties</b> |              |                        |         |           |
| <b>L-7-50ID-9-C</b>        | 7.875        | 1-3/4                  | Natural | 100       |
| <b>L-4-18ID-9-C</b>        | 4.0          | 3/4                    | Natural |           |

Bulk packages available. Contact your Regional Sales Office.  
Use QC-100, L-200, L-400-C or ERG-50 Installation Tools.



| Cat. No.                   | Width (in.) | Height (in.) | Slot Height (in.) | Slot Width (in.) | Colour  | Std. Pkg. |
|----------------------------|-------------|--------------|-------------------|------------------|---------|-----------|
| <b>Identification Tags</b> |             |              |                   |                  |         |           |
| <b>IDNY-1500-9-M</b>       | 1.5         | 0.745        | 0.090             | 0.200            | Natural | 100       |
| <b>IDNY-2000-9-M</b>       | 2.0         |              | 0.113             | 0.336            | Natural |           |



- 3/4 in. and 1-1/8 in. mounts for use with 18# through 50# tensile cable ties
- Supplied on rubber-based or acrylic closed cell foam adhesive or with no adhesive for #6 screw mount applications
- Available in 6.6 Natural Nylon and 6.6 Black Nylon
- UL Flammability 94 V-2 (clip)

| Cat. No.                        | Mount Method              | Colour        |
|---------------------------------|---------------------------|---------------|
| <b>Cable Tie Mounting Bases</b> |                           |               |
| 3/4 in. Class                   |                           |               |
| <b>MPNY-750-9-C</b>             | Synthetic Rubber Adhesive | Natural       |
| <b>MPNY-750-0-C</b>             | Synthetic Rubber Adhesive | Black         |
| <b>MPNY-750A-9-C</b>            | Acrylic Adhesive          | Natural       |
| <b>MPNY-750A-0-C</b>            | Acrylic Adhesive          | Black         |
| <b>MPNY-750S-9-C</b>            | #6 Screw                  | Natural       |
| <b>MPNY-750S-0-C</b>            | #6 Screw                  | Black         |
| 1 in. Class                     |                           |               |
| <b>MPNY-1000-9-C</b>            | Synthetic Rubber Adhesive | Natural Nylon |
| <b>MPNY-1000-0-C</b>            | Synthetic Rubber Adhesive | Black Nylon   |
| <b>MPNY-1000A-9-C</b>           | Acrylic Adhesive          | Natural Nylon |
| <b>MPNY-1000A-0-C</b>           | Acrylic Adhesive          | Black Nylon   |
| <b>MPNY-1000S-9-C</b>           | #6 Screw                  | Natural Nylon |
| <b>MPNY-1000S-0-C</b>           | #6 Screw                  | Black Nylon   |

For use with 18–50 lb. Cable Ties.

- Mounting Surface should be cleaned with alcohol based (IPA) cleaner before application
- Acrylic Based may be repositioned initially. Allow 24–72 hours setup for maximum performance with Acrylic Based adhesives
- For Rubber Based, allow 15 minutes setup for maximum performance