



The DNA of tech.™

Product Information Notification

Product Group: SIL/Thu Apr 4, 2024/PIN-SIL-000504-2024-REV-0



SIC534 Datasheet Update

For further information, please contact your regional Vishay office.

CONTACT INFORMATION

Americas

Vishay Americas
2585 Junction Avenue
-
San Jose United States 95134- 1923
Phone: 408-988-8000
Fax: 408-988-8000
-

Europe

Vishay Europe Sales GmbH
Dr Felix Zandman Platz 1
-
Selb Germany 95101
Phone: 49-9287-710
Fax: 49-9287-70435
-

Asia

Vishay Intertechnology Asia Pte.Ltd
37A Tampines Street 92
#07-01
Singapore Singapore Singapore 528886
Phone: 65-6788-6668
Fax: 65-6788-0988
business-asia@vishay.com

Description of Change: Current datasheet describes peak current to be 35A. Further application validation shows the peak current rating can be increased to 40A.

Reason for Change: 40A peak current capability is desired for some applications.

Expected Influence on Quality/Reliability/Performance: There will be no effect on performance, quality or reliability.

Part Numbers/Series/Families Affected: SIC534CD-T1-GE3

Vishay Brand(S): Vishay Siliconix

Time Schedule:

Start Shipment Date: Mon May 6, 2024


Sample Availability: Samples are available now

Product Identification: Lot Number and Country of Origin

Qualification Data: Available upon Request

Issued By: Lisette Saba, malinalisette.saba@vishay.com

Updated Datasheet

**VISHAY**
www.vishay.com

SiC534
Vishay Siliconix

30 A VRPower® Integrated Power Stage

DESCRIPTION

The SiC534 is an integrated power stage solution optimized for synchronous buck applications to offer high current, high efficiency, and high power density performance. Packaged in Vishay's proprietary 4.5 mm x 3.5 mm MLP package, SiC534 enables voltage regulator designs to deliver up to 30 A continuous current per phase.

The internal power MOSFETs utilize Vishay's state-of-the-art Gen IV TrenchFET® technology that delivers industry benchmark performance to significantly reduce switching and conduction losses.

The SiC534 incorporates an advanced MOSFET gate driver IC that features high current driving capability, adaptive dead-time control, an integrated bootstrap Schottky diode, and zero current detection to improve light load efficiency. The driver is also compatible with a wide range of PWM controllers, supports tri-state PWM, and 5 V PWM logic.


A user selectable diode emulation mode (ZCD_EN#) is included to improve the light load performance. The device also supports PS4 mode to reduce power consumption when system operates in standby state.

FEATURES


- Thermally enhanced PowerPAK® MLP4535-22L package
- Vishay's Gen IV MOSFET technology and a low-side MOSFET with integrated Schottky diode
- Delivers up to 30 A continuous current, 40 A at 10 ms peak current
- High efficiency performance
- High frequency operation up to 2 MHz
- Power on reset
- 5 V PWM logic with tri-state and hold-off
- Supports PS4 mode light load requirement for IMVP8 with low shutdown supply current (5 V, 3 μ A)
- Under voltage lockout for V_{CIN}
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

APPLICATIONS

- Multi-phase VRDs for computing, graphics card and memory
- Intel IMVP-8 VRPower delivery
 - V_{CORE} , $V_{GRAPHICS}$, $V_{SYSTEM\ AGENT}$ Skylake, Kabylake platforms
 - V_{CCGI} for Apollo Lake platforms
- Up to 24 V rail input DC/DC VR modules



Previous Datasheet

**VISHAY**
www.vishay.com

SiC534
Vishay Siliconix

30 A VRPower® Integrated Power Stage

DESCRIPTION

The SiC534 is an integrated power stage solution optimized for synchronous buck applications to offer high current, high efficiency, and high power density performance. Packaged in Vishay's proprietary 4.5 mm x 3.5 mm MLP package, SiC534 enables voltage regulator designs to deliver up to 30 A continuous current per phase.

The internal power MOSFETs utilize Vishay's state-of-the-art Gen IV TrenchFET® technology that delivers industry benchmark performance to significantly reduce switching and conduction losses.

The SiC534 incorporates an advanced MOSFET gate driver IC that features high current driving capability, adaptive dead-time control, an integrated bootstrap Schottky diode, and zero current detection to improve light load efficiency. The driver is also compatible with a wide range of PWM controllers, supports tri-state PWM, and 5 V PWM logic.

A user selectable diode emulation mode (ZCD_EN#) is included to improve the light load performance. The device also supports PS4 mode to reduce power consumption when system operates in standby state.

FEATURES

- Thermally enhanced PowerPAK® MLP4535-22L package
- Vishay's Gen IV MOSFET technology and a low-side MOSFET with integrated Schottky diode
- Delivers up to 30 A continuous current, 35 A at 10 ms peak current
- High efficiency performance
- High frequency operation up to 2 MHz
- Power on reset
- 5 V PWM logic with tri-state and hold-off
- Supports PS4 mode light load requirement for IMVP8 with low shutdown supply current (5 V, 3 μ A)
- Under voltage lockout for V_{CIN}
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

APPLICATIONS

- Multi-phase VRDs for computing, graphics card and memory
- Intel IMVP-8 VRPower delivery
 - V_{CORE} , $V_{GRAPHICS}$, $V_{SYSTEM\ AGENT}$ Skylake, Kabylake platforms
 - V_{CCGI} for Apollo Lake platforms
- Up to 24 V rail input DC/DC VR modules

