

Product change notification (PCN)

Title / short description	AXL F DI8/1 DO8/1 ... - Hardware change
Affected article category	SPS and I/O systems
Change category	Material, Marking
Change number	CDR240017-00
Reason for PCN/PDN Revision	

Purpose/objective of the change

Ensure delivery capacity

Detailed description of the change

To improve the delivery capability, the hardware is changed.
The input IC is exchanged for a compatible alternative.
For traceability the hardware version is increased.
The function of the items does not change.

Identifying characteristics

Increase to the production batch (V/C) and the hardware version (HW).

Start of Production (SOP)	-	Last Time Delivery (LTD)	-
Effective date (EOP)	2024-12-15	End of Service (EOSR)	-
End of Sales (EOS)	-		

Short-term change (< 6 months) or discontinuation (< 12 months), due to:

- | | | |
|---|---|--|
| ☐ Software / Firmware Bugfix | ☐ Short-term delivery stop by supplier | ☐ Short-term recall by supplier |
| ☐ Force majeure | ☐ Product improvement with customer benefits | |
| ☐ Others | | |

Attachments

- CDR240017_printing_change.jpg
- Material_list.csv
- PCN-CDR240017-00_DE
- PCN-CDR240017-00_EN

Material list

Item no.	Item Type	Hardware / Firmware		Item no.	Substitute item Type
		old	new		
2701916	AXL F DI8/1 DO8/1 1H	HW02 / FW100 (V/C: 06)	HW03 / FW100 (V/C: 07)		
2702017	AXL F DI8/1 DO8/1 XC 1H	HW03 / FW100 (V/C: 06)	HW04 / FW100 (V/C: 07)		

Axioline



AXL F DI8/1 DO8/1 1H
Order No.: 2701916

HW/FW: 02/100



XXXXXXXXXX (Seriennr.)



Type: Voltage Current
U_{IO} : 24 VDC 8 A
U_{BUS} : 5 VDC 60 mA
IN : 24 VDC 8 chl. 2.4 mA each
OUT: 24 VDC 8 chl. 0.5 A each

Phoenix Contact GmbH & Co. KG
Flachsmarktstraße 8
32825 Blomberg / Germany
www.phoenixcontact.com



Wire Range: 24-16 AWG



Amb. Temp.: 60°C



LISTED
PROG. CNTLR.
E238705



UK
CA



Axioline



AXL F DI8/1 DO8/1 1H
Order No.: 2701916

HW/FW: 03/100



XXXXXXXXXX (Seriennr.)



Type: Voltage Current
U_{IO} : 24 VDC 8 A
U_{BUS} : 5 VDC 60 mA
IN : 24 VDC 8 chl. 2.4 mA each
OUT: 24 VDC 8 chl. 0.5 A each

Phoenix Contact GmbH & Co. KG
Flachsmarktstraße 8
32825 Blomberg / Germany
www.phoenixcontact.com



Wire Range: 24-16 AWG



Amb. Temp.: 60°C



LISTED
PROG. CNTLR.
E238705



UK
CA