



Assembly Specifications	
Temp Rating	-20 to 80 C
Max Voltage	60V
Max Current	3A
IP Protection	IP 67
Length (L)	119in / 3023mm
Tolerance	+2.0in -2.0in

Wiring Schematic		
A Pin #	Conductor Color	B Pin #
1	Black	1
2		2
3	Blue	3
4	Orange	4
5		5
6		6
7		7
8		8
Shield	Attached	Shield

Cable Specifications	
Cable Jacket	PVC
Cable OD	0.19in / 4.8mm
No./Gauge	M46B-424
Conductor Jacket	PVC
Shielding	Yes



- Notes**
- Connector pin view is from front of connector
 - Not for interrupting current
 - Some options and features may not be shown
 - Additional technical details available upon request; Consult Factory
 - Dimension in parentheses are for reference only

REV	BY	DATE	DESCRIPTION	Tolerance Unless Otherwise Specified
0	MMG	01/04/22	Initial Release	0.00 = +/- 0.13
1	MMG	03/16/22	Production Release	0.000 = +/- 0.050
				ANGLES = +/- 5
				Secondary Unit 50t
				Reference Only



1200 East St, Fairport, OHIO 44077
 PH: (440) 350-1230 www.mjmindustries.com

Part Number:
M08A03M1-0119B-M08A03F9

Description:
 M08 A Coded 3 Position Male Straight to M08 A Coded 3 Position Female 90 with 119in of PVC Cable

