LB1D LB2D HB11D

LED High Bay

Features Housing

Die-formed Cold-rolled Steel and V Hook & Hanging Chain Included Eco-frame & full Body Linear Construction

Optical

High Transmission Acrylic Shade

Electrical

UL2459 / CSA182.3 Power Connector Included

Integrate LED Module with High Lumen Efficiency and High CRI Rated 50,000 Hours LED Life

Certification

ETL/cETL Listed, DLC Premium Listed

5 Years Limited Warranty on Driver and LED

Options

-LS with Lens

-EM with Built-in Emergency Driver or External Emergency Driver

Bi-Level Dimming -Bi





LB1D-LS







LB2D/HB11D LB2D-LS/HB11D-LS

DLC Premium Models

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Dimension (L x W x H)	DLC Premium
LB1D-42W-VHO-4000K	120V ~ 277V	42W	4000K	80	5730	21.0" x 9.0" x 3.5"	Premium
LB1D-42W-VHO-5000K	120V ~ 277V	42W	5000K	80	5780	21.0" x 9.0" x 3.5"	Premium
LB2D-65W-VHO-4000K	120V ~ 277V	62W	4000K	80	8640	21.0" x 12.0" x 3.5"	Premium
LB2D-65W-VHO-5000K	120V ~ 277V	62W	5000K	80	8720	21.0" x 12.0" x 3.5"	Premium
HB11D-130W-VHO-4000K	120V ~ 277V	125W	4000K	80	17630	43.0" x12.0" x 3.5"	Premium
HB11D-130W-VHO-5000K	120V ~ 277V	125W	5000K	80	17830	43.0" x12.0" x 3.5"	Premium