



130 W Cochran St, Unit B
Simi Valley, CA 93065
Tel:818-701-4933

Process Change Notification (PCN)

Notification number:	051024-1
Notification date:	10 May 2024
Proposed implementation date:	10 Aug 2024 (90 days notification before change, according to JEDEC standard)
Product type affected:	Please refer to table 1 in Appendix 1.
Change Category	Assembly process / mold chase for SOD923 products
Change Classification	Major
Change description:	To add a new mold chase to increase production capacity. Remark: Full electrical characterization and high reliability testing has been completed to ensure there is no change to device functionality or electrical specifications in the datasheet.
Reason for change:	To support increasing market demand and supply continuity.
Deposition of old product	Existing inventory will keep shipping until depleted
Identification of Changed product:	No changes to product marking
Contact person:	Please contact your respective Account manager (AM) / Inside sales representative (ISR/CSR) if you have further query.
Approved by:	Jason Gao (Director of Engineering) Steve Zhang (Director of Supply Chain) Seaman Wu (Director of Quality) Pamela Cheng (GM & EVP of Sales)




130 W Cochran St, Unit B
Simi Valley, CA 93065
Tel:818-701-4933

Appendix 1: Table 1

No.	Product type	Existing marking	New marking	Package type/code
1	BZX984B4V7-TP	X1.	X1.	SOD923
2	ESD12VD9-TP	C	C	SOD923
3	ESD3V3D9B-TP	3B	3B	SOD923
4	ESD3V3D9-TP	E1	E1	SOD923
5	ESD3V3D9-TP-HF	E1	E1	SOD923
6	ESD5V0D9B-TP	9C	9C	SOD923
7	ESD5V0D9B-TP-HF	9C	9C	SOD923
8	ESD5V0D9-TP	B	B	SOD923
9	ESD7V0D9-TP	9M	9M	SOD923
10	ESDLC5V0D9B-TP	1L	1L	SOD923
11	ESDLC5V0D9L-TP	LV	LV	SOD923
12	ESDLC5V0D9L-TP-HF	LV	LV	SOD923
13	ESDLC5V0D9-TP	9L	9L	SOD923
14	ESDLC5V0D9-TPCA01	9L	9L	SOD923
15	ESDLC5V0D9-TP-HF	9L	9L	SOD923
16	ESDSL5V0D9B-TP	4L	4L	SOD923
17	RB520CS-30-TP	E	E	SOD923
18	RB521CS-30-TP	F	F	SOD923



130 W Cochran St, Unit B
Simi Valley, CA 93065
Tel:818-701-4933

Item	Before	After																																																				
Unit View-Top																																																						
Unit View-Bottom																																																						
Unit View-Side																																																						
POD	 <table><tr><th colspan="6">DIMENSIONS</th></tr><tr><th rowspan="2">DIM</th><th colspan="2">INCHES</th><th colspan="2">MM</th><th rowspan="2">NOTE</th></tr><tr><th>MIN</th><th>MAX</th><th>MIN</th><th>MAX</th></tr><tr><td>A</td><td>0.037</td><td>0.041</td><td>0.95</td><td>1.05</td><td></td></tr><tr><td>B</td><td>0.030</td><td>0.033</td><td>0.75</td><td>0.85</td><td></td></tr><tr><td>C</td><td>0.022</td><td>0.026</td><td>0.55</td><td>0.65</td><td></td></tr><tr><td>D</td><td>0.014</td><td>0.017</td><td>0.36</td><td>0.43</td><td></td></tr><tr><td>E</td><td>0.006</td><td>0.010</td><td>0.15</td><td>0.25</td><td></td></tr><tr><td>F</td><td>0.003</td><td>0.007</td><td>0.07</td><td>0.17</td><td></td></tr></table>		DIMENSIONS						DIM	INCHES		MM		NOTE	MIN	MAX	MIN	MAX	A	0.037	0.041	0.95	1.05		B	0.030	0.033	0.75	0.85		C	0.022	0.026	0.55	0.65		D	0.014	0.017	0.36	0.43		E	0.006	0.010	0.15	0.25		F	0.003	0.007	0.07	0.17	
DIMENSIONS																																																						
DIM	INCHES		MM		NOTE																																																	
	MIN	MAX	MIN	MAX																																																		
A	0.037	0.041	0.95	1.05																																																		
B	0.030	0.033	0.75	0.85																																																		
C	0.022	0.026	0.55	0.65																																																		
D	0.014	0.017	0.36	0.43																																																		
E	0.006	0.010	0.15	0.25																																																		
F	0.003	0.007	0.07	0.17																																																		
Remark	No change to POD																																																					



130 W Cochran St, Unit B
Simi Valley, CA 93065
Tel: 818-701-4933

Date: 10 May 2024

PCN #: 051024-1

PCN Title: Assembly process / mold chase for SOD923 products

Dear Customer.

This is a PCN announcement to the above-mentioned product which is/are offered by Micro Commercial Components Corp (MCC). We would appreciate your acknowledgement of receipt of this notification within 30 days of the date of this PCN to your local ISR, sales representative. Please refer to the attached document for more information (including implementation date / product date code of this change). If you have any questions or concerns related to this PCN, please contact your local sales representative / ISR for support. *Sincerely, MCC PCN Team*

Thank you.

Yours sincerely,

PCN Team



130 W Cochran St, Unit B
Simi Valley, CA 93065
Tel:818-701-4933

Reliability Report

Part Number: ESDLC5V0D9-TP

Date: 2024-01-27

Test Results : PASS

Test Item	Conditions	Duration	Quantity	Rejects
TEST Pre- and Post-Stress Electrical Test	T _a = 25 °C	N/A	all parts	see below
* Pre-conditioning for MSL 1	JESD22A-113 1. Temperature Cycling: -40 °C ~ 60 °C, 2. Bake: 125 °C, 3. Moisture Soak: 85 °C, 8 5%RH for MSL1; 4. Reflow*3Cycles: 260 °C	5Cycles; 24 hours; 192hours 3Cycles	308Pcs	0
HTRB High Temperature Reverse Bias	MIL-STD-750 Method 1038 T _j = T _{jmax} , 100% VR	1000 hours	77Pcs	0
TC Temperature Cycling	JESD22-A104 -55 °C (+0,-10)/15Min~ 150(+15,-0)/15Min,	1000Cycles (500hours)	77Pcs	0
AC Autoclave	JESD22-A102 T _a = 121 °C±2 °C, RH = 100 %, 15psig	96 hours	77Pcs	0
H3TRB High Humidity High Temperature Reverse Bias	JESD22-A101 T _a = 85 °C±2 °C, RH = 85%±5%, 100 % VR (VR MAX=100V)	1000 hours	77Pcs	0
RSH Resistance to Solder Heat	JESD22-B106 260 °C (+5, -0)	10 s	30Pcs	0
SD Solderability	J-STD-002 235 °C ± 5 °C	3 s	10Pcs	0
HTSL High Temperature Storage Life	JESD22-A103 TstgMax	1000 hours	77Pcs	0

*Remark : detail MSL of product refer to data sheet on MCC website.