

K-no.: 24509

6 A Current Sensor modul for 5V-Supply voltage

Date: 08.04.2008

For electronic current measurement:
DC, AC, pulsed, mixed ..., with a galvanic
isolation between primary circuit
(high power) and secondary circuit
(electronic circuit)

Customer: Standard type

Customers Part no.:

Page 1 of 2

Description

- Closed loop (compensation)
Current Sensor with magnetic
field probe
- Printed circuit board mounting
- Casing and materials UL-listed

Characteristics

- Excellent accuracy
- Very low offset current
- Very low temperature dependency and offset
current drift
- Very low hysteresis of offset current
- Short response time
- Wide frequency bandwidth
- Compact design
- Reduced offset ripple

Applications

Mainly used for stationary operation in industrial
applications:

- AC variable speed drives and servo motor
drives
- Static converters for DC motor drives
- Battery supplied applications
- Switched Mode Power Supplies (SMPS)
- Power Supplies for welding applications
- Uninterruptible Power Supplies (UPS)

Electrical data – Ratings

I_{PN}	Primary nominal r.m.s. current	6	A
V_{out}	Output voltage @ I_P	$2.5 \pm (0.625 \cdot I_P / I_{PN})$	V
V_{out}	Output voltage @ $I_P=0$, $T_A=25^\circ\text{C}$	2.5 ± 0.025	V
V_{Ref}	Reference voltage	2.5 ± 0.005	V
K_N	Turns ratio	1...3 : 2000	

Accuracy – Dynamic performance data

		min.	typ.	max.	Unit
$I_{P,max}$	Max. measuring range	± 20			
X	Accuracy @ I_{PN} , $T_A=25^\circ\text{C}$			0.7	%
ϵ_L	Linearity			0.1	%
$V_{out} -2,5V$	Offset voltage @ $I_P=0$, $T_A=25^\circ\text{C}$			± 25	mV
$\Delta V_{out} / 2,5V / \Delta T$	Temperature drift of V_{out} @ $I_P=0$, $T_A=-40...85^\circ\text{C}$		26	51	ppm/K
t_r	Response time @ 90% von I_{PN}		300		ns
$\Delta t (I_{P,max})$	Delay time at $di/dt = 100 \text{ A}/\mu\text{s}$		200		ns
f	Frequency bandwidth	DC...100			kHz

General data

		min.	typ.	max.	Unit
T_A	Ambient operating temperature	-40		+85	$^\circ\text{C}$
T_S	Ambient storage temperature	-40		+85	$^\circ\text{C}$
m	Mass		12		g
V_C	Supply voltage	4.75	5	5.25	V
I_C	Current consumption		15		mA

Constructed and manufactured and tested in accordance with EN 61800-5-1 (Pin 1 - 6 to Pin 7 – 9)
Reinforced insulation, Insulation material group 1, Pollution degree 2

S_{clear}	Clearance (component without solder pad)	7			mm
S_{creep}	Creepage (component without solder pad)	7			mm
V_{sys}	System voltage	overvoltage category 3	RMS	300	V
V_{work}	Working voltage	(tabel 7 acc. to EN61800-5-1) overvoltage category 2	RMS	650	V
U_{PD}	Rated discharge voltage	peak value		1320	V

Date Name Issue Amendment

08.04.08 Le 82 "preliminary" delete.

Hrsg.: KB-E
editor

Bearb: Le.
designer

KB-PM: KRe
check

freig.: Heu.
released

K-no.: 24509

6 A Current Sensor modul for 5V-Supply voltage

Date: 08.04.2008

For electronic current measurement:
DC, AC, pulsed, mixed ..., with a galvanic
isolation between primary circuit
(high power) and secondary circuit
(electronic circuit)

Customer: Standard type

Customers Part no.:

Page 2 of 2


Mechanical outline (mm):

General tolerances DIN ISO 2768-c

Connections:


1...6: $\varnothing$ 1 mm

7...9: 0,46*0,46 mm



Marking:

VAC
4646X653
F DC

Schematic diagram

Possibilities of wiring (@ $T_A = 85^\circ\text{C}$)

primary windings	primary current RMS	primary current maximal	output voltage RMS	turns ratio	primary resistance	wiring
N_P	I_P [A]	$\hat{I}_{P,max}$ [A]	$V_{out}(I_{PN})$ [V]	K_N	R_P [mW]	
1	6	± 20	2.5 ± 0.625	1:2000	0.33	
2	3	± 10	2.5 ± 0.625	2:2000	1.5	
3	2	± 6.7	2.5 ± 0.625	3:2000	3	

Temperature of the primary conductor should not exceed 110°C .
Additional information is obtainable on request.
This specification is no declaration of warranty acc. BGB §443 dar.

Hrsg.: KB-E
editor

Bearb.: Le.
designer

KB-PM: KRe
check

freig.: Heu.
released

K-No.: 24509

6 A Current Sensor Modul for 5V-supply voltage

Date: 08.04.2008

For the electronic measurement of currents:
DC, AC, pulsed, mixed ..., with a galvanic
Isolation between the primary circuit
(high power) and the secondary circuit

Customer:

Customers Part No.:

Page 1 of 2

Electrical Data

		min.	typ.	max.	Unit
V_{Ctot}	Maximum supply voltage (without function)			6	V
I_C	Supply Current with primary current	15mA	$+I_P \cdot K_N + V_{out}/R_L$		mA
$I_{out,SC}$	Short circuit output current		± 20		mA
R_P	Resistance / primary winding @ $T_A=25^\circ C$		1		m Ω
R_S	Secondary coil resistance @ $T_A=85^\circ C$			67	Ω
$R_{i,(V_{out})}$	Output resistance of V_{out}			1	Ω
R_L	External recommended resistance of V_{out}	1			k Ω
C_L	External recommended capacitance of V_{out}			500	pF
$\Delta X_T/\Delta T$	Temperature drift of X @ $T_A = -40 \dots +85^\circ C$			40	ppm/K
$\Delta V_0 = \Delta(V_{out}-2.5V)$	Sum of any offset drift including:		9	20	mV
V_{0t}	Long term drift of V_0		3		mV
V_{0T}	Temperature drift von V_0 @ $T_A = -40 \dots +85^\circ C$		8		mV
V_{0H}	Hysteresis of V_{out} @ $I_P=0$ (after an overload of $10 \times I_{PN}$)		7.5	mV	
$\Delta V_0/\Delta V_C$	Supply voltage rejection ratio			1	mV/V
V_{OSS}	Offsetripple (with 1 MHz- filter first order)			100	mV
V_{OSS}	Offsetripple (with 100 kHz- filter first order)		10	20	mV
V_{OSS}	Offsetripple (with 20 kHz- filter first order)		2.5	5	mV
C_k	Maximum possible coupling capacity (primary – secondary)		5	10	pF
	Mechanical stress according to M3209/3 Settings: 10 – 2000 Hz, 1 min/Decade, 2 hours			30g	

Inspection¹⁾ (Measurement after temperature balance of the samples at room temperature)

$V_{out}(I_P=I_{PN})$	(V)	M3011/6:	Output voltage vs. internal reference ($I_P=6A$, 40-80Hz)	625 $\pm$ 0.7%	mV
$V_{out}-2.5V(I_P=0)$	(V)	M3226:	Offset voltage	± 0.025	V
V_d	(V)	M3014:	Test voltage, rms, 1 s pin 1 – 6 vs. pin 7 – 9	1.5	kV
V_e	(AQL 1/S4)		Partial discharge voltage acc.M3024 (RMS) with V_{vor} (RMS)	1400 1750	V V

Type Testing¹⁾ (Pin 1 - 6 to Pin 7 - 9)

Designed according standard EN 50178 with insulation material group 1

V _W	HV transient test according to M3064 (1,2 μs / 50 μs-wave form)	8	kV
V _d	Testing voltage to M3014 (5 s)	3	kV
V _e	Partial discharge voltage acc.M3024 (RMS)	1400	V
	with V _{vor} (RMS)	1750	V

¹⁾ preliminary data

Applicable documents

Current direction: A positive output current appears at point I_S , by primary current in direction of the arrow.
Housing and bobbin material UL-listed: Flammability class 94V-0.
Enclosures according to IEC529: IP50.

Datum		Index	Änderung
08.04.08	Le	82	"preliminary" delete.
Hrsg.: KB-E	Bearb: Le	KB-PM: KRe	freig.: Heu.
editor	designer	check	released

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts
nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu
Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder GM-Eintragung vorbehalten

Copying of this document, disclosing it to third parties or using the contents there for any
purposes without express written authorization by use illegally forbidden.
Any offenders are liable to pay all relevant damages.

		Additional Information		Item No.: T60404-N4646-X653	
K-No.: 24509		6 A Current Sensor Modul for 5V-supply voltage For the electronic measurement of currents: DC, AC, pulsed, mixed ..., with a galvanic Isolation between the primary circuit (high power) and the secondary circuit			Date: 08.04.2008
Customer:			Customers Part No.:		Page 2 of 2
Explanation of several of the terms used in the tablets (in alphabetical order)					
t_r: Response time (describe the dynamic performance for the specified measurement range), measured as delay time at I _P = 0,9 · I _{PN} between a rectangular current and the output voltage V _{out} (I _p)					
Δt (I_{Pmax}): Delay time (describe the dynamic performance for the rapid current pulse rate e.g short circuit current) measured between I _{Pmax} and the output voltage V _{out} (I _{Pmax}) with a primary current rise of di _P /dt ≥ 100 A/μs.					
U_{PD} Rated discharge voltage (recurring peak voltage separated by the insulation) proved with a sinusoidal voltage V _e U _{PD} = √2 · V _e / 1,5					
V_{vor} Defined voltage is the RMS value of a sinusoidal voltage with peak value of 1,875 · U _{PD} required for partial discharge test in IEC 61800-5-1 V _{vor} = 1,875 · U _{PD} / √2					
V_{sys} System voltage RMS value of rated voltage according to IEC 61800-5-1					
V_{work} Working voltage voltage according to IEC 61800-5-1 which occurs by design in a circuit or across insulation					
V₀: Offset voltage between V _{out} and the rated reference voltage of V _{ref} = 2,5V. V ₀ = V _{out} (0) - 2,5V					
V_{0H}: Zero variation of V ₀ after overloading with a DC of tenfold the rated value					
V_{0t}: Long term drift of V ₀ after 100 temperature cycles in the range -40 bis 85 °C.					
X: Permissible measurement error in the final inspection at RT, defined by $X = 100 \cdot \left \frac{V_{out}(I_{PN}) - V_{out}(0)}{0,625V} - 1 \right \%$					
X_{ges}(I_{PN}): Permissible measurement error including any drifts over the temperature range by the current measurement I _{PN} $X_{ges} = 100 \cdot \left \frac{V_{out}(I_{PN}) - 2,5V}{0,625V} - 1 \right \%$ or $X_{ges} = 100 \cdot \left \frac{V_{out}(I_{PN}) - V_{ref}}{0,625V} - 1 \right \%$					
ε_L: Linearity fault defined by $e_L = 100 \cdot \left \frac{I_P}{I_{PN}} - \frac{V_{out}(I_P) - V_{out}(0)}{V_{out}(I_{PN}) - V_{out}(0)} \right \%$					
This "Additional information" is no declaration of warranty according BGB §443.					
Hrsg.: KB-E editor		Bearb: Le designer		KB-PM: KRe check	
				freig.: Heu. released	