



Project Number: 220319	Tracking Code: 220319_Report_Rev_2	
Requested by: Steven Xu	Date: 5/20/2013	Product Rev: 1
Part #: ET60T-00-24-06-L-RT1-GP/ET60S-00-24-06-L-RT1-GP	Tech: Kason He	Eng: Vico Zhao
Part description: ET60S/ET60T	Qty to test: 50	
Test Start: 10/22/2012	Test Completed: 12/2/2012	



## DESIGN QUALIFICATION TEST REPORT

ET60S/ET60T

ET60T-00-24-06-L-RT1-GP/ET60S-00-24-06-L-RT1-GP

Tracking Code: 220319_Report_Rev_2	Part #: ET60T-00-24-06-L-RT1-GP/ET60S-00-24-06-L-RT1-GP
Part description: ET60S/ET60T	

**REVISION HISTORY**

<b>DATA</b>	<b>REV.NUM.</b>	<b>DESCRIPTION</b>	<b>ENG</b>
<b>1/4/2013</b>	<b>1</b>	<b>Initial Issue</b>	<b>KH</b>
<b>5/20/2013</b>	<b>2</b>	<b>Insert additional CCC graph</b>	<b>CE</b>

## CERTIFICATION

All instruments and measuring equipment were calibrated to National Institute for Standards and Technology (NIST) traceable standards according to ISO 10012-1 and ANSI/NCSL 2540-1, as applicable.

All contents contained herein are the property of Samtec. No portion of this report, in part or in full shall be reproduced without prior written approval of Samtec.

## SCOPE

To perform the following tests: Design Qualification test. Please see test plan.

## APPLICABLE DOCUMENTS

Standards: EIA Publication 364

## TEST SAMPLES AND PREPARATION

- 1) All materials were manufactured in accordance with the applicable product specification.
- 2) All test samples were identified and encoded to maintain traceability throughout the test sequences.
- 3) After soldering, the parts to be used for LLCR testing were cleaned according to TLWI-0001.
- 4) Either an automated cleaning procedure or an ultrasonic cleaning procedure may be used.
- 5) The automated procedure is used with aqueous compatible soldering materials.
- 6) Parts not intended for testing LLCR are visually inspected and cleaned if necessary.
- 7) Any additional preparation will be noted in the individual test sequences.
- 8) Solder Information: Lead Free
- 9) Samtec Test PCBs used: PCB-103705-TST/PCB-103706-TST//PCB-103697-TST  
PCB-103818-TST/PCB-103819-TST

**FLOWCHARTS****Gas Tight**

TEST STEP	GROUP A1 192 Points
01	LLCR-1
02	Gas Tight
03	LLCR-2

Gas Tight = EIA-364-36A

LLCR = EIA-364-23, LLCR

20 mV Max, 100 mA Max

Use Keithley 580 or 3706 in 4 wire dry circuit mode

Max delta allowed is 20 mOhms

**Normal Force**

TEST STEP	GROUP A1 Individual Contacts (8-10 min)	GROUP A2 Individual Contacts (8-10 min)	GROUP B1 Power - Individual Contacts (8-10 min)	GROUP B2 Power - Individual Contacts (8-10 min)
01	Contact Gaps	Contact Gaps	Contact Gaps	Contact Gaps
02	Setup Approved	Thermal Aging (Mated and Undisturbed)	Setup Approved	Thermal Aging (Mated and Undisturbed)
03	Normal Force (in the body and soldered on PCB unless otherwise specified)	Contact Gaps	Normal Force (in the body and soldered on PCB unless otherwise specified)	Contact Gaps
04		Setup Approved		Setup Approved
05		Normal Force (in the body and soldered on PCB unless otherwise specified)		Normal Force (in the body and soldered on PCB unless otherwise specified)

Thermal Aging = EIA-364-17, Test Condition 4 (105°C)

Time Condition 'B' (250 Hours)

Normal Force = EIA-364-04

(Perpendicular) Displacement Force = 12.7 mm/min  $\pm$  6 mm/min

Spec is 50 N @ 1 mm displacement

Contact Gaps / Height - No standard method. Usually measured optically

Gaps to be taken on a minimum of 20% of each part tested

Test all beams from each contact

Signal = 2 beams per x 3 contacts

Power = 3 beams per

**FLOWCHARTS Continued****Thermal Aging**

<b>TEST STEP</b>	<b>GROUP A1 8 Boards Thermal Aging (Mated)</b>
<b>01</b>	Contact Gaps
<b>02</b>	Forces - Mating / Unmating
<b>03</b>	LLCR-1
<b>04</b>	Thermal Aging (Mated and Undisturbed)
<b>05</b>	LLCR-2
<b>06</b>	Forces - Mating / Unmating
<b>07</b>	Contact Gaps

Thermal Aging = EIA-364-17, Test Condition 4 (105°C)

Time Condition 'B' (250 Hours)

Mating / Unmating Forces = EIA-364-13

Contact Gaps / Height - No standard method. Usually measured optically.

Gaps to be taken on a minimum of 20% of each part tested

LLCR = EIA-364-23, LLCR

20 mV Max, 100 mA Max

Use Keithley 580 or 3706 in 4 wire dry circuit mode

**FLOWCHARTS Continued****Durability/Mating/Unmating/Gaps**

<b>TEST STEP</b>	<b>GROUP B1 8 Boards (largest position submitted)</b>
<b>01</b>	Contact Gaps
<b>02</b>	LLCR-1
<b>03</b>	Forces - Mating / Unmating
<b>04</b>	25 Cycles
<b>05</b>	Forces - Mating / Unmating
<b>06</b>	25 Cycles (50 Total)
<b>07</b>	Forces - Mating / Unmating
<b>08</b>	25 Cycles (75 Total)
<b>09</b>	Forces - Mating / Unmating
<b>10</b>	25 Cycles (100 Total)
<b>11</b>	Forces - Mating / Unmating
<b>12</b>	Clean w/Compressed Air
<b>13</b>	Contact Gaps
<b>14</b>	LLCR-2
<b>15</b>	Thermal Shock (Mated and Undisturbed)
<b>16</b>	LLCR-3
<b>17</b>	Cyclic Humidity (Mated and Undisturbed)
<b>18</b>	LLCR-4
<b>19</b>	Forces - Mating / Unmating

Thermal Shock = EIA-364-32, Table II, Test Condition I:

-55°C to +85°C 1/2 hour dwell, 100 cycles

Humidity = EIA-364-31, Test Condition B (240 Hours)

and Method III (+25°C to +65°C @ 90% RH to 98% RH)

ambient pre-condition and delete steps 7a and 7b

Mating / Unmating Forces = EIA-364-13

Contact Gaps / Height - No standard method. Usually measured optically.

Gaps to be taken on a minimum of 20% of each part tested

LLCR = EIA-364-23, LLCR

20 mV Max, 100 mA Max

Use Keithley 580 or 3706 in 4 wire dry circuit mode

**FLOWCHARTS Continued****IR & DWV**

TEST STEP	GROUP A1  2 Mated Sets  Break Down Pin-to-Pin	GROUP A2 2 Unmated of Part # Being Tested Break Down Pin-to-Pin	GROUP A3 2 Unmated of Mating Part # Break Down Pin-to-Pin	GROUP B1  2 Mated Sets  Pin-to-Pin
01	DWV/Break Down Voltage	DWV/Break Down Voltage	DWV/Break Down Voltage	IR & DWV at test voltage (on both mated sets and on each connector unmated)
02				Thermal Shock (Mated and Undisturbed)
03				IR & DWV at test voltage (on both mated sets and on each connector unmated)
04				Cyclic Humidity (Mated and Undisturbed)
05				IR & DWV at test voltage (on both mated sets and on each connector unmated)

DWV on Group B1 to be performed at Test Voltage

DWV test voltage is equal to 75% of the lowest break down voltage from Groups A1, A2 or A3

Thermal Shock = EIA-364-32, Table II, Test Condition I:

-55°C to +85°C 1/2 hour dwell, 100 cycles

Humidity = EIA-364-31, Test Condition B (240 Hours)

and Method III (+25°C to +65°C @ 90% RH to 98% RH)

ambient pre-condition and delete steps 7a and 7b

IR = EIA-364-21

DWV = EIA-364-20, Test Condition 1

**FLOWCHARTS Continued**

<b>TEST STEP</b>	<b>GROUP C1 2 Mated Sets  Break Down Row-to-Row</b>	<b>GROUP C2 2 Unmated of Part # Being Tested  Break Down Row-to-Row</b>	<b>GROUP C3 2 Unmated of Mating Part #  Break Down Row-to-Row</b>	<b>GROUP D1 2 Mated Sets  Row-to-Row</b>
<b>01</b>	DWV/Break Down Voltage	DWV/Break Down Voltage	DWV/Break Down Voltage	IR & DWV at test voltage (on both mated sets and on each connector unmated)
<b>02</b>				Thermal Shock (Mated and Undisturbed)
<b>03</b>				IR & DWV at test voltage (on both mated sets and on each connector unmated)
<b>04</b>				Cyclic Humidity (Mated and Undisturbed)
<b>05</b>				IR & DWV at test voltage (on both mated sets and on each connector unmated)

<b>TEST STEP</b>	<b>GROUP E1 2 Mated Sets  Break Down Pin-to-Power</b>	<b>GROUP E2 2 Unmated of Part # Being Tested  Break Down Pin-to-Power</b>	<b>GROUP E3 2 Unmated of Mating Part #  Break Down Pin-to-Power</b>	<b>GROUP F1 2 Mated Sets  Pin-to-Power</b>
<b>01</b>	DWV/Break Down Voltage	DWV/Break Down Voltage	DWV/Break Down Voltage	IR & DWV at test voltage (on both mated sets and on each connector unmated)
<b>02</b>				Thermal Shock (Mated and Undisturbed)
<b>03</b>				IR & DWV at test voltage (on both mated sets and on each connector unmated)
<b>04</b>				Cyclic Humidity (Mated and Undisturbed)
<b>05</b>				IR & DWV at test voltage (on both mated sets and on each connector unmated)



**FLOWCHARTS Continued**

<b>TEST STEP</b>	<b>GROUP G1 2 Mated Sets  Break Down Power-to-Power</b>	<b>GROUP G2 2 Unmated of Part # Being Tested Break Down Power-to-Power</b>	<b>GROUP G3 2 Unmated of Mating Part #  Break Down Power-to-Power</b>	<b>GROUP H1 2 Mated Sets  Power-to-Power</b>
<b>01</b>	DWV/Break Down Voltage	DWV/Break Down Voltage	DWV/Break Down Voltage	IR & DWV at test voltage (on both mated sets and on each connector unmated)
<b>02</b>				Thermal Shock (Mated and Undisturbed)
<b>03</b>				IR & DWV at test voltage (on both mated sets and on each connector unmated)
<b>04</b>				Cyclic Humidity (Mated and Undisturbed)
<b>05</b>				IR & DWV at test voltage (on both mated sets and on each connector unmated)

**FLOWCHARTS Continued****POWER PINS**Current Carrying Capacity - Power Pins

TEST STEP	GROUP A1 3 Mated Assemblies 1 Contact Powered	GROUP A2 3 Mated Assemblies 2 Contacts Powered	GROUP A3 3 Mated Assemblies 3 Contacts Powered	GROUP A4 3 Mated Assemblies 4 Contacts Powered	GROUP A5 3 Mated Assemblies All Contacts Powered
01	CCC	CCC	CCC	CCC	CCC

**SIGNAL PINS**Current Carrying Capacity - Singal Pins

TEST STEP	GROUP D1 3 Mated Assemblies 1 Vertical Row Powered	GROUP D2 3 Mated Assemblies 2 Adjacent Vertical Rows Powered	GROUP D3 3 Mated Assemblies 3 Adjacent Vertical Rows Powered	GROUP D4 3 Mated Assemblies 4 Adjacent Vertical Rows Powered	GROUP D5 3 Mated Assemblies All Contacts Powered
01	CCC	CCC	CCC	CCC	CCC

**POWER & SIGNAL PINS**Current Carrying Capacity - Power and Signal Pins

TEST STEP	GROUP E1 3 Mated Assemblies Signal Pins @ 1/2 rated current from Group D5 Power Pins - All Contacts Powered
01	CCC

(TIN PLATING) - Tabulate calculated current at RT, 65°C, 75°C and 95°C  
after derating 20% and based on 105°C

(GOLD PLATING) - Tabulate calculated current at RT, 85°C, 95°C and 115°C  
after derating 20% and based on 125°C

CCC, Temp rise = EIA-364-70

**FLOWCHARTS Continued****Mechanical Shock / Vibration / LLCR**

TEST STEP	GROUP A1 192 Points
01	LLCR-1
02	Shock
03	Vibration
04	LLCR-2

Mechanical Shock = EIA 364-27 Half Sine,

100 g's, 6 milliSeconds (Condition "C") each axis

Vibration = EIA 364-28, Random Vibration

7.56 g RMS, Condition VB --- 2 hours/axis

LLCR = EIA-364-23, LLCR

20 mV Max, 100 mA Max

Use Keithley 580 or 3706 in 4 wire dry circuit mode

Max delta allowed is 20 mOhms

**Shock / Vibration / nanoSecond Event Detection**

TEST STEP	GROUP A1 60 Points
01	Event Detection, Shock
02	Event Detection, Vibration

Mechanical Shock = EIA 364-27 Half Sine,

100 g's, 6 milliSeconds (Condition "C") each axis

Vibration = EIA 364-28, Random Vibration

7.56 g RMS, Condition VB --- 2 hours/axis

Event detection requirement during Shock / Vibration is 50 nanoseconds minimum

## ATTRIBUTE DEFINITIONS

The following is a brief, simplified description of attributes.

### THERMAL SHOCK:

- 1) EIA-364-32, *Thermal Shock (Temperature Cycling) Test Procedure for Electrical Connectors*.
- 2) Test Condition 1: -55°C to +85°C
- 3) Test Time: ½ hour dwell at each temperature extreme
- 4) Number of Cycles: 100
- 5) All test samples are pre-conditioned at ambient.
- 6) All test samples are exposed to environmental stressing in the mated condition.

### THERMAL:

- 1) EIA-364-17, *Temperature Life with or without Electrical Load Test Procedure for Electrical Connectors*.
- 2) Test Condition 4 at 105° C.
- 3) Test Time Condition B for 250 hours.
- 4) All test samples are pre-conditioned at ambient.
- 5) All test samples are exposed to environmental stressing in the mated condition.

### HUMIDITY:

- 1) Reference document: EIA-364-31, *Humidity Test Procedure for Electrical Connectors*.
- 2) Test Condition B, 240 Hours.
- 3) Method III, +25° C to + 65° C, 90% to 98% Relative Humidity excluding sub-cycles 7a and 7b.
- 4) All samples are pre-conditioned at ambient.
- 5) All test samples are exposed to environmental stressing in the mated condition.

### MECHANICAL SHOCK (Specified Pulse):

- 1) Reference document: EIA-364-27, *Mechanical Shock Test Procedure for Electrical Connectors*
- 2) Test Condition C
- 3) Peak Value: 100 G
- 4) Duration: 6 Milliseconds
- 5) Wave Form: Half Sine
- 6) Velocity: 12.3 ft/s
- 7) Number of Shocks: 3 Shocks / Direction, 3 Axis (18 Total)

### VIBRATION:

- 1) Reference document: EIA-364-28, *Vibration Test Procedure for Electrical Connectors*
- 2) Test Condition V, Letter B
- 3) Power Spectral Density: 0.04 G<sup>2</sup> / Hz
- 4) G 'RMS': 7.56
- 5) Frequency: 50 to 2000 Hz
- 6) Duration: 2.0 Hours per axis (3 axis total)

### NANOSECOND-EVENT DETECTION:

- 1) Reference document: EIA-364-87, *Nanosecond-Event Detection for Electrical Connectors*
- 2) Prior to test, the samples were characterized to assure the low nanosecond event being monitored will trigger the detector.
- 3) After characterization it was determined the test samples could be monitored for 50 nanosecond events

### MATING/UNMATING:

- 1) Reference document: EIA-364-13, *Mating and Unmating Forces Test Procedure for Electrical Connectors*.
- 2) The full insertion position was to within 0.003" to 0.004" of the plug bottoming out in the receptacle to prevent damage to the system under test.
- 3) One of the mating parts is secured to a floating X-Y table to prevent damage during cycling.

**ATTRIBUTE DEFINITIONS Continued**

The following is a brief, simplified description of attributes

**NORMAL FORCE (FOR CONTACTS TESTED IN THE HOUSING):**

- 1) Reference document: EIA-364-04, *Normal Force Test Procedure for Electrical Connectors*.
- 2) The contacts shall be tested in the connector housing.
- 3) If necessary, a "window" shall be made in the connector body to allow a probe to engage and deflect the contact at the same attitude and distance (plus 0.05 mm [0.002"]) as would occur in actual use.
- 4) The connector housing shall be placed in a holding fixture that does not interfere with or otherwise influence the contact force or deflection.
- 5) Said holding fixture shall be mounted on a floating, adjustable, X-Y table on the base of the Dillon TC<sup>2</sup>, computer controlled test stand with a deflection measurement system accuracy of 5.0  $\mu$ m (0.0002").
- 6) The nominal deflection rate shall be 5 mm (0.2")/minute.
- 7) Unless otherwise noted a minimum of five contacts shall be tested.
- 8) The force/deflection characteristic to load and unload each contact shall be repeated five times.
- 9) The system shall utilize the TC<sup>2</sup> software in order to acquire and record the test data.
- 10) The permanent set of each contact shall be measured within the TC<sup>2</sup> software.
- 11) The acquired data shall be graphed with the deflection data on the X-axis and the force data on the Y-axis and a print out will be stored with the Tracking Code paperwork.

**NORMAL FORCE (FOR CONTACTS TESTED OUTSIDE THE HOUSING):**

- 1) Reference document: EIA-364-04, *Normal Force Test Procedure for Electrical Connectors*.
- 2) The contacts shall be tested in the loose state, *not* inserted in connector housing.
- 3) The contacts shall be prepared to allow access to the spring member at the same attitude and deflection level as would occur in actual use.
- 4) In the event that portions of the contact prevent insertion of the test probe and/or deflection of the spring member under evaluation, said material shall be removed leaving the appropriate contact surfaces exposed.
- 5) In the case of multi-tine contacts, each tine shall be tested independently on separate samples as required.
- 6) The connector housing shall be simulated, if required, in order to provide an accurate representation of the actual contact system performance.
- 7) A holding fixture shall be fashioned to allow the contact to be properly deflected.
- 8) Said holding fixture shall be mounted on a floating, adjustable, X-Y table on the base of the Dillon TC<sup>2</sup>, computer controlled test stand with a deflection measurement system accuracy of 5  $\mu$ m (0.0002").
- 9) The probe shall be attached to a Dillon P/N 49761-0105, 5 N (1.1 Lb) load cell providing an accuracy of  $\pm$  0.2%.
- 10) The nominal deflection rate shall be 5 mm (0.2")/minute.
- 11) Unless otherwise noted a minimum of five contacts shall be tested.
- 12) The force/deflection characteristic to load and unload each contact shall be repeated five times.
- 13) The system shall utilize the TC<sup>2</sup> software in order to acquire and record the test data.
- 14) The permanent set of each contact shall be measured within the TC<sup>2</sup> software.
- 15) The acquired data shall be graphed with the deflection data on the X-axis and the force data on the Y-axis and a print out will be stored with the Tracking Code paperwork.

**ATTRIBUTE DEFINITIONS Continued**

The following is a brief, simplified description of attributes

**TEMPERATURE RISE (Current Carrying Capacity, CCC):**

- 1) EIA-364-70, *Temperature Rise versus Current Test Procedure for Electrical Connectors and Sockets*.
- 2) When current passes through a contact, the temperature of the contact increases as a result of  $I^2R$  (resistive) heating.
- 3) The number of contacts being investigated plays a significant part in power dissipation and therefore temperature rise.
- 4) The size of the temperature probe can affect the measured temperature.
- 5) Copper traces on PC boards will contribute to temperature rise:
  - a. Self heating (resistive)
  - b. Reduction in heat sink capacity affecting the heated contacts
- 6) A de-rating curve, usually 20%, is calculated.
- 7) Calculated de-rated currents at three temperature points are reported:
  - a. Ambient
  - b. 80° C
  - c. 95° C
  - d. 115° C
- 8) Typically, neighboring contacts (in close proximity to maximize heat build up) are energized.
- 9) The thermocouple (or temperature measuring probe) will be positioned at a location to sense the maximum temperature in the vicinity of the heat generation area.
- 10) A computer program, *TR 803.exe*, ensures accurate stability for data acquisition.
- 11) Hook-up wire cross section is larger than the cross section of any connector leads/PC board traces, jumpers, etc.
- 12) Hook-up wire length is longer than the minimum specified in the referencing standard.

**ATTRIBUTE DEFINITIONS Continued**

The following is a brief, simplified description of attributes

**LLCR:**

- 1) EIA-364-23, *Low Level Contact Resistance Test Procedure for Electrical Connectors and Sockets*.
- 2) A computer program, *LLCR 221.exe*, ensures repeatability for data acquisition.
- 3) The following guidelines are used to categorize the changes in LLCR as a result from stressing
  - a.  $\leq +5.0$  mOhms: -----Stable
  - b.  $+5.1$  to  $+10.0$  mOhms: -----Minor
  - c.  $+10.1$  to  $+15.0$  mOhms: -----Acceptable
  - d.  $+15.1$  to  $+50.0$  mOhms: -----Marginal
  - e.  $+50.1$  to  $+2000$  mOhms: -----Unstable
  - f.  $>+2000$  mOhms: -----Open Failure

**GAS TIGHT:**

To provide method for evaluating the ability of the contacting surfaces in preventing penetration of harsh vapors which might lead to oxide formation that may degrade the electrical performance of the contact system.

- 1) EIA-364-23, *Low Level Contact Resistance Test Procedure for Electrical Connectors and Sockets*.
- 2) A computer program, *LLCR 221.exe*, ensures repeatability for data acquisition.
- 3) The following guidelines are used to categorize the changes in LLCR as a result from stressing
  - a.  $\leq +5.0$  mOhms: -----Stable
  - b.  $+5.1$  to  $+10.0$  mOhms: -----Minor
  - c.  $+10.1$  to  $+15.0$  mOhms: -----Acceptable
  - d.  $+15.1$  to  $+50.0$  mOhms: -----Marginal
  - e.  $+50.1$  to  $+2000$  mOhms: -----Unstable
  - f.  $>+2000$  mOhms: -----Open Failure
- 4) Procedure:
  - a. Reference document: EIA-364-36, *Test Procedure for Determination of Gas-Tight Characteristics for Electrical Connectors, Sockets and/or Contact Systems*.
  - b. Test Conditions:
    - i. Class II--- Mated pairs of contacts assembled to their plastic housings.
    - ii. Reagent grade Nitric Acid shall be used of sufficient volume to saturate the test chamber
    - iii. The ratio of the volume of the test chamber to the surface area of the acid shall be 10:1.
    - iv. The chamber shall be saturated with the vapor for at least 15 minutes before samples are added.
    - v. Exposure time, 55 to 65 minutes.
    - vi. The samples shall be no closer to the chamber walls than 1 inches and no closer to the surface of the acid than 3 inches.
    - vii. The samples shall be dried after exposure for a minimum of 1 hour.
    - viii. Drying temperature  $50^{\circ}\text{C}$
    - ix. The final LLCR shall be conducted within 1 hour after drying.

**ATTRIBUTE DEFINITIONS Continued**

The following is a brief, simplified description of attributes

**INSULATION RESISTANCE (IR):**

To determine the resistance of insulation materials to leakage of current through or on the surface of these materials when a DC potential is applied.

**1) PROCEDURE:**

- a. Reference document: EIA-364-21, *Insulation Resistance Test Procedure for Electrical Connectors*.
- b. Test Conditions:
  - i. Between Adjacent Contacts or Signal-to-Ground
  - ii. Electrification Time 2.0 minutes
  - iii. Test Voltage (500 VDC) corresponds to calibration settings for measuring resistances.

**2) MEASUREMENTS:**

- 3) When the specified test voltage is applied (VDC), the insulation resistance shall not be less than 5000 megohms.

**DIELECTRIC WITHSTANDING VOLTAGE (DWV):**

To determine if the sockets can operate at its rated voltage and withstand momentary over potentials due to switching, surges, and other similar phenomenon. Separate samples are used to evaluate the effect of environmental stresses so not to influence the readings from arcing that occurs during the measurement process.

**1) PROCEDURE:**

- a. Reference document: EIA-364-20, *Withstanding Voltage Test Procedure for Electrical Connectors*.
- b. Test Conditions:
  - i. Between Adjacent Contacts or Signal-to-Ground
  - ii. Barometric Test Condition 1
  - iii. Rate of Application 500 V/Sec
  - iv. Test Voltage (VAC) until breakdown occurs

**2) MEASUREMENTS/CALCULATIONS**

- a. The breakdown voltage shall be measured and recorded.
- b. The dielectric withstanding voltage shall be recorded as 75% of the minimum breakdown voltage.
- c. The working voltage shall be recorded as one-third (1/3) of the dielectric withstanding voltage (one-fourth of the breakdown voltage).



## RESULTS

### Temperature Rise, CCC at a 20% de-rating

#### Power pin

- CCC for a 30°C Temperature Rise-----70.0A per contact with 1 adjacent power contacts powered
- CCC for a 30°C Temperature Rise-----59.5A per contact with 2 adjacent power contacts powered
- CCC for a 30°C Temperature Rise-----52.8A per contact with 3 adjacent power contacts powered
- CCC for a 30°C Temperature Rise-----48.2A per contact with 4 adjacent power contacts powered
- CCC for a 30°C Temperature Rise-----45.0A per contact with all adjacent power contacts powered

#### Signal pin

- CCC for a 30°C Temperature Rise-----3.3A per contact with 3 adjacent signal contacts powered
- CCC for a 30°C Temperature Rise-----2.5A per contact with 6 adjacent signal contacts powered
- CCC for a 30°C Temperature Rise-----2.2A per contact with 9 adjacent signal contacts powered
- CCC for a 30°C Temperature Rise-----2.0A per contact with 12 adjacent signal contacts powered
- CCC for a 30°C Temperature Rise-----1.6A per contact with all adjacent signal contacts powered

#### Power pin and Signal pin

- CCC for a 30°C Temperature Rise-----43.1A per contact with all adjacent power contacts powered and signal contacts powered @ 1/2 rated current @ .95 AMPS.

### Mating/Unmating Forces: Thermal Aging Group

- Initial
  - Mating
    - Min ----- 6.52 Lbs
    - Max-----10.98 Lbs
  - Unmating
    - Min ----- 5.33 Lbs
    - Max----- 6.10 Lbs
- After Thermal
  - Mating
    - Min ----- 4.63 Lbs
    - Max----- 5.08 Lbs
  - Unmating
    - Min ----- 3.31 Lbs
    - Max----- 4.06 Lbs

**RESULTS Continued****Mating/Unmating Forces: Mating/Unmating Durability Group**

- **Initial**
  - **Mating**
    - **Min** ----- 5.93 Lbs
    - **Max** ----- 7.70 Lbs
  - **Unmating**
    - **Min** ----- 4.98 Lbs
    - **Max** ----- 6.05 Lbs
- **After 25 Cycles**
  - **Mating**
    - **Min** ----- 7.25 Lbs
    - **Max** ----- 8.71 Lbs
  - **Unmating**
    - **Min** ----- 5.78 Lbs
    - **Max** ----- 7.17 Lbs
- **After 50 Cycles**
  - **Mating**
    - **Min** ----- 8.31 Lbs
    - **Max** ----- 9.58 Lbs
  - **Unmating**
    - **Min** ----- 6.29 Lbs
    - **Max** ----- 7.97 Lbs
- **After 75 Cycles**
  - **Mating**
    - **Min** ----- 8.98 Lbs
    - **Max** ----- 10.94 Lbs
  - **Unmating**
    - **Min** ----- 7.15 Lbs
    - **Max** ----- 8.93 Lbs
- **After 100 Cycles**
  - **Mating**
    - **Min** ----- 9.93 Lbs
    - **Max** ----- 12.31 Lbs
  - **Unmating**
    - **Min** ----- 8.35 Lbs
    - **Max** ----- 9.96 Lbs
- **After Humidity**
  - **Mating**
    - **Min** ----- 4.83 Lbs
    - **Max** ----- 6.25 Lbs
  - **Unmating**
    - **Min** ----- 3.66 Lbs
    - **Max** ----- 5.02 Lbs

**RESULTS Continued****Normal Force at 0.0132 inches deflection power pin****Left**

- **Initial**
  - Min ----- 442.10 gf      Set ---- 0.0005 in
  - Max ----- 503.90 gf      Set ---- 0.0016 in
- **Thermal**
  - Min ----- 264.60 gf      Set----- 0.0043 in
  - Max ----- 334.20 gf      Set----- 0.0053 in

**Middle**

- **Initial**
  - Min ----- 420.80 gf      Set ---- 0.0001 in
  - Max ----- 498.90 gf      Set ---- 0.0005 in
- **Thermal**
  - Min ----- 252.70 gf      Set----- 0.0045 in
  - Max ----- 297.60 gf      Set----- 0.0055 in

**Right**

- **Initial**
  - Min ----- 401.00 gf      Set ---- 0.0000 in
  - Max ----- 472.50 gf      Set ---- 0.0004 in
- **Thermal**
  - Min ----- 252.20 gf      Set----- 0.0041 in
  - Max ----- 295.10 gf      Set----- 0.0051 in

**Normal Force at 0.009 inches deflection signal pin****Row1 Left**

- **Initial**
  - Min ----- 110.20 gf      Set ---- 0.0000 in
  - Max ----- 133.60 gf      Set ---- 0.0005 in
- **Thermal**
  - Min ----- 109.40 gf      Set----- 0.0005 in
  - Max ----- 129.00 gf      Set----- 0.0016 in

**Row1 right**

- **Initial**
  - Min ----- 110.40 gf      Set ---- 0.0001 in
  - Max ----- 134.40 gf      Set ---- 0.0004 in
- **Thermal**
  - Min ----- 104.00 gf      Set----- 0.0008 in
  - Max ----- 131.90 gf      Set----- 0.0020 in

**Row2 Left**

- **Initial**
  - Min ----- 115.50 gf      Set ---- 0.0001 in
  - Max ----- 131.90 gf      Set ---- 0.0003 in
- **Thermal**
  - Min ----- 103.90 gf      Set----- 0.0006 in
  - Max ----- 130.50 gf      Set----- 0.0012 in

**Row2 right**

- **Initial**
  - Min ----- 111.70 gf      Set ---- 0.0001 in
  - Max ----- 127.80 gf      Set ---- 0.0004 in
- **Thermal**
  - Min ----- 100.00 gf      Set----- 0.0007 in
  - Max ----- 118.80 gf      Set----- 0.0018 in

**RESULTS Continued****Normal Force at 0.009 inches deflection signal pin****Row3 Left**

- **Initial**
  - Min ----- 111.20 gf      Set ---- 0.0000 in
  - Max ----- 134.40 gf      Set ---- 0.0003 in
- **Thermal**
  - Min ----- 109.40 gf      Set ---- 0.0007 in
  - Max ----- 124.90 gf      Set ---- 0.0012 in

**Row3 right**

- **Initial**
  - Min ----- 110.00 gf      Set ---- 0.0002 in
  - Max ----- 122.70 gf      Set ---- 0.0007 in
- **Thermal**
  - Min ----- 102.00 gf      Set ---- 0.0007 in
  - Max ----- 128.00 gf      Set ---- 0.0015 in

**Insulation Resistance minimums, IR****Pin to Pin**

- **Initial**
  - Mated ----- 10000Meg  $\Omega$  ----- Passed
  - Unmated ----- 10000Meg  $\Omega$  ----- Passed
- **Thermal**
  - Mated ----- 10000Meg  $\Omega$  ----- Passed
  - Unmated ----- 10000Meg  $\Omega$  ----- Passed
- **Humidity**
  - Mated ----- 5687Meg  $\Omega$  ----- Passed
  - Unmated ----- 6423Meg  $\Omega$  ----- Passed

**Pin to Power**

- **Initial**
  - Mated ----- 10000Meg  $\Omega$  ----- Passed
  - Unmated ----- 10000Meg  $\Omega$  ----- Passed
- **Thermal**
  - Mated ----- 10000Meg  $\Omega$  ----- Passed
  - Unmated ----- 10000Meg  $\Omega$  ----- Passed
- **Humidity**
  - Mated ----- 10000Meg  $\Omega$  ----- Passed
  - Unmated ----- 10000Meg  $\Omega$  ----- Passed

**Power to Power**

- **Initial**
  - Mated ----- 10000Meg  $\Omega$  ----- Passed
  - Unmated ----- 10000Meg  $\Omega$  ----- Passed
- **Thermal**
  - Mated ----- 10000Meg  $\Omega$  ----- Passed
  - Unmated ----- 10000Meg  $\Omega$  ----- Passed
- **Humidity**
  - Mated ----- 5943Meg  $\Omega$  ----- Passed
  - Unmated ----- 6853Meg  $\Omega$  ----- Passed

**RESULTS Continued****Row1 to Row1**

- **Initial**
  - Mated -----10000Meg  $\Omega$  ----- Passed
  - Unmated -----10000Meg  $\Omega$  ----- Passed
- **Thermal**
  - Mated -----10000Meg  $\Omega$  ----- Passed
  - Unmated -----10000Meg  $\Omega$  ----- Passed
- **Humidity**
  - Mated ----- 5391Meg  $\Omega$  ----- Passed
  - Unmated ----- 6259Meg  $\Omega$  ----- Passed

**Row2 to Row2**

- **Initial**
  - Mated -----10000Meg  $\Omega$  ----- Passed
  - Unmated -----10000Meg  $\Omega$  ----- Passed
- **Thermal**
  - Mated -----10000Meg  $\Omega$  ----- Passed
  - Unmated -----10000Meg  $\Omega$  ----- Passed
- **Humidity**
  - Mated ----- 5981Meg  $\Omega$  ----- Passed
  - Unmated ----- 6397Meg  $\Omega$  ----- Passed

**Dielectric Withstanding Voltage minimums, DWV**

- **Minimums**
  - Breakdown Voltage ----- 1125 VAC
  - Test Voltage -----844 VAC
  - Working Voltage -----281 VAC

**Pin to Pin**

- Initial DWV -----Passed
- Thermal DWV -----Passed
- Humidity DWV -----Passed

**Pin to Power**

- Initial DWV -----Passed
- Thermal DWV -----Passed
- Humidity DWV -----Passed

**Power to Power**

- Initial DWV -----Passed
- Thermal DWV -----Passed
- Humidity DWV -----Passed

**Row1 to Row1**

- Initial DWV -----Passed
- Thermal DWV -----Passed
- Humidity DWV -----Passed

**Row2 to Row2**

- Initial DWV -----Passed
- Thermal DWV -----Passed
- Humidity DWV -----Passed

**RESULTS Continued****LLCR Gas Tight (144 signal and 48 power LLCR test points)****Signal pin**

- **Initial** ----- 16.83mOhms Max
- **Gas-Tight**
  - <= +5.0 mOhms----- 144 Points ----- Stable
  - +5.1 to +10.0 mOhms ----- 0 Points ----- Minor
  - +10.1 to +15.0 mOhms ----- 0 Points ----- Acceptable
  - +15.1 to +50.0 mOhms ----- 0 Points ----- Marginal
  - +50.1 to +2000 mOhms ----- 0 Points ----- Unstable
  - >+2000 mOhms ----- 0 Points ----- Open Failure

**Power pin**

- **Initial** ----- 0.26mOhms Max
- **Gas-Tight**
  - <= +5.0 mOhms----- 48 Points ----- Stable
  - +5.1 to +10.0 mOhms ----- 0 Points ----- Minor
  - +10.1 to +15.0 mOhms ----- 0 Points ----- Acceptable
  - +15.1 to +50.0 mOhms ----- 0 Points ----- Marginal
  - +50.1 to +2000 mOhms ----- 0 Points ----- Unstable
  - >+2000 mOhms ----- 0 Points ----- Open Failure

**LLCR Thermal Aging (144 signal and 48 power LLCR test points)****Signal pin**

- **Initial** ----- 16.74mOhms Max
- **Thermal Aging**
  - <= +5.0 mOhms----- 144 Points ----- Stable
  - +5.1 to +10.0 mOhms ----- 0 Points ----- Minor
  - +10.1 to +15.0 mOhms ----- 0 Points ----- Acceptable
  - +15.1 to +50.0 mOhms ----- 0 Points ----- Marginal
  - +50.1 to +2000 mOhms ----- 0 Points ----- Unstable
  - >+2000 mOhms ----- 0 Points ----- Open Failure

**Power pin**

- **Initial** ----- 0.23mOhms Max
- **Thermal Aging**
  - <= +5.0 mOhms----- 48 Points ----- Stable
  - +5.1 to +10.0 mOhms ----- 0 Points ----- Minor
  - +10.1 to +15.0 mOhms ----- 0 Points ----- Acceptable
  - +15.1 to +50.0 mOhms ----- 0 Points ----- Marginal
  - +50.1 to +2000 mOhms ----- 0 Points ----- Unstable
  - >+2000 mOhms ----- 0 Points ----- Open Failure

**RESULTS Continued****LLCR Durability (144 signal and 48 power LLCR test points)****Signal pin**

- **Initial** ----- 16.86mOhms Max
- **Durability, 100 Cycles**
  - <= +5.0 mOhms----- 144 Points ----- Stable
  - +5.1 to +10.0 mOhms ----- 0 Points ----- Minor
  - +10.1 to +15.0 mOhms ----- 0 Points ----- Acceptable
  - +15.1 to +50.0 mOhms ----- 0 Points ----- Marginal
  - +50.1 to +2000 mOhms----- 0 Points ----- Unstable
  - >+2000 mOhms----- 0 Points ----- Open Failure
- **Thermal**
  - <= +5.0 mOhms----- 144 Points ----- Stable
  - +5.1 to +10.0 mOhms ----- 0 Points ----- Minor
  - +10.1 to +15.0 mOhms ----- 0 Points ----- Acceptable
  - +15.1 to +50.0 mOhms ----- 0 Points ----- Marginal
  - +50.1 to +2000 mOhms----- 0 Points ----- Unstable
  - >+2000 mOhms----- 0 Points ----- Open Failure
- **Humidity**
  - <= +5.0 mOhms----- 144 Points ----- Stable
  - +5.1 to +10.0 mOhms ----- 0 Points ----- Minor
  - +10.1 to +15.0 mOhms ----- 0 Points ----- Acceptable
  - +15.1 to +50.0 mOhms ----- 0 Points ----- Marginal
  - +50.1 to +2000 mOhms----- 0 Points ----- Unstable
  - >+2000 mOhms----- 0 Points ----- Open Failure

**Power pin**

- **Initial** ----- 0.26mOhms Max
- **Durability, 100 Cycles**
  - <= +5.0 mOhms----- 48 Points ----- Stable
  - +5.1 to +10.0 mOhms ----- 0 Points ----- Minor
  - +10.1 to +15.0 mOhms ----- 0 Points ----- Acceptable
  - +15.1 to +50.0 mOhms ----- 0 Points ----- Marginal
  - +50.1 to +2000 mOhms----- 0 Points ----- Unstable
  - >+2000 mOhms----- 0 Points ----- Open Failure
- **Thermal**
  - <= +5.0 mOhms----- 48 Points ----- Stable
  - +5.1 to +10.0 mOhms ----- 0 Points ----- Minor
  - +10.1 to +15.0 mOhms ----- 0 Points ----- Acceptable
  - +15.1 to +50.0 mOhms ----- 0 Points ----- Marginal
  - +50.1 to +2000 mOhms----- 0 Points ----- Unstable
  - >+2000 mOhms----- 0 Points ----- Open Failure
- **Humidity**
  - <= +5.0 mOhms----- 48 Points ----- Stable
  - +5.1 to +10.0 mOhms ----- 0 Points ----- Minor
  - +10.1 to +15.0 mOhms ----- 0 Points ----- Acceptable
  - +15.1 to +50.0 mOhms ----- 0 Points ----- Marginal
  - +50.1 to +2000 mOhms----- 0 Points ----- Unstable
  - >+2000 mOhms----- 0 Points ----- Open Failure

**RESULTS Continued****LLCR Shock & Vibration (144 signal and 48 power LLCR test points)****Signal pin**

- **Initial** ----- 18.62mOhms Max
- **Shock &Vibration**
  - <= +5.0 mOhms----- 144 Points ----- Stable
  - +5.1 to +10.0 mOhms -----0 Points ----- Minor
  - +10.1 to +15.0 mOhms -----0 Points ----- Acceptable
  - +15.1 to +50.0 mOhms -----0 Points ----- Marginal
  - +50.1 to +2000 mOhms-----0 Points ----- Unstable
  - >+2000 mOhms-----0 Points ----- Open Failure

**Power pin**

- **Initial** -----0.29mOhms Max
- **Shock &Vibration**
  - <= +5.0 mOhms----- 48 Points ----- Stable
  - +5.1 to +10.0 mOhms -----0 Points ----- Minor
  - +10.1 to +15.0 mOhms -----0 Points ----- Acceptable
  - +15.1 to +50.0 mOhms -----0 Points ----- Marginal
  - +50.1 to +2000 mOhms-----0 Points ----- Unstable
  - >+2000 mOhms-----0 Points ----- Open Failure

**Mechanical Shock & Random Vibration:**

- **Shock**
  - No Damage----- Pass
  - 50 Nanoseconds ----- Pass
- **Vibration**
  - No Damage----- Pass
  - 50 Nanoseconds ----- Pass



**DATA SUMMARIES****TEMPERATURE RISE (Current Carrying Capacity, CCC):**


- 1) High quality thermocouples whose temperature slopes track one another were used for temperature monitoring.
- 2) The thermocouples were placed at a location to sense the maximum temperature generated during testing.
- 3) Temperature readings recorded are those for which three successive readings, 15 minutes apart, differ less than 1° C (computer-controlled data acquisition).
- 4) Adjacent contacts were powered:

**DATA SUMMARIES CONTINUED****Power Pins****a. Linear configuration with 1 adjacent power conductors/contacts powered**


227578 (Samtec)

1 (1x1-Power Pins) Contacts in Series

Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP




227578 (Samtec)  
1 (1x1-Power Pins) Contacts in Series  
Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP




**DATA SUMMARIES Continued****b. Linear configuration with 2 adjacent power conductors/contacts powered**

227578 (Samtec)  
2 (1x2-Power Pins) Contacts in Series  
Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP




227578 (Samtec)  
2 (1x2-Power Pins) Contacts in Series  
Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP




**DATA SUMMARIES Continued****c. Linear configuration with 3 adjacent power conductors/contacts powered**

227578 (Samtec)  
3 (1x3-Power Pins) Contacts in Series  
Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP



227578 (Samtec)  
3 (1x3-Power Pins) Contacts in Series  
Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP




**DATA SUMMARIES Continued**

d. Linear configuration with 4 adjacent power conductors/contacts powered

227578 (Samtec)

4 (1x4-Power Pins) Contacts in Series


Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP

*Current Rating per Contact (30 Deg. Rise, 20% Derated) = 48.2 Amps*

227578 (Samtec)

4 (1x4-Power Pins) Contacts in Series

Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP




**DATA SUMMARIES Continued**

e. Linear configuration with all adjacent power conductors/contacts powered

227578 (Samtec)

6 (All Power-Power Pins) Contacts in Series


Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP

*Current Rating per Contact (30 Deg. Rise, 20% Derated) = 45.0 Amps*

227578 (Samtec)

6 (All Power-Power Pins) Contacts in Series


Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP




**DATA SUMMARIES Continued****Signal Pins**

f. Linear configuration with 3 adjacent signal conductors/contacts powered

227578 (Samtec)  
 3 (3x1-Signal Pins) Contacts in Series  
 Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP





227578 (Samtec)  
 3 (3x1-Signal Pins) Contacts in Series  
 Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP



**DATA SUMMARIES Continued**

g. Linear configuration with 6 adjacent signal conductors/contacts powered


227578 (Samtec)  
6 (3x2-Signal Pins) Contacts in Series  
Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP






**DATA SUMMARIES Continued****h. Linear configuration with 9 adjacent signal conductors/contacts powered**

227578 (Samtec)  
9 (3x3-Signal Pins) Contacts in Series  
Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP




227578 (Samtec)  
9 (3x3-Signal Pins) Contacts in Series  
Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP




**DATA SUMMARIES Continued****i. Linear configuration with 12 adjacent signal conductors/contacts powered**

227578 (Samtec)  
12 (3x4-Signal Pins) Contacts in Series  
Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP





227578 (Samtec)  
12 (3x4-Signal Pins) Contacts in Series  
Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP




**DATA SUMMARIES Continued****j. Linear configuration with all adjacent signal conductors/contacts powered**

227578 (Samtec)  
24 (All Power-Signal Pins) Contacts in Series  
Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP




**DATA SUMMARIES Continued****k. Linear configuration with all adjacent signal conductors and power conductors/contacts powered**

227578 (Samtec)(Signal Pins Powered @ 1/2 rated current @ .95 AMPS)  
6 (All Power-Power Pins) Contacts in Series



227578 (Samtec)(Signal Pins Powered @ 1/2 rated current .0.95 Amps)  
6 (All Power-Power Pins) Contacts in Series  
Part Numbers: ET60T-00-24-06-L-RT1-GP / ET60S-00-24-06-L-RT1-GP



**DATA SUMMARIES Continued****Mating\Unmating Force: Mating\Unmating Durability Group**

	Initial				After 25 Cycles			
	Mating		Unmating		Mating		Unmating	
	Newton	Force (Lbs)	Newton	Force (Lbs)	Newton	Force (Lbs)	Newton	Force (Lbs)
Minimum	26.38	5.93	22.15	4.98	32.25	7.25	25.71	5.78
Maximum	34.25	7.70	26.91	6.05	38.74	8.71	31.89	7.17
<b>Average</b>	29.15	<b>6.55</b>	24.34	<b>5.47</b>	35.39	<b>7.96</b>	28.38	<b>6.38</b>
St Dev	2.70	0.61	1.58	0.36	1.90	0.43	1.98	0.45
Count	8	8	8	8	8	8	8	8
	After 50 Cycles				After 75 Cycles			
	Mating		Unmating		Mating		Unmating	
	Newton	Force (Lbs)	Newton	Force (Lbs)	Newton	Force (Lbs)	Newton	Force (Lbs)
Minimum	36.96	8.31	27.98	6.29	39.94	8.98	31.80	7.15
Maximum	42.61	9.58	35.45	7.97	48.66	10.94	39.72	8.93
<b>Average</b>	39.53	<b>8.89</b>	31.67	<b>7.12</b>	44.39	<b>9.98</b>	36.01	<b>8.10</b>
St Dev	1.99	0.45	2.53	0.57	3.88	0.87	2.81	0.63
Count	8	8	8	8	8	8	8	8
	After 100 Cycles				After Humidity			
	Mating		Unmating		Mating		Unmating	
	Newton	Force (Lbs)	Newton	Force (Lbs)	Newton	Force (Lbs)	Newton	Force (Lbs)
Minimum	44.17	9.93	37.14	8.35	21.48	4.83	16.28	3.66
Maximum	54.75	12.31	44.30	9.96	27.80	6.25	22.33	5.02
<b>Average</b>	50.07	<b>11.26</b>	40.58	<b>9.12</b>	24.44	<b>5.50</b>	18.92	<b>4.25</b>
St Dev	4.27	0.96	2.20	0.49	2.25	0.51	1.77	0.40
Count	8	8	8	8	8	8	8	8

**Mating\Unmating Force: Thermal Aging Group**

	Initial				After Thermals			
	Mating		Unmating		Mating		Unmating	
	Newton	Force (Lbs)	Newton	Force (Lbs)	Newton	Force (Lbs)	Newton	Force (Lbs)
Minimum	29.00	6.52	23.71	5.33	20.59	4.63	14.72	3.31
Maximum	48.84	10.98	27.13	6.10	22.60	5.08	18.06	4.06
<b>Average</b>	37.46	<b>8.42</b>	25.45	<b>5.72</b>	21.30	<b>4.79</b>	16.21	<b>3.65</b>
St Dev	7.53	1.69	1.21	0.27	0.67	0.15	1.12	0.25
Count	8	8	8	8	8	8	8	8

**DATA SUMMARIES Continued****NORMAL FORCE (FOR CONTACTS TESTED IN THE HOUSING):**

- 1) Calibrated force gauges are used along with computer controlled positioning equipment.
- 2) For Normal force 8-10 measurements are taken and the averages reported.

**Power pin left**

Initial	Deflections in inches Forces in Grams										
	<u>0.0013</u>	<u>0.0026</u>	<u>0.0040</u>	<u>0.0053</u>	<u>0.0066</u>	<u>0.0079</u>	<u>0.0091</u>	<u>0.0106</u>	<u>0.0119</u>	<u>0.0132</u>	<i>SET</i>
<b>Averages</b>	41.67	88.11	134.88	181.88	232.18	280.66	324.73	374.66	422.39	470.93	0.0008
<b>Min</b>	28.20	65.20	108.40	156.70	204.20	248.60	289.50	343.20	394.10	442.10	0.0005
<b>Max</b>	55.20	107.00	153.80	205.30	257.60	310.10	358.20	407.00	456.50	503.90	0.0016
<b>St. Dev</b>	10.198	13.010	14.602	16.354	16.996	18.865	20.032	19.727	19.468	19.387	0.0003
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

After Thermals	Deflections in inches Forces in Grams										
	<u>0.0013</u>	<u>0.0026</u>	<u>0.0040</u>	<u>0.0053</u>	<u>0.0066</u>	<u>0.0079</u>	<u>0.0091</u>	<u>0.0106</u>	<u>0.0119</u>	<u>0.0132</u>	<i>SET</i>
<b>Averages</b>	-0.08	-0.08	-0.08	16.05	56.91	103.25	141.74	194.86	242.13	289.43	0.0048
<b>Min</b>	-0.40	-0.40	-0.40	0.10	34.00	81.50	124.20	173.80	218.20	264.60	0.0043
<b>Max</b>	0.10	0.10	0.10	28.30	76.20	119.30	169.40	229.70	281.40	334.20	0.0053
<b>St. Dev</b>	0.148	0.171	0.176	10.382	13.413	13.648	13.995	16.972	18.018	19.659	0.0003
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

**Power pin middle**

Initial	Deflections in inches Forces in Grams										
	<u>0.0013</u>	<u>0.0026</u>	<u>0.0040</u>	<u>0.0053</u>	<u>0.0066</u>	<u>0.0079</u>	<u>0.0091</u>	<u>0.0106</u>	<u>0.0119</u>	<u>0.0132</u>	<i>SET</i>
<b>Averages</b>	40.68	80.85	124.38	171.04	222.00	269.61	313.03	363.58	408.03	457.68	0.0003
<b>Min</b>	24.10	56.50	98.90	134.20	183.60	227.30	273.70	323.60	371.20	420.80	0.0001
<b>Max</b>	54.20	102.20	151.60	202.90	254.10	303.20	347.20	402.60	448.10	498.90	0.0005
<b>St. Dev</b>	9.804	15.789	16.277	18.908	18.432	19.529	18.984	20.245	20.462	20.363	0.0001
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

After Thermals	Deflections in inches Forces in Grams										
	<u>0.0013</u>	<u>0.0026</u>	<u>0.0040</u>	<u>0.0053</u>	<u>0.0066</u>	<u>0.0079</u>	<u>0.0091</u>	<u>0.0105</u>	<u>0.0119</u>	<u>0.0132</u>	<i>SET</i>
<b>Averages</b>	0.03	0.03	0.04	10.53	49.93	95.61	132.81	186.04	231.06	277.24	0.0050
<b>Min</b>	-0.40	-0.40	-0.40	0.10	33.50	75.80	116.80	168.10	210.80	252.70	0.0045
<b>Max</b>	0.40	0.40	0.40	23.80	65.20	115.10	153.20	208.20	253.60	297.60	0.0055
<b>St. Dev</b>	0.314	0.314	0.318	9.135	11.273	13.416	12.461	12.998	13.503	13.736	0.0004
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

**DATA SUMMARIES Continued****Power pin right**

Initial	Deflections in inches Forces in Grams										
	<u>0.0013</u>	<u>0.0026</u>	<u>0.0040</u>	<u>0.0053</u>	<u>0.0066</u>	<u>0.0079</u>	<u>0.0091</u>	<u>0.0106</u>	<u>0.0119</u>	<u>0.0132</u>	<i>SET</i>
<b>Averages</b>	36.82	69.73	109.51	153.36	201.33	247.43	289.25	336.86	380.22	425.78	0.0002
<b>Min</b>	22.80	50.10	87.80	125.60	170.50	217.70	260.10	310.60	353.70	401.00	0.0000
<b>Max</b>	53.50	98.20	140.80	190.30	243.30	286.40	331.20	381.80	423.00	472.50	0.0004
<b>St. Dev</b>	8.928	14.084	15.450	15.996	18.233	17.295	18.052	18.181	17.335	17.935	0.0001
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

After Thermals	Deflections in inches Forces in Grams										
	<u>0.0013</u>	<u>0.0026</u>	<u>0.0040</u>	<u>0.0053</u>	<u>0.0066</u>	<u>0.0079</u>	<u>0.0091</u>	<u>0.0105</u>	<u>0.0119</u>	<u>0.0132</u>	<i>SET</i>
<b>Averages</b>	-0.08	-0.08	-0.09	16.72	56.76	100.47	135.74	184.26	225.75	267.83	0.0047
<b>Min</b>	-0.40	-0.40	-0.40	0.10	41.20	85.50	121.30	172.70	212.70	252.20	0.0041
<b>Max</b>	0.20	0.20	0.10	31.60	75.00	118.80	157.30	207.70	251.70	295.10	0.0051
<b>St. Dev</b>	0.175	0.159	0.144	8.685	8.635	8.709	9.198	10.250	11.438	12.893	0.0003
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

**NORMAL FORCE (FOR CONTACTS TESTED OUTSIDE THE HOUSING):**

- 1) Calibrated force gauges are used along with computer controlled positioning equipment.
- 2) Typically, 8-10 readings are taken and the averages reported.

**Signal pin row1 left**

Initial	Deflections in inches Forces in Grams										
	<u>0.0009</u>	<u>0.0018</u>	<u>0.0027</u>	<u>0.0040</u>	<u>0.0045</u>	<u>0.0054</u>	<u>0.0063</u>	<u>0.0072</u>	<u>0.0081</u>	<u>0.0090</u>	<i>SET</i>
<b>Averages</b>	13.54	26.05	36.53	56.00	63.43	74.13	86.21	99.74	111.98	123.45	0.0002
<b>Min</b>	12.20	22.00	31.20	47.60	53.60	63.60	75.30	86.90	98.50	110.20	0.0000
<b>Max</b>	15.40	29.40	40.40	61.30	67.90	80.80	94.80	108.70	121.30	133.60	0.0005
<b>St. Dev</b>	1.054	2.280	2.811	4.380	4.481	5.418	5.681	6.674	7.585	8.254	0.0001
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

After Thermals	Deflections in inches Forces in Grams										
	<u>0.0009</u>	<u>0.0018</u>	<u>0.0027</u>	<u>0.0040</u>	<u>0.0045</u>	<u>0.0054</u>	<u>0.0063</u>	<u>0.0072</u>	<u>0.0081</u>	<u>0.0090</u>	<i>SET</i>
<b>Averages</b>	3.43	16.12	27.78	48.28	55.64	67.06	81.05	95.52	108.02	121.13	0.0010
<b>Min</b>	-0.20	11.80	22.90	43.60	49.30	60.00	73.60	86.40	97.90	109.40	0.0005
<b>Max</b>	7.80	20.00	31.80	53.40	61.60	71.30	86.60	102.20	115.30	129.00	0.0016
<b>St. Dev</b>	2.928	3.018	3.158	3.626	4.345	3.798	3.925	4.691	5.390	6.027	0.0003
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

**DATA SUMMARIES Continued****Signal pin row1 right**

Initial	Deflections in inches Forces in Grams										
	<u>0.0009</u>	<u>0.0018</u>	<u>0.0027</u>	<u>0.0040</u>	<u>0.0045</u>	<u>0.0054</u>	<u>0.0063</u>	<u>0.0072</u>	<u>0.0081</u>	<u>0.0090</u>	<i>SET</i>
<b>Averages</b>	12.98	24.75	35.09	54.32	61.58	72.18	84.40	97.75	109.44	121.10	0.0003
<b>Min</b>	11.80	22.80	32.80	50.60	55.70	66.00	76.40	87.70	99.10	110.40	0.0001
<b>Max</b>	14.40	28.20	39.10	60.20	67.70	80.50	94.40	108.50	122.10	134.40	0.0004
<b>St. Dev</b>	0.887	1.798	1.687	2.758	3.326	4.073	4.513	5.104	5.776	6.070	0.0001
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

After Thermals	Deflections in inches Forces in Grams										
	<u>0.0009</u>	<u>0.0018</u>	<u>0.0027</u>	<u>0.0040</u>	<u>0.0045</u>	<u>0.0054</u>	<u>0.0063</u>	<u>0.0072</u>	<u>0.0081</u>	<u>0.0090</u>	<i>SET</i>
<b>Averages</b>	2.51	14.58	25.67	45.89	52.35	63.88	76.73	90.53	103.03	115.48	0.0011
<b>Min</b>	-0.30	9.40	20.20	40.50	45.40	57.00	67.80	81.50	93.90	104.00	0.0008
<b>Max</b>	8.50	18.40	31.20	53.00	60.50	73.80	88.10	104.60	118.30	131.90	0.0020
<b>St. Dev</b>	2.859	2.906	3.594	3.837	4.603	4.857	5.641	6.559	6.879	7.527	0.0003
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

**Signal pin row2 left**

Initial	Deflections in inches Forces in Grams										
	<u>0.0009</u>	<u>0.0018</u>	<u>0.0027</u>	<u>0.0040</u>	<u>0.0045</u>	<u>0.0054</u>	<u>0.0063</u>	<u>0.0072</u>	<u>0.0081</u>	<u>0.0090</u>	<i>SET</i>
<b>Averages</b>	12.77	24.58	35.79	55.90	63.22	74.17	86.78	100.83	113.36	125.12	0.0002
<b>Min</b>	11.20	22.20	32.50	50.10	56.30	67.40	79.10	92.30	103.60	115.50	0.0001
<b>Max</b>	15.80	27.70	38.70	62.00	69.50	81.50	94.70	107.90	120.60	131.90	0.0003
<b>St. Dev</b>	1.221	1.750	1.924	3.119	3.450	3.976	4.484	4.486	5.106	5.288	0.0001
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

After Thermals	Deflections in inches Forces in Grams										
	<u>0.0009</u>	<u>0.0018</u>	<u>0.0027</u>	<u>0.0040</u>	<u>0.0045</u>	<u>0.0054</u>	<u>0.0063</u>	<u>0.0072</u>	<u>0.0081</u>	<u>0.0090</u>	<i>SET</i>
<b>Averages</b>	3.74	15.73	26.84	46.29	53.55	64.59	77.20	91.49	104.93	117.43	0.0009
<b>Min</b>	-0.10	9.30	20.40	40.00	45.50	55.80	66.70	79.20	93.20	103.90	0.0006
<b>Max</b>	9.80	22.20	34.00	52.80	62.00	73.30	87.90	103.60	117.10	130.50	0.0012
<b>St. Dev</b>	3.192	3.844	4.039	4.853	6.280	6.185	7.399	8.369	8.330	8.647	0.0002
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

**Signal pin row2 right**

Initial	Deflections in inches Forces in Grams										
	<u>0.0009</u>	<u>0.0018</u>	<u>0.0027</u>	<u>0.0040</u>	<u>0.0045</u>	<u>0.0054</u>	<u>0.0063</u>	<u>0.0072</u>	<u>0.0081</u>	<u>0.0090</u>	<i>SET</i>
<b>Averages</b>	11.88	23.37	34.12	53.23	59.99	70.13	81.80	95.08	106.12	117.70	0.0003
<b>Min</b>	10.20	20.70	29.30	49.20	55.10	63.90	76.00	86.90	99.70	111.70	0.0001
<b>Max</b>	13.90	27.40	39.50	62.30	69.00	79.80	90.20	105.70	116.50	127.80	0.0004
<b>St. Dev</b>	1.054	2.021	2.622	3.546	3.893	4.486	4.365	5.415	5.402	5.149	0.0001
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

After Thermals	Deflections in inches Forces in Grams										
	<u>0.0009</u>	<u>0.0018</u>	<u>0.0027</u>	<u>0.0040</u>	<u>0.0045</u>	<u>0.0054</u>	<u>0.0063</u>	<u>0.0072</u>	<u>0.0081</u>	<u>0.0090</u>	<i>SET</i>
<b>Averages</b>	2.35	14.59	25.27	44.13	50.15	61.44	72.72	85.93	97.52	108.55	0.0012
<b>Min</b>	-0.10	10.20	19.10	39.10	45.50	56.30	66.40	79.60	89.50	100.00	0.0007
<b>Max</b>	5.00	17.70	29.60	50.20	55.40	68.40	80.80	95.80	108.80	118.80	0.0018
<b>St. Dev</b>	1.955	2.509	3.268	3.468	3.330	3.860	4.631	5.575	5.935	6.761	0.0004
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12



**DATA SUMMARIES Continued****Signal pin row3 left**

Initial	Deflections in inches Forces in Grams										
	<u>0.0009</u>	<u>0.0018</u>	<u>0.0027</u>	<u>0.0040</u>	<u>0.0045</u>	<u>0.0054</u>	<u>0.0063</u>	<u>0.0072</u>	<u>0.0081</u>	<u>0.0090</u>	<i>SET</i>
<b>Averages</b>	13.35	26.35	37.28	57.46	65.03	76.28	88.52	101.75	113.98	125.80	0.0002
<b>Min</b>	12.00	23.30	33.60	49.60	56.10	66.40	77.90	88.60	99.70	111.20	0.0000
<b>Max</b>	16.30	29.90	44.00	64.10	71.60	84.00	95.10	108.70	121.20	134.40	0.0003
<b>St. Dev</b>	1.146	1.939	2.711	4.251	4.407	5.415	5.782	6.909	7.495	7.890	0.0001
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

After Thermals	Deflections in inches Forces in Grams										
	<u>0.0009</u>	<u>0.0018</u>	<u>0.0027</u>	<u>0.0040</u>	<u>0.0045</u>	<u>0.0054</u>	<u>0.0063</u>	<u>0.0072</u>	<u>0.0081</u>	<u>0.0090</u>	<i>SET</i>
<b>Averages</b>	2.07	14.90	26.44	46.26	52.85	64.77	78.29	93.45	106.38	119.05	0.0010
<b>Min</b>	-0.10	11.20	22.50	39.80	45.80	56.80	68.30	83.00	96.10	109.40	0.0007
<b>Max</b>	7.70	19.00	30.50	51.10	58.70	70.20	83.40	99.40	112.70	124.90	0.0012
<b>St. Dev</b>	2.374	2.656	2.625	3.140	3.262	3.426	3.900	4.458	4.636	4.205	0.0002
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

**Signal pin row3 right**

Initial	Deflections in inches Forces in Grams										
	<u>0.0009</u>	<u>0.0018</u>	<u>0.0027</u>	<u>0.0040</u>	<u>0.0045</u>	<u>0.0054</u>	<u>0.0063</u>	<u>0.0072</u>	<u>0.0081</u>	<u>0.0090</u>	<i>SET</i>
<b>Averages</b>	12.10	23.35	33.69	52.48	59.59	69.54	81.58	94.51	105.62	116.98	0.0004
<b>Min</b>	11.00	21.10	31.50	48.30	54.70	64.40	76.30	86.30	98.10	110.00	0.0002
<b>Max</b>	13.50	26.30	36.10	55.30	63.30	74.10	87.00	100.20	112.70	122.70	0.0007
<b>St. Dev</b>	0.716	1.623	1.368	2.102	2.831	3.115	3.397	3.815	4.350	4.084	0.0002
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

After Thermals	Deflections in inches Forces in Grams										
	<u>0.0009</u>	<u>0.0018</u>	<u>0.0027</u>	<u>0.0040</u>	<u>0.0045</u>	<u>0.0054</u>	<u>0.0063</u>	<u>0.0072</u>	<u>0.0081</u>	<u>0.0090</u>	<i>SET</i>
<b>Averages</b>	1.90	13.08	23.68	42.57	49.68	61.10	72.91	86.38	98.88	111.42	0.0011
<b>Min</b>	-0.40	9.00	18.80	35.00	43.00	53.70	65.20	78.20	91.20	102.00	0.0007
<b>Max</b>	8.40	19.50	30.70	52.60	60.50	72.90	86.60	101.80	114.60	128.00	0.0015
<b>St. Dev</b>	3.221	3.795	4.175	4.703	4.632	4.937	5.804	5.904	5.966	6.595	0.0003
<b>Count</b>	12	12	12	12	12	12	12	12	12	12	12

**DATA SUMMARIES Continued****INSULATION RESISTANCE (IR):**

Pin to Pin			
	Mated	Unmated	Unmated
Minimum	ET60S/ET60T	ET60S	ET60T
Initial	10000	10000	10000
Thermal	10000	10000	10000
Humidity	5687	6581	6423

Pin to Power			
	Mated	Unmated	Unmated
Minimum	ET60S/ET60T	ET60S	ET60T
Initial	10000	10000	10000
Thermal	10000	10000	10000
Humidity	10000	10000	10000

Row2to Row2			
	Mated	Unmated	Unmated
Minimum	ET60S/ET60T	ET60S	ET60T
Initial	10000	10000	10000
Thermal	10000	10000	10000
Humidity	5981	6397	7284

Row1 to Row1			
	Mated	Unmated	Unmated
Minimum	ET60S/ET60T	ET60S	ET60T
Initial	10000	10000	10000
Thermal	10000	10000	10000
Humidity	5391	6259	6392

Power to Power			
	Mated	Unmated	Unmated
Minimum	ET60S/ET60T	ET60S	ET60T
Initial	10000	10000	10000
Thermal	10000	10000	10000
Humidity	5943	6853	7069

**DIELECTRIC WITHSTANDING VOLTAGE (DWV):**

Voltage Rating Summary	
Minimum	ET60S/ET60T
Break Down Voltage	1125
Test Voltage	844
Working Voltage	281

Pin to Pin	
Initial Test Voltage	Passed
After Thermal Test Voltage	Passed
After Humidity Test Voltage	Passed

Row to Row	
Initial Test Voltage	Passed
After Thermal Test Voltage	Passed
After Humidity Test Voltage	Passed

Pin to Ground	
Initial Test Voltage	Passed
After Thermal Test Voltage	Passed
After Humidity Test Voltage	Passed

Pin to Closest Metallic Hardware	
Initial Test Voltage	Passed
After Thermal Test Voltage	Passed
After Humidity Test Voltage	Passed

Ground to Closest Metallic Hardware	
Initial Test Voltage	Passed
After Thermal Test Voltage	Passed
After Humidity Test Voltage	Passed

**DATA SUMMARIES Continued****LLCR Durability:**

- 1) A total of 144 signal points and 48 power points were measured.
- 2) EIA-364-23, *Low Level Contact Resistance Test Procedure for Electrical Connectors and Sockets*.
- 3) A computer program, *LLCR 221.exe*, ensures repeatability for data acquisition.
- 4) The following guidelines are used to categorize the changes in LLCR as a result from stressing.
  - a.  $\leq +5.0$  mOhms:-----Stable
  - b.  $+5.1$  to  $+10.0$  mOhms:-----Minor
  - c.  $+10.1$  to  $+15.0$  mOhms:-----Acceptable
  - d.  $+15.1$  to  $+50.0$  mOhms:-----Marginal
  - e.  $+50.1$  to  $+2000$  mOhms-----Unstable
  - f.  $>+2000$  mOhms:-----Open Failure

<b>LLCR Measurement Summaries by Pin Type</b>				
Date	10/22/2012	10/27/2012	11/6/2012	11/17/2012
Room Temp (Deg C)	24	24	24	22
Rel Humidity (%)	52	52	52	56
Technician	Kason He	Kason He	Kason He	Kason He
mOhm values	<b>Actual</b>	<b>Delta</b>	<b>Delta</b>	<b>Delta</b>
	<b>Initial</b>	<b>100 Cycles</b>	<b>Therm Shck</b>	<b>Humidity</b>
<b>Pin Type 1: Signal</b>				
Average	14.20	0.20	0.21	0.38
St. Dev.	1.91	0.27	0.28	0.34
Min	10.34	0.00	0.00	0.01
Max	16.86	1.81	1.69	2.89
Summary Count	144	144	144	144
Total Count	144	144	144	144
<b>Pin Type 2: Power</b>				
Average	0.22	0.01	0.02	0.02
St. Dev.	0.01	0.01	0.01	0.01
Min	0.21	0.00	0.00	0.00
Max	0.26	0.06	0.04	0.06
Summary Count	48	48	48	48
Total Count	48	48	48	48

<b>LLCR Delta Count by Category</b>						
	<b>Stable</b>	<b>Minor</b>	<b>Acceptable</b>	<b>Marginal</b>	<b>Unstable</b>	<b>Open</b>
mOhms	$\leq 5$	$>5 \text{ \& } \leq 10$	$>10 \text{ \& } \leq 15$	$>15 \text{ \& } \leq 50$	$>50 \text{ \& } \leq 1000$	$>1000$
<b>100 Cycles</b>	192	0	0	0	0	0
<b>Therm Shck</b>	192	0	0	0	0	0
<b>Humidity</b>	192	0	0	0	0	0

**DATA SUMMARIES Continued****LLCR Thermal Aging:**

- 1) A total of 144 signal points and 48 power points were measured.
- 2) EIA-364-23, *Low Level Contact Resistance Test Procedure for Electrical Connectors and Sockets*.
- 3) A computer program, *LLCR 221.exe*, ensures repeatability for data acquisition.
- 4) The following guidelines are used to categorize the changes in LLCR as a result from stressing.
  - a.  $\leq +5.0$  mOhms: -----Stable
  - b.  $+5.1$  to  $+10.0$  mOhms:-----Minor
  - c.  $+10.1$  to  $+15.0$  mOhms: -----Acceptable
  - d.  $+15.1$  to  $+50.0$  mOhms: -----Marginal
  - e.  $+50.1$  to  $+2000$  mOhms: -----Unstable
  - f.  $>+2000$  mOhms:-----Open Failure

<b>LLCR Measurement Summaries by Pin Type</b>		
Date	10/25/2012	11/6/2012
Room Temp (Deg C)	24	24
Rel Humidity (%)	55	52
Technician	Kason He	Kason He
<b>mOhm values</b>	<b>Actual</b>	<b>Delta</b>
	<b>Initial</b>	<b>Thermal</b>
<b>Pin Type 1: Signal</b>		
Average	14.07	0.22
St. Dev.	1.93	0.27
Min	9.99	0.00
Max	16.74	1.35
Summary Count	144	144
Total Count	144	144
<b>Pin Type 2: Power</b>		
Average	0.20	0.02
St. Dev.	0.02	0.02
Min	0.15	0.00
Max	0.23	0.12
Summary Count	48	48
Total Count	48	48

<b>LLCR Delta Count by Category</b>						
	<b>Stable</b>	<b>Minor</b>	<b>Acceptable</b>	<b>Marginal</b>	<b>Unstable</b>	<b>Open</b>
<b>mOhms</b>	<b><math>\leq 5</math></b>	<b><math>&gt;5</math> &amp; <math>\leq 10</math></b>	<b><math>&gt;10</math> &amp; <math>\leq 15</math></b>	<b><math>&gt;15</math> &amp; <math>\leq 50</math></b>	<b><math>&gt;50</math> &amp; <math>\leq 1000</math></b>	<b><math>&gt;1000</math></b>
<b>Thermal</b>	<b>192</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>0</b>

**DATA SUMMARIES Continued****LLCR Gas Tight:**

- 1) A total of 144 signal points and 48 power points were measured.
- 2) EIA-364-23, *Low Level Contact Resistance Test Procedure for Electrical Connectors and Sockets*.
- 3) A computer program, *LLCR 221.exe*, ensures repeatability for data acquisition.
- 4) The following guidelines are used to categorize the changes in LLCR as a result from stressing.
  - a.  $\leq +5.0$  mOhms: -----Stable
  - b.  $+5.1$  to  $+10.0$  mOhms: -----Minor
  - c.  $+10.1$  to  $+15.0$  mOhms: -----Acceptable
  - d.  $+15.1$  to  $+50.0$  mOhms: -----Marginal
  - e.  $+50.1$  to  $+2000$  mOhms: -----Unstable
  - f.  $>+2000$  mOhms: -----Open Failure

<b>LLCR Measurement Summaries by Pin Type</b>		
Date	10/25/2012	11/23/2012
Room Temp (Deg C)	24	22
Rel Humidity (%)	55	58
Technician	Kason He	Kason He
mOhm values	<b>Actual Initial</b>	<b>Delta Acid Vapor</b>
<b>Pin Type 1: Signal</b>		
Average	13.68	0.20
St. Dev.	2.17	0.24
Min	7.68	0.00
Max	16.83	1.31
Summary Count	144	144
Total Count	144	144
<b>Pin Type 2: Power</b>		
Average	0.21	0.03
St. Dev.	0.02	0.02
Min	0.17	0.00
Max	0.26	0.12
Summary Count	48	48
Total Count	48	48

<b>LLCR Delta Count by Category</b>						
mOhms	Stable	Minor	Acceptable	Marginal	Unstable	Open
	$\leq 5$	$>5 \text{ \& } \leq 10$	$>10 \text{ \& } \leq 15$	$>15 \text{ \& } \leq 50$	$>50 \text{ \& } \leq 1000$	$>1000$
Acid Vapor	192	0	0	0	0	0

**DATA SUMMARIES Continued****LLCR Shock & Vibration:**

- 1). A total of 144 signal points and 48 power points were measured.
- 2). EIA-364-23, *Low Level Contact Resistance Test Procedure for Electrical Connectors and Sockets*.
- 3). The following guidelines are used to categorize the changes in LLCR as a result from stressing.
  - a.  $\leq +5.0$  mOhms: -----Stable
  - b.  $+5.1$  to  $+10.0$  mOhms: -----Minor
  - c.  $+10.1$  to  $+15.0$  mOhms: -----Acceptable
  - d.  $+15.1$  to  $+50.0$  mOhms: -----Marginal
  - e.  $+50.1$  to  $+2000$  mOhms -----Unstable
  - f.  $>+2000$  mOhms: -----Open Failure

<b>LLCR Measurement Summaries by Pin Type</b>		
Date	11/2/2012	11/6/2012
Room Temp (Deg C)	21	22
Rel Humidity (%)	34	32
Technician	Tony Wagoner	Tony Wagoner
mOhm values	<b>Actual Initial</b>	<b>Delta Shock-Vib</b>
<b>Pin Type 1: Power</b>		
Average	0.24	0.02
St. Dev.	0.02	0.02
Min	0.21	0.00
Max	0.29	0.08
Summary Count	48	48
Total Count	48	48
<b>Pin Type 2: Signal</b>		
Average	14.34	0.44
St. Dev.	2.19	0.53
Min	10.11	0.01
Max	18.62	2.78
Summary Count	144	144
Total Count	144	144

<b>LLCR Delta Count by Category</b>						
mOhms	Stable	Minor	Acceptable	Marginal	Unstable	Open
	$\leq 5$	$>5$ & $\leq 10$	$>10$ & $\leq 15$	$>15$ & $\leq 50$	$>50$ & $\leq 1000$	$>1000$
Shock-Vib	192	0	0	0	0	0

**Nanosecond Event Detection:**

<b>Shock and Vibration Event Detection Summary</b>	
Contacts tested	60
Test Condition	C, 100g's, 6ms, Half-Sine
Shock Events	0
Test Condition	V-B, 7.56 rms g
Vibration Events	0
Total Events	0

**EQUIPMENT AND CALIBRATION SCHEDULES****Equipment #:** HZ-TCT-01**Description:** Normal force analyzer**Manufacturer:** Mecmesin Multitester**Model:** Mecmesin Multitester 2.5-i**Serial #:** 08-1049-04**Accuracy:** Last Cal: 4/27/2012, Next Cal: 4/26/2013**Equipment #:** HZ-OV-01**Description:** Oven**Manufacturer:** Huida**Model:** CS101-1E**Serial #:** CS101-1E-B**Accuracy:** Last Cal: 12/13/2012, Next Cal: 12/12/2013**Equipment #:** HZ-THC-01**Description:** Humidity transmitter**Manufacturer:** Thermtron**Model:** HMM30C**Serial #:** D0240037**Accuracy:** Last Cal: 3/1/2012, Next Cal: 2/28/2013**Equipment #:** HZ-HPM-01**Description:** NA9636H**Manufacturer:** Ainuo**Model:** 6031A**Serial #:** 089601091**Accuracy:** Last Cal: 3/8/2012, Next Cal: 3/7/2013**Equipment #:** MO-04**Description:** Multimeter /Data Acquisition System**Manufacturer:** Keithley**Model:** 2700**Serial #:** 0798688**Accuracy:** Last Cal: 4/20/2012, Next Cal: 4/20/2013**Equipment #:** PS-11**Description:** Power Supply**Manufacturer:** Hewlett Packard / Agilent**Model:** AT-6032A**Serial #:** 3440A10457**Accuracy:** Last Cal: no calibrate, Next Cal: no calibrate**Equipment #:** HZ-MO-05**Description:** Micro-ohmmeter**Manufacturer:** Keithley**Model:** 3706**Serial #:** 1285188**Accuracy:** Last Cal: 11/15/2012, Next Cal: 11/14/2013

**EQUIPMENT AND CALIBRATION SCHEDULES****Equipment #:** HZ-TSC-01**Description:** Vertical Thermal Shock Chamber**Manufacturer:** Cincinnatti Sub Zero**Model:** VTS-3-6-6-SC/AC**Serial #:** 10-VT14994**Accuracy:** See Manual

... Last Cal: 06/28/2012, Next Cal: 06/27/2013

**Equipment #:** SVC-01**Description:** Shock & Vibration Table**Manufacturer:** Data Physics**Model:** LE-DSA-10-20K**Serial #:** 10037**Accuracy:** See Manual

... Last Cal: 11/30/2012, Next Cal: 11/30/2013

**Equipment #:** ACLM-01**Description:** Accelerometer**Manufacturer:** PCB Piezotronics**Model:** 352C03**Serial #:** 115819**Accuracy:** See Manual

... Last Cal: 07/09/2012, Next Cal: 07/09/2013

**Equipment #:** ED-03**Description:** Event Detector**Manufacturer:** Analysis Tech**Model:** 32EHD**Serial #:** 1100604**Accuracy:** See Manual

... Last Cal: 06/04/2012, Next Cal: 06/04/2013