



Cable Assembly Coaxial BNC to BNC RG-58C 60.0" (1.5m) 5.0'

RoHS Compliant

FEATURES

- 50Ω impedance
- BNC Plug to BNC Plug
- RG-58C



Product Description

Terminated with BNC male straight connector to BNC male straight connector for a durable, impedance match coaxial cable assembly. Gold plated contacts are utilized to minimize insertion loss.


General Specifications

Attribute	Value
Terminated/Unterminated	Terminated
Coaxial Type	RG-58C
Connector 1	BNC Plug
Connector 2	BNC Plug
Connector 1 Gender	Male
Connector 2 Gender	Male
Characteristic Impedance	50 Ω
Length	60.0" (1.5m) 5.0'
Voltage Rating	500 Vrms





Product Drawing



Features:

- The molded strain relief is directly bonded to the cable jacket for superior strength and durability.
- •PTFE insulation and nickel tarnish resistant outer shells used in the BNC connector provide long life and reliability.
- Gold-plated center contacts assure the most noise free connection possible.
- •The connectors and cable are impedance matched.

Dimensions: Millimeters (Inches)

Part Number Table

Cable Designation & Type:

RG58C/U, 50 Ohm cable makes it ideal for most test and measurement applications, RF transmission systems and Thinnet LAN applications.

Voltage:

500 Vrms max from center conductor to shield, and 30 Vac / 60 Vdc max from shield to earth in controlled hands-free testing environments.

Materials:

BNC male: Body – Brass, Tarnish Resistant Nickel Plating
Center Contact – Brass, Gold Plated Dielectric
– PTFE

Strain Relief: PVC molded directly to cable and connectors

Part Number	Description
9202399R0624	Cable Assembly Coaxial BNC to BNC RG-58C 6.00" (152.40mm)
9202400R0625	Cable Assembly Coaxial BNC to BNC RG-58C 12.00" (304.80mm)
9202390R0615	Cable Assembly Coaxial BNC to BNC RG-58C 24.00" (609.60mm)
9202383R0608	Cable Assembly Coaxial BNC to BNC RG-58C 36.00" (914.40mm)
9202403R0628	Cable Assembly Coaxial BNC to BNC RG-58C 48.0" (1.2m) 4.0'
9202392R0617	Cable Assembly Coaxial BNC to BNC RG-58C 60.0" (1.5m) 5.0'
9202385R0610	Cable Assembly Coaxial BNC to BNC RG-58C 72.0" (1.8m) 6.0'
9202389R0614	Cable Assembly Coaxial BNC to BNC RG-58C 96.0" (2.4m) 8.0'
9202393R0618	Cable Assembly Coaxial BNC to BNC RG-58C 120.0" (3.0m) 10.0'
9202413R0638	Cable Assembly Coaxial BNC to BNC RG-58C 144.0" (3.7m) 12.0'
9202405R0630	Cable Assembly Coaxial BNC to BNC RG-58C 180.0" (4.6m) 15.0'
9202423R0648	Cable Assembly Coaxial BNC to BNC RG-58C 240.0" (6.1m) 20.0'
9202406R0631	Cable Assembly Coaxial BNC to BNC RG-58C 300.0" (7.6m) 25.0'
9202412R0637	Cable Assembly Coaxial BNC to BNC RG-58C 360.0" (9.1m) 30.0'
9202430R0655	Cable Assembly Coaxial BNC to BNC RG-58C 600.0" (15.2m) 50.0'

Important Notice: This data sheet and its contents (the "Information") belong to the members of the EASE group of companies (the "Group") or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate, but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. EASE is the registered trademark of Ease Electronics Co., Limited 2019.